INCH-POUNDS

MIL-C-1318B
AMENDMENT 4
29 August 1997

SUPERSEDING
AMENDMENT 3
23 March 1993

MILITARY SPECIFICATION

CARTRIDGE CALIBER .50, TRACER, M17

This amendment forms a part of MIL-C-1318B, dated 3 April 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1, Under Drawings, U.S. Army Munitions Command, Delete the following:

"D7553544 - Packing and Marking: Cartridges, Cal .50, Bulk; Box, Ammunition M2A1, Box, Wirebound
D7573346 - Packing and Marking, Cartridge, Cal .50, Linked, Box, Ammunition, M2A1; Box, Wirebound
F8596993 - Packing and Marking, Cartridge, Cal .50, Linked, M15 or M15A1; Box, Ammunition, M2A1; Box, Wirebound"

2.1, Under Drawings, U.S. Army Munitions Command, Add the following:

" 9332394 - Packing and Marking, CRTGS, Cal.50; Linked; Box, Ammunition, M2A1
11740658 - Packing and Marking, Cartridges, Cal .50; Bulk, Box, Ammunition, M2A1
12576456 - Packing and Marking for Box, Wirebound for Cartridge, .50 Caliber
12576457 - Packing and Marking for Box, Ammo, M2A1 for Cartridge, .50 Caliber"

PAGE 3

* 3.4, Delete in its entirety and substitute:

"3.4 Residual stress. The cartridge shall not split when subjected to a 1% mercurous nitrate solution for 15 minutes when tested as specified in 4.5.3."

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

3.5, line 5, after "...4.5.4." Add: "Alternate method – The cartridge shall not release more than one bubble of air when subjected to a pressure differential of 7.5 pounds per square inch (psi) for thirty seconds when tested as specified in para. 4.5.4."

* 3.5, Delete “cartridge” and substitute “cartridges”.

3.6, Delete in its entirety and substitute:

“3.6 Accuracy. The average of the mean radii of all targets of the sample cartridges, fired at 600 yards, shall not exceed 20.0 inches or, when fired at 200 yards, shall not exceed 6.25 inches. The test shall be performed as specified in 4.5.5.”

3.6, Delete in its entirety and substitute:

"3.6 Accuracy. The average of the mean radii of all targets of the sample cartridges, fired at 600 yards, shall not exceed 12 inches when tested as specified in 4.5.5."

3.8, Delete in its entirety and substitute:

"3.8 Velocity. The average velocity of the sample cartridge, conditioned at 70 ft/sec, at 78 feet from the muzzle of the weapon. The standard deviation of the velocities shall not exceed 36 ft/sec when tested as specified in 4.5.7 and 4.5.12."

* 3.8, Delete in its entirety and substitute:

"3.8 Velocity. The average velocity of the sample cartridge, conditioned at 70° Farenheit, shall be 2910 ft/sec, plus or minus 30 ft/sec, at 78 ft from the muzzle of the weapon. The standard deviation of the velocities shall not exceed 36 ft/sec when tested as specified in 4.5.7."

PAGE 4

* 3.10, Delete in its entirety and substitute:

“3.10 Function and Casualty. The cartridge shall function without casualty. The test shall be performed as specified in 4.5.9.”

PAGE 5

4.3.1, Delete “Ctg. Cal .50, Ball, M33” and substitute “Ctg, Cal .50 Tracer, M17”

4.3.1, Delete “5/machine or tool” and substitute “5/tool/machine” in five places.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4.3.1, Delete “7638551” and substitute “12953486”.

* 4.3.1, Delete in its entirety and substitute:

"4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in the sample quantities indicated below.

PART DESCRIPTION	DRAWINGS	QUANTITY
Ctg, Cal .50, Tracer, M17	7672165	1800
Case	5502646	5/machine
Core	12953485	5/machine
Jacket	6174992	5/machine
Bullet	12953486	5/machine
Disc, Closure	7585150	5/machine"

PAGE 6

Table I, Add:

“8. Cyclic rate 0 2 /

2/ If any burst fails to meet the cyclic rate requirement specified in 3.10, the first article sample shall be rejected.”

* Table I, Delete:

“8. Cyclic rate 0 2 /

2/ If any burst fails to meet the cyclic rate requirement specified in 3.10, the first article sample shall be rejected.”

PAGE 7

Table II, NO. OF SAMPLE UNITS, Delete “5” and substitute “5/tool/machine” in five places.

Table II, Delete “7638551” and substitute “12953486”

* Table II, Delete in its entirety and substitute the following:

"TABLE II. First Article Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

Examination or Test	No. of Samples	AQL or 100%	Requirement Paragraph	Paragraph Reference
Case (Dwg 5502646) Exam for defects	5/ machine	Acc-0 Rej-1	3.1, 3.13	Gage 1/
Core (Dwg 12953485) Exam for defects	5/ machine	Acc-0 Rej-1	3.1, 3.13	Gage 1/
Jacket (Dwg 6174992) Exam for defects	5/ machine	Acc-0 Rej-1	3.1, 3.13	Gage 1/
Bullet (Dwg 12953486) Exam for defects	5/ machine	Acc-0 Rej-1	3.1, 3.13	Gage 1/
Disc, Closure (Dwg 7585150) Exam for defects	5/ machine	Acc-0 Rej-1	3.1, 3.13	Gage 1/
Ctg, Cal .50, Tracer, M17 (Dwg 7672165) Exam for defects	1880	Acc-0 Rej-1	3.1, 3.13	4.4.2.1

1/ To be inspected for all mandatory drawing requirements using standard measuring and test equipment (except workmanship which is inspected for visually)."

PAGE 8

* Table II, After	"Waterproofing	50	1/	3.5	4.5.4 and 4.5.12",
Add:	"Alternate Waterproofing	50	Acc-4 Rej-9"	3.5	4.5.4 and 4.5.12

PAGE 9

4.4.1.2, Delete subpara. "a" thru "d" in their entirety and substitute:

"a. Cartridge cases from one unchanged process and from one manufacturer.
b. Bullets from one unchanged process and from one manufacturer.
c. Primers from one lot interfix number and from one manufacturer.
d. Propellant from no more than two lot numbers and from one manufacturer."

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

PAGE 15

* 4.4.3.1, After “Waterproofing 20 3/ 3.5 4.5.4”,

Add: “Alternate Waterproofing 20 Acc-4 3.5 4.5.4 and 4.5.12
Rej-9
6/”

PAGE 17

4.4.3.1, Add:

" 6/ Failure of nine or more cartridges to comply with the requirement shall result in failure of the lot. If more than four but less than nine cartridges fail in the first test, a second sample consisting of double the number of cartridges in the first sample shall be tested. The lot shall be rejected if in the combined first and second sample, nine or more cartridges fail to comply with the applicable requirement."

PAGE 18

Table III, Add:

“8. Cyclic rate 0 5/ Major”

* Table III, Delete:

“8. Cyclic rate 0 5 /

PAGE 19

Table III, Notes, Add the following:

“5/ Failure of any burst to comply with the applicable requirement shall be cause for rejection of the lot subject to the testing of a second sample consisting of double the number of cartridges the first sample. Failure of any burst in the second sample to comply with the applicable requirement shall be cause for rejection of the lot. The second sample, if required, shall only be fired in the weapon type in which the failure occurred.”

* Table III, Notes, Delete the following:

“5/ Failure of any burst to comply with the applicable requirement shall be cause for rejection of the lot subject to the testing of a second sample consisting of double the number of cartridges the first sample. Failure of any burst in the second sample to comply with the applicable requirement shall be cause for rejection of the lot. The second sample, if required, shall only be fired in the weapon type in which the failure occurred.”

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

PAGE 20

4.5.4, Add at the end:

"Alternate Waterproofing: The ammunition to be tested (not to exceed five cartridges at one time) shall be placed horizontally on a perforated tray. The tray shall be placed in a desiccator containing a sufficient quantity of freshly boiled water to maintain a head of 2 to 2-1/2 inches. The desiccator shall be evacuated to a pressure of 7-1/2 pounds per square inch (15 inches of mercury) below atmospheric pressure for thirty seconds. The number of bubbles liberated from the mouth or primer of each cartridge shall be observed."

4.5.5, Add: "The size of the target shall be adjusted to suit the target range (200 or 600 yards)."

* 4.5.5, Delete: "The size of the target shall be adjusted to suit the target range (200 or 600 yards)."

4.5.7, Add: "Prior to this test the cartridge shall be temperature conditioned in accordance with 4.5.12."

* 4.5.9, Delete: "Observation for compliance with Tables I and III, as applicable, and the cyclic rate of each test weapon, shall be made. Cyclic rate of each weapon shall be recorded."

Substitute: "Observation for compliance with Table I and III, as applicable, shall be made. Cyclic rate of each weapon shall be recorded."

4.5.9, Change "revised" to "reused".

PAGE 22

* 5.2.1, Delete the following drawing numbers: "7553346, 7553544, 8596993" and substitute: "12576456."

* 5.3, Delete the following drawing numbers: "7553346, 7553544, 8596993" and substitute: "12576456"

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment are made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodian:
Army-AR
Air Force-70

Preparing activity:
Army-AR

(Project 1305-0178)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.