MIL-M-1315A
15 NOVEMBER 1950
SUPERSEDING
MIL-M-1315
3 August 1949

MILITARY SPECIFICATION

MACHINES, LINK LOADING AND DELINKING

This specification was approved by the Departments of the Army, the Navy, and the Air Force for use of procurement services of the respective Departments.

1. SCOPE

1.1 **Scope.**—This specification covers link loading and delinking machines to be used in assembling metallic belt links and ammunition to form flexible belts. Attachments provided are for disassembling the ammunition and the metallic belt links.

1.2 **Classification.** — Machines and attachments shall be of the following models, as specified (see 6.1):

Machine, link loading, caliber .30, M3.
Machine, linking-delinking, caliber .50, M7.
Linker-delinker, hand, caliber, .50, M12.
Attachment, delinking, caliber, .30, M8.

2. APPLICABLE SPECIFICATIONS, OTHER PUBLICATIONS, AND DRAWINGS

2.1 **Specifications.** — The following specifications and specifications referenced on drawings in 2.3, of the issue in effect on date of invitation for bids, form a part of this specification:

FEDERAL SPECIFICATIONS

NN-B-591 —Boxes; Wood-Cleated-Fiberboard.

NN-B-601 —Boxes; Wood-Cleated-Plywood, for Domestic Shipment.

NN-B-621 —Boxes; Wood, Nailed and Lock-Corner.

NN-B-631 —Boxes; Wood, Wirebound, for Domestic Shipment.

LLL-B-631—Boxes; Fiber, Corrugated (for Domestic Shipment).

LLL-B-636—Boxes; Fiber, Solid (for Domestic Shipment).

MILITARY SPECIFICATIONS

JAN-P-105—Packaging and Packing for Overseas Shipment — Boxes; Wood, Cleated, Plywood.

JAN-P-106—Packaging and Packing for Overseas Shipment — Boxes; Wood, Nailed.

JAN-P-108—Packaging and Packing for Overseas Shipment — Boxes; Fiberboard (V-Board and W-Board), Exterior and Interior.

JAN-P-116—Packaging and Packing for Overseas Shipment — Preservation, Methods of.

JAN-P-117—Packaging and Packing for Overseas Shipment — Bags, Interior Packing.

JAN-P-120—Packaging and Packing for Overseas Shipments—Carton, Folding, Paperboard.

JAN-P-125—Packaging and Packing for Overseas Shipment — Barrier Material, Waterproof, Flexible.

JAN-P-140—Packaging and Packing for Overseas Shipment — Adhesive, Water-Resistant, Case Liner.

905080—50—(291)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

U. S. ARMY SPECIFICATIONS

52–0–1 —General Specification Governing the Manufacture and Inspection of Small Arms Weapons, Spare and Replacement Parts, and Accessories.

94–40645 —Marking, Exterior, Domestic and Export Shipment, by Contractors.

100–2 —Standard Specification for Marking Shipments by Contractors.

(*Army.*—Copies of specifications should be obtained from the procuring agency or as directed by that agency. Both the title and identifying number or symbol should be stipulated when requesting copies.)

(*Navy.*—Copies of Federal, Military and Navy Department specifications may be obtained upon application to the Bureau of Supplies and Accounts, Navy Department, Washington 25, D. C., except that activities of the Armed Forces should make application to the Commanding Officer, Naval Supply Center, Norfolk 11, Va. Both the title and identifying number or symbol should be stipulated when requesting copies.)

(*Marine Corps.*—Copies of Federal, Military and Navy Department specifications may be obtained upon application to the Quartermaster General, Headquarters, U. S. Marine Corps, Navy Building, Washington 25, D. C., or to the Quartermaster Depot, Marine Corps Depot of Supplies, 1100 South Broad Street, Philadelphia 46, Pa. Both the title and identifying number or symbol should be stipulated when requesting copies.)

(*Air Force.*—Copies of Federal, Military and U. S. Army specifications may be obtained upon application to the Commanding General, Air Matériel Command, Wright-Patterson Air Force Base, Dayton, Ohio. Both the title and identifying number or symbol should be stipulated when requesting copies.)

2.2 Other publications. — The following publication, of the issue in effect on date of invitation for bids, forms a part of this specification:

BUREAU OF SUPPLIES AND ACCOUNTS PUBLICATION

Navy Shipment Marking Handbook.

(Copies of the Navy Shipment Marking Handbook may be obtained upon application to the Bureau of Supplies and Accounts, Department of the Navy, Washington 25, D. C., except that activities of the Armed Forces should make application to the Commanding Officer, Naval Supply Center, Norfolk 11, Va.)

2.3 Drawings. — The following drawings and drawings referenced thereon, of the issue in effect on date of invitation for bids, form a part of this specification:

U. S. ARMY ORDNANCE CORPS DRAWINGS

D35341 —Machine, Link Loading, Caliber, .30, M3 — List of Drawings and Specifications.

D7107071—Machine, Linking and Delinking, Caliber .50, M7—List of Drawings and Specifications.

D7161200—Linker-Delinker, Hand, Caliber .50, M12 — List of Drawings and Specifications.

D7162737—Attachment, Delinking, Caliber .30, M8.

(Copies of drawings should be obtained from the procuring agency or as directed by that agency. Both the title and identifying number or symbol should be stipulated when requesting copies.)

3. REQUIREMENTS

3.1 Design and construction.

3.1.1 *Materials.*—Materials shall be as specified on applicable drawings and in applicable specifications. Materials shall be free of any defects which affect appearance or functioning of equipment. Materials which are not covered by specifications or which are not specifically designated shall be of the best commercial quality suitable for the purpose intended.

3.1.2 *Components.*—All components shall be in accordance with this specification and the applicable requirements of Specification 52–0–1; and they shall conform to dimensions and tolerances specified on applicable drawings. Screws fastening permanent members shall be staked.

3.1.3 *Spare parts.*—Each lot of machines submitted for government inspection shall,

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

unless otherwise specified, be accompanied by the proportional quantity of acceptable spare parts. The quantity of spare parts to be furnished will be specified on lists furnished by the procuring agency.

3.1.4 *Protective finishes.*—All metal parts shall be given the protective finishes specified on applicable drawings and in applicable specifications.

3.1.5 *Interchangeability.*—All spare parts, components, and assemblies, which are maintained for replacement purposes, shall be interchangeable.

3.1.6 *Handbook of instructions.* — Unless otherwise specified, the contractor shall furnish two copies of a Handbook of Instructions sealed in a waterproof envelope securely attached to each machine supplied under this specification. Additional copies of the handbook and the mailing address to whom the additional copies are to be sent shall be specified (see 6.1). The face cover of each Handbook of Instructions shall be legibly and indelibly marked with the Manufacturers' serial number of the machine to which the handbook applies. The size and contents of the handbook shall be that normally furnished by the contractor in general commercial practice. The following is the preferred size and contents according to the nature or complexity in design and construction of the applicable machine:

a. Size of handbook, approximately 8 by 10½ inches. The cover and binding shall be of durable material such as to provide a reasonable life under normal conditions.

b. Index to the contents.

c. The contents shall include necessary photographs, line drawings, pictorial, or exploded views or assemblies, subassemblies, and parts identified by code or part number and completely covered by parts lists including vendors' items purchased from open market listed with vendors' name and part numbers; also lubrication (including types of lubricants), diagrams and instructions, instructions for periodic adjustments, safety, lifting, moving, installation, and operation according to the nature and complexity of the machine.

d. The contractor's ordering and repair data and instructions shall be conspicuously located in the handbook.

e. Any other data of instructions the contractor considers important to maintain efficient maintenance and operation of the machine including equipment.

3.1.7 *Workmanship.*—All machined surfaces shall have a smooth finish and all details of manufacture shall be in accordance with high grade commercial practice. All parts and assemblies shall be clean and free of chips, dirt, grease, or other foreign material. The cleaning method used shall not be injurious to parts or finishes nor shall the parts be contaminated by the cleaning agents used.

3.2 Functioning.—Finished machines shall operate smoothly and without interference or lost motion. Links and cartridges shall be firmly bedded.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 General procedures and inspection.

4.1.1 *Sampling.*

4.1.1.1 *Lot.*—Unless otherwise specified, a lot shall consist of not more than 100 machines or attachments of a type or kind together with a proportional quantity of spare parts. The contractor shall maintain an adequate system of lot identification so that the identity of all defective material can be maintained until reconditioned and accepted, accepted as a waiver or merit material, destroyed, or otherwise disposed of to the satisfaction of the Government.

4.1.1.2 *Size of samples.*—The size of sample for inspection shall be selected in accordance

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

with Specification 52–0–1. The size of sample for test shall consist of at least two machines from each lot.

4.1.2 *Inspection and tests, general.*

4.1.2.1 *Place.*—Unless otherwise specified, inspection and tests shall be made by a Government inspector at the place of manufacture.

4.1.2.2 *Rejection.*—The machines of a lot shall be rejected when more than 5 percent of the machines or components examined visually contain defects, or when any sample fails in the functioning test.

4.1.2.3 *Reinspection and retests.*—When requested by the contractor, a retest shall be made of any lot which fails in the functioning test, using twice the number of items in the sample from the lot as were used in the original test. Failure of any sample in the retest shall be cause for final rejection of the lot. Failure of any lot because of visual defects shall be cause for retest only after the contractor reinspects the lot and removes all defective parts. When more than 1 percent of the machines examined are found defective on the reinspection, the lot shall be subject to final rejection.

4.1.2.4 *Visual inspection.*—Each machine or attachment and spare part shall be inspected visually to determine completeness of design and construction including manufacture, assembly, finish, workmanship, and appearance. Before final acceptance the inspector shall inspect the packaging, packing, and marking to determine compliance with this specification.

4.2 Functioning test. — At least two machines from each lot shall be thoroughly tested for any malfunctioning directly traceable to the construction of the machine under test.

5. PREPARATION FOR DELIVERY

5.1 Preservation.—All unpainted metal surfaces shall be coated with type P–1 preservative conforming to Specification JAN–P–116. The rubber grips of the linker-delinker, hand, caliber .50, M12, shall not be coated.

5.2 Packaging.

5.2.1 *Machine, link-loading, caliber .30, M3.*—The machines, preserved as specified in 5.1, shall be packaged individually in snug-fitting fiberboard boxes conforming to Specification JAN–P–108. The machines shall be securely padded or blocked in the box.

5.2.2 *Machine, linking-delinking, caliber .50, M7.*—The machines shall be packaged as specified in 5.2.1.

5.2.3 *Linker-delinker, hand, caliber .50, M12.*—The linker-delinkers shall have the extractor extension spring disconnected from the extractor and the handles compressed to fit in the smallest possible space. The linker-delinkers shall be packaged individually in snug-fitting paperboard cartons conforming to Specification JAN–P–108.

5.2.4 *Attachment, delinking, caliber .30, M8.*—Attachments shall be so packaged as to prevent damage.

5.2.5 *Spare parts.* — Spare parts shall be packaged in greaseproof, waterproof bags conforming to Specification JAN–P–117. The quantities to be placed in the issue and intermediate packages shall be in accordance with lists furnished by the procuring agency.

5.3 Packing.

5.3.1 *For domestic shipment.*—Items shall be packed in wood-cleated-plywood, nailed and lock-corner wood, or wire-bound wood boxes conforming to Specification NN–B–601, NN–B–621, or NN–B–631, respectively. (Caseliner is not required.) When the contents

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

support all surfaces of the container or when interior blocking is used to maintain this support, the use of corrugated fiber or solid fiber boxes conforming to Specification LLL–B–636 or LLL–B–631, respectively, is permissible within the weight and size limitations of these specifications. Wood-cleated-fiberboard boxes conforming to NN–B–591 may also be used when the gross weight does not exceed 150 pounds.

5.3.2 *For overseas shipment.*—Items, packaged as specified in 5.2, shall be overpacked in snug-fitting wood cleated plywood boxes conforming to Specification JAN–P–105, or in nailed wood boxes conforming to Specification JAN–P–106. The gross weight of any overseas shipping container shall not exceed 200 pounds. Spare parts containers shall be lined with a case liner constructed of barrier material conforming to Specification JAN–P–125 and sealed with adhesive conforming to Specification JAN–P–140.

5.4 Labeling and marking.

5.4.1 *Identification.* — Each package, interior container, and exterior container shall be marked or labeled to clearly identify the item and the quantity contained therein. Each shipping container shall have the words "DOMESTIC PACK" stencilled or printed adjacent to the description of contents to indicate that contents have been packed for domestic shipment and storage. The letters shall be 1½ inches high, where possible, but never less than 1 inch.

5.4.2 *Shipping containers.*—In addition to any special marking required by the contract or order, shipments for the Army shall be marked in accordance with Specification 100–2; for the Navy, in accordance with the Navy Shipment Marking Handbook; and for the Air Force, in accordance with Specification 94–40645.

6. NOTES

6.1 Ordering data. — Procurements, documents should specify the following:

a. Title, number, and date of this specification.
b. Model required (see 1.2).
c. Title, number, and date of applicable drawings (see 2.3).
d. List of spare parts required (see 3.1.3).
e. List of spare parts in issue and intermediate packages (see 5.2.5).
f. Whether domestic or overseas packing is required (see 5.3).

Notice.—This specification, together with specifications and drawings pertaining to it and bearing a "Notice" of similar restrictions, is intended for use only in connection with procurement by the United States Government; and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement, nor be used for any other purpose except when specifically authorized by the Chief of Ordnance.

Custodian:
Army—Ordnance Corps
Other interest:
Army—T
Navy—O
Air Force.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.