MIL-P-1297B
8 JULY 1958
SUPERSEDING
MIL-P-1297A
12 AUGUST 1952

MILITARY SPECIFICATION

PISTOL, AUTOMATIC, CALIBER .45, M1911A1

This specification has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 This specification covers one type of caliber .45 semiautomatic, recoil operated, magazine fed pistol used as a defensive hand weapon.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

MILITARY

MIL-W-13855 — Weapons, Small Arms, General Specification for.

MIL-P-14232 — Packaging of Parts, Spare Parts, Equipment and Tools for Weapons and Fire Control General Specification for.

MIL-P-14313 — Pistols and Revolvers, Packaging of.

MIL-G-14461 — General Quality Control Requirements for Ordnance Materiel.

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-109 — Inspection Terms and and Definitions.

DRAWINGS

ORDNANCE CORPS

F7265655 — Pistol, Automatic, Caliber .45, M1911A1.

GL6113002 — Index to Lists of Acceptance Inspection Equipment and Parts.

PUBLICATIONS

ORDNANCE CORPS

LSQAP-7265655—Index of Supplementary Quality Assurance Provisions.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Production samples. On each contract samples of pistols and parts representing initial production shall be taken by the Government inspector and shall be forwarded prepaid by the contractor to a testing agency designated by the procuring activity (see 6.1). Samples shall be representative of material

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:06Z
Check the source to verify that this is the current version before use.

which has been inspected and approved by the Government inspector. The production samples shall be contained in the pilot pack (see 5.1).

3.2 **Materials and construction.** Pistols and parts shall conform to the materials, dimensions, tolerance limits, physical properties, degree of surface roughness, and final protective finishes specified on drawings listed on Drawing F7265655, and the materials and construction shall be in accordance with the applicable provisions of Specification MIL–W–13855.

3.3 **Design.** Pistols and parts shall conform to the design specified on drawings listed on Drawing F7265655, and this specification, and shall be in accordance with the applicable provisions of Specification MIL–W–13855.

3.3.1 *Barrel.* The barrel bore shall be free of cracks, seams, and pits. Scratches or marks, occurring in a chamber which otherwise meets the surface roughness requirements, shall be permitted provided they do not cause marks on the case of a high-pressure test cartridge fired in the chamber. Burrs and sharp edges shall be removed from chamber edges. The barrel shall be so fabricated that when the pistol is completely assembled, the requirements for targeting and accuracy hereinafter prescribed shall be met.

3.3.2 *Barrel bushing.* The barrel bushing shall assemble to and disassemble from the slide without the use of tools and when assembled and locked to the slide, it shall retain the recoil spring group in the pistol.

3.3.3 *Barrel link.* The barrel link shall be retained on the barrel lug by the link pin and shall move of its own weight throughout its full range of travel. It shall move the barrel into the locked and unlocked positions when the pistol is function fired or manually operated.

3.3.4 *Disconnector.* The disconnector shall move throughout its full range of travel when cammed downward by the slide or raised by action of the sear spring. It shall disengage the sear from the hammer when the trigger is pulled, and shall be disengaged from the sear by recoil of the slide when the pistol is function fired or manually operated.

3.3.5 *Ejector.* The ejector shall be retained on the receiver by the ejector pin and shall eject cartridge cases completely out of the pistol when the pistol is function fired or manually operated.

3.3.6 *Extractor.* The extractor shall be retained in the slide by the firing pin stop and shall extract cartridge cases from the barrel when the pistol is function fired or manually operated.

3.3.7 *Firing pin and firing pin spring.* The firing pin and the firing pin spring shall be retained in the slide by the firing pin stop. The firing pin spring shall hold the firing pin to the rear of the face of the firing pin hole in the slide before the hammer is released for firing and shall retract the firing pin into the slide after firing.

3.3.8 *Hammer.* The hammer shall be retained in the receiver by the hammer pin, shall move without binding throughout its full range of travel under spring action, and shall be securely engaged by the sear in the half cock or full cock position when the pistol is function fired or manually operated.

3.3.9 *Lanyard loop.* The lanyard loop shall be fastened securely in the mainspring housing by the lanyard loop pin without perceptible relative movement of these parts when manually examined.

3.3.10 *Magazine assembly and magazine catch.* The magazine shall be free of dents, cracks, sharp edges, and other defects which may affect functioning of either the magazine or the pistol. The magazine follower and the magazine catch shall function without binding throughout their full range of travel under spring action. The magazine shall fit in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:06Z
Check the source to verify that this is the current version before use.

receiver and shall be retained in place by the magazine catch. When the last round is fired, the magazine follower shall automatically position the slide stop to engage in the slide. When the magazine catch is depressed, it shall disengage the magazine and the magazine shall drop out of the receiver of its own weight.

3.3.11 *Receiver assembly.* The receiver assembly shall be free of cracks and functioning surfaces shall be free of burrs and sharp edges. The plunger tube and the stock screw bushings shall be fastened securely to the receiver without perceptible relative movement of these parts when manually examined.

3.3.12 *Safeties.*

3.3.12.1 *Safety lock.* The safety lock shall function without binding when moved to the "safe" and "fire" positions when the hammer is in the full cock position, and shall be retained in either position by the safety lock plunger until reset manually. When the safety lock is in the "safe" position, it shall prevent rotation of the sear and the hammer and shall block reaward movement of the slide.

3.3.12.2 *Grip safety.* The grip safety shall function without binding through its full range of travel under spring action and shall be normally held and returned to the "safe" position by action of the sear spring. When the grip safety is in the "safe" position, it shall prevent rearward movement of the trigger.

3.3.13 *Sear spring.* The sear spring shall be retained on the receiver by the mainspring housing and by spring action shall hold the grip safety in the "safe" position, position the disconnector, return the trigger to the forward position, and rotate the sear to engage the hammer.

3.3.14 *Sights.* The front and rear sights shall be fastened securely to the slide without perceptible relative movement of these parts when manually examined.

3.3.15 *Slide.* The slide shall function without binding through its full range of travel on the receiver guide ways as evidenced by manual examination.

3.3.16 *Slide stop.* The slide stop shall move readily from one position to the other, and shall be held in either position by the slide stop plunger. The slide stop shall be capable of being positioned to hold the slide in the rearward position manually and automatically by the action of the magazine follower after the last round has been fired. The slide stop shall hold the slide in the rearward position until it is depressed manually to disengage it from the slide.

3.3.17 *Stocks.* Stocks shall be fastened securely on the receiver by the stock screws without perceptible relative movement of these parts when manually examined. The stocks shall be free of splits, cracks, or other defects which may affect appearance or serviceability.

3.3.18 *Trigger assembly.* The trigger assembly shall move through its full range of travel under spring action without binding and after partial or complete trigger pull it shall return to its normal forward position under spring action immediately upon release when manually examined.

3.3.19 *Pistol assembly.*

3.3.19.1 With the magazine removed from the pistol and the slide fully retracted, the hammer shall not release when the slide is released and allowed to move forward into battery position while the trigger and grip safety are depressed. After the trigger is released and then depressed, the hammer shall release.

3.3.19.2 With the hammer in full cock position, the slide retracted approximately one-fourth inch, and the trigger and grip safety depressed, the hammer shall not release when the slide is released and allowed to move forward into battery position.

3.3.19.3 The hammer shall not release from the full cock position when the trigger is de-

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:06Z
Check the source to verify that this is the current version before use.

pressed without depressing the grip safety and while pushing forward on the hammer.

3.3.19.4 The hammer shall not release from the half cock position when the trigger and grip safety are depressed.

3.3.19.5 The hammer shall not go forward beyond the half cock position when the hammer is pulled back between the half cock and full cock position and then released.

3.3.19.6 The hammer shall not release from the full cock position when the trigger and the grip safety are depressed and the safety lock is in the "safe" position.

3.3.19.7 The hammer shall release from the full cock position when the safety lock and the grip safety are in the "fire" positions and the trigger is depressed.

3.3.20 *Breeching space.* The breeching space shall be within 0.904 to 0.925 inch when tested as specified in 4.4.1.

3.3.21 *Trigger pull.* The trigger pull shall be free of creep and within 5½ to 6½ pounds when tested as specified in 4.4.2. Creep shall be interpreted to mean any perceptible irregular movement between the time positive resistance is met and the hammer is released.

3.3.22 *Firing pin indent.* The firing pin indent shall be within 0.012 to 0.018 inch and it shall not be off center more than one-half the diameter of the firing pin striker point when tested as specified in 4.4.3.

3.3.23 *Interchangeability.* Unless otherwise specified on the drawings, all parts shall be interchangeable. Pistols and repair parts shall be capable of meeting the interchangeability tests specified in 4.3.3.1.4 and 4.3.3.2.1. (In normal assembly operations there shall be no objections interposed to preferential assembly of parts provided that all parts are dimensionally acceptable.)

3.3.24 *High-pressure resistance.* Each pistol shall be capable of withstanding the high-pressure resistance test specified in 4.4.5. Parts shall be free of cracks, seams, and other injurious defects after proof firing as evidenced by visual and magnetic particle inspection.

3.3.25 *Functioning.* Each pistol shall operate without malfunctions or unserviceable parts when tested as specified in 4.4.6.

3.3.26 *Targeting and accuracy.* At a range of 15 yards, at least 4 shots out of a series of 7 shots shall be within or cut the edge of the sighting image, and the center of impact of the 7-shot group shall not be located more than 4 inches radially from the center of the sighting image to qualify for targeting; and the 7-shots shall be within or cut the edge of a 4-inch diameter circle to qualify for accuracy when tested as specified in 4.4.7.

3.3.27 *Endurance.* Each pistol shall be capable of passing a 5,000-round endurance test as specified in 4.4.8 with not more than the number of malfunctions, nonacceptable conditions, and unserviceable parts allowed in table I.

3.4 **Marking.** Each pistol shall be clearly marked in accordance with the applicable drawings and Specification MIL–W–13855.

3.5 **Workmanship.** Workmanship shall be in accordance with the requirements of Specification MIL–W–13855.

4. QUALITY ASSURANCE PROVISIONS

4.1 **General quality assurance provisions.** The quality assurance provisions contained herein, together with those contained in applicable specifications and supplementary quality assurance provisions (SQAP's) listed on the Index of Supplementary Quality Assurance Provisions LSQAP–7265655, cover the Government prescribed inspection for assurance that the established requirements have been met. Such inspection shall be performed by the contractor under Government surveillance, or by the Government when so speci-

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:06Z
Check the source to verify that this is the current version before use.

fied. Whenever the term "inspector" is used herein, it denotes Government inspector. Where there is satisfactory evidence of high quality of the product which is a definite result of the contractor's quality control system, the amount of Government examination may be adjusted to a minimum.

4.1.1 *Contractor's quality control system.* The contractor shall provide and maintain a quality control system in accordance with Specification MIL–G–14461. The contractor's quality control system shall, as a minimum, provide control of all requirements specified for examination and testing herein regardless of any inspection which the Government may elect to perform. The inspection procedures and equipment specified herein shall prevail in case of dispute as to the adequacy of the contractor's quality control system.

4.1.2 *Government verification.* All quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification shall consist of surveillance of the operations to determine whether the practices, methods, and procedures of the written inspection plan are being properly applied, and Government product inspection to measure quality of product offered for acceptance. Deviation from the prescribed or agreed upon procedures, or instances of poor practices which might have an effect upon the quality of the product will be immediately called to the attention of the contractor. Failure of the contractor to promptly correct deficiencies discovered will be cause for suspension of acceptance until correction has been made or until conformance of product to prescribed criteria has been demonstrated. To avoid interference with operations, the contractor will designate a responsible official or officials to whom the Government inspector will report such instances.

4.1.3 *Inspection terms and definitions.* Inspection terms and definitions used herein are in accordance with Standard MIL–STD–109.

TABLE I. *Malfunctions, nonacceptable conditions, and broken parts* [1]

Malfunctions and nonacceptable conditions	Number permitted in the endurance test	
	First 2,500 rounds	Second 2,500 rounds
Disconnector fails to function	0	0
Failure of sear to release	0	0
Failure to extract	0	0
Failure to eject	1	0
Failure to close	0	2
Faulty trigger pull	0	No penalty
Grip safety fails to function	0	0
Light blow	0	0
Magazine catch fails to function	0	0
Misfire	1	1
Pierced primers	1	1
Primers, setback	0	0
Safety lock fails to function	0	0
Slide stop fails to function	0	0
Uncontrolled fire	0	0
Other malfunctions and nonacceptable conditions.	2	4
Broken or unserviceable parts		
Barrel lug, broken or burred	0	0
Extractor, broken or burred	0	0
Ejector, broken or burred	0	0
Firing pin hole, enlarged	0	0
Firing pin, broken	0	1
Link, broken	0	0
Locking lugs, chipped or burred (barrel or slide).	0	0
Springs, broken or set	0	0
Stock screws, loose	0	0
Other broken parts	1	2
Magazine failures		
Bent side walls	0	0
Bent or cracked lips	0	0
Failure to feed (due to follower)	0	1
Follower distorted	0	1
Inability to load seven rounds	0	0
Other magazine failures	0	0

[1] When malfunctions are traceable to particular parts, it is permissible to replace such parts and record them as unserviceable, subject to limitations of table I. When it is definitely established by the inspector that previously recorded malfunctions are attributable to an unserviceable part, such malfunctions shall not be counted against the pistol being tested, provided that they occurred not more than 200 rounds prior to replacement of the unserviceable part. These 200 rounds shall have been fired with the unserviceable part. However, such malfunctions shall remain recorded and properly identified. An unserviceable part is one that causes malfunctions or impairs the safety of the weapon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:06Z
Check the source to verify that this is the current version before use.

4.2 Preliminary inspection.

4.2.1 *Pistols and parts.* Inspection of production samples (see 3.1) shall be performed at the designated testing agency. Production samples shall be subjected to the inspection specified herein and such other inspection as is necessary to determine compliance with the requirements of the contract.

4.2.2 *Pilot pack.* Inspection of the pilot pack shall be in accordance with the applicable provisions of Specification MIL–P–14313.

4.3 Inspection provisions.

4.3.1 *Inspection lot.*

4.3.1.1 *Pistols.* The number of pistols in an inspection lot shall be either 500 or one month's production, whichever is smaller. Pistols shall be assembled from lots of component parts that have met all inspection requirements specified herein. Endurance test lot size shall be as specified in 4.3.3.1.4.

4.3.1.2 *Component parts and repair parts.* The formation, size, and presentation of inspection lots of parts shall be in accordance with Standard MIL–STD–105. The inspector shall insure that inspection lots are as large as practicable, in consideration of quality history, manufacturing conditions, and contractor's delivery schedule, and within the limitations of Specification MIL–W–13855.

4.3.1.3 *Packaging.*

4.3.1.3.1 *Pistols.* Inspection lot sizes for packaging of pistols shall be in accordance with Specification MIL–P–14313.

4.3.1.3.2 *Repair parts.* Inspection lot sizes for packaging of repair parts shall be as specified in 4.3.1.2.

4.3.2 *Examination.*

4.3.2.1 *Pistols.* Pistols shall be examined for completeness of manufacture, assembly, finish, and workmanship in accordance with SQAP–7265655. Pistols which have passed all examinations after successful completion of testing shall be stamped by the inspector with the Department of Defense complete inspection approval stamp as specified on the applicable drawing.

4.3.2.2 *Component parts and concurrent repair parts.* Examination of parts shall be performed in accordance with the applicable SQAP's listed on the Index of Supplementary Quality Assurance Provisions LSQAP–7265655. The contractor's examination of parts shall be accomplished prior to their assembly into the end item.

4.3.2.3 *Packaging.*

4.3.2.3.1 *Pistols.* Examination of packaging of pistols shall be performed in accordance with Specification MIL–P–14313.

4.3.2.3.2 *Repair parts.* Examination of packaging of repair parts shall be performed in accordance with the applicable SQAP's.

4.3.3 *Testing.*

4.3.3.1 *Pistols.*

4.3.3.1.1 *High-pressure resistance, function firing, and targeting and accuracy firing testing.* The contractor shall test each pistol for high-pressure resistance, function firing, and targeting and accuracy firing using the test methods specified in 4.4.5, 4.4.6, and 4.4.7 respectively. Pistols failing to meet any of the requirements shall be rejected.

4.3.3.1.2 *Breeching space testing.* The contractor shall test each pistol for breeching space using the test methods specified in 4.4.1. Pistols failing to meet the requirements shall be rejected.

4.3.3.1.3 *Trigger pull and firing pin indent testing.* The contractor shall test a sample of ten pistols selected by the inspector from each inspection lot for trigger pull and firing pin

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:06Z
Check the source to verify that this is the current version before use.

indent using the test methods specified in 4.4.2 and 4.4.3 respectively. Failure of any pistol to meet the requirements shall cause rejection of the represented lot.

4.3.3.1.4 *Interchangeability testing.* The inspector shall subject a sample of ten pistols from each inspection lot to interchangeability testing. Pistols taken for interchangeability testing shall have been found satisfactory in all other examinations and tests. Test frequency may be reduced to not less than one test of ten pistols each month when a record of consistently satisfactry results has been established. The ten pistols shall be tested for and shall comply with the requirements for breeching space, trigger pull, and firing pin indent before and after interchanging of parts, using the test methods specified in 4.4.1, 4.4.2, 4.4.3, and 4.4.4 respectively, and in addition, the pistols shall be tested for function firing and targeting and accuracy firing after interchanging of parts using the test methods specified in 4.4.6 and 4.4.7. Hand fitting of parts will be allowed on not more than two pistols during interchanging of parts provided that no part is altered beyond drawing requirements. No malfunctions shall be allowed in the function firing test and failure of not more than two pistols shall be allowed in the targeting and accuracy firing test. Failure of the interchangeability test shall cause retest or rejection of the represented lot. At the discretion of the inspector, an interchangeability retest may be allowed without reconditioning the lot of pistols. Failure in the retest shall cause rejection of the represented lot subject to reconditioning and further test as a reconditioned lot. A sample of 20 pistols from each retest or reconditioned lot shall be tested using the same procedure described above except that hand fitting and failure in the targeting and accuracy firing will be allowed on not more than 4 pistols.

4.3.3.1.5 *Endurance testing.*

4.3.3.1.5.1 *Lot size.* The first five endurance test lots shall each consist of 500 pistols or a month's production, whichever is smaller. When five successive lots meet the requirements, the lot size shall be increased to 2,500 pistols or a month's production, whichever is smaller. When five successive lots of the increased lot size have met the requirements, the lot size shall be further increased to 5,000 pistols or a month's production, whichever is smaller. If rejection of a lot occurs at any time, the next smaller test lot size criteria shall be reinstated and the above procedure repeated in returning to the larger lot size.

4.3.3.1.5.2 *Procedure.* One pistol and ten magazines selected by the inspector from each endurance lot shall be tested by the contractor for endurance using the test methods specified in 4.4.8. The contractor shall provide replacement parts as required to complete the test. Failure of the pistol to meet the requirements shall cause retest or rejection of the represented lot. Endurance retests shall be as specified in Specification MIL–W–13855 except that 2 pistols and 20 magazines shall be taken from each lot under consideration and tested using the test methods specified in 4.4.8. Failure of any pistol in the retest to meet the requirements shall cause rejection of the represented lot subject to reconditioning and further test as a reconditioned lot. Sample size and test methods for reconditioned lots shall be the same as for retest.

4.3.3.2 *Component parts and concurrent repair parts testing.* Raw material testing, part testing, and certification shall be performed in accordance with the applicable SQAP's. This will include chemical analysis and physical tests of materials, and tests of protective finish, heat treatment, bonding, and function of parts as applicable. The contractor shall accomplish these tests prior to assembly of parts into the end item.

4.3.3.2.1 *Concurrent repair parts interchangeability testing.* The inspector shall subject concurrent repair parts to the interchangeability test specified in Specification MIL–W–13855.

4.3.3.3 *Packaging.*

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:06Z
Check the source to verify that this is the current version before use.

4.3.3.3.1 *Pistols.* Testing of packaging of pistols shall be performed in accordance with Specification MIL–P–14313.

4.3.3.3.2 *Repair parts.* Testing of packaging of repair parts shall be performed in accordance with the applicable SQAP's.

4.3.4 *Inspection equipment.*

4.3.4.1 List of Government acceptance inspection equipment applicable to examination and testing of parts and pistols is contained in the Index to Lists of Acceptance Inspection Equipment and Parts, Drawing GL6113002.

4.3.4.2 Applicable measuring and testing equipment provisions are contained in Specification MIL–G–14461. The Government inspector shall determine that the contractor has available and utilizes correctly, gaging, measuring, and test equipment of required accuracy and precision and that the instruments are of proper type and range to make measurements of the required accuracy. The contractor shall have available a set of master gages, standards, and appropriate instruments for regularly scheduled calibration of his inspection equipment. Records of such regularly scheduled calibration shall be maintained by the contractor and made available for review by the Government. The calibration of gages, standards, and instruments will be periodically checked by authorized Government personnel.

4.3.4.3 Government standard caliber .45 high-pressure test ammunition shall be used in the high-pressure resistance test. Government standard caliber .45 service ball ammunition shall be used in all other firing tests.

4.4 **Test methods.**

4.4.1 *Breeching space.* Pistols shall be gaged for breeching space requirement (see 3.3.20) after proof firing, prior to acceptance, using the inspection equipment in accordance with Drawing B6045103. The pistol shall be held in a horizontal position, the gage inserted in the barrel chamber while the slide is held open, and the slide manually returned to battery position. The minimum gage and the maximum gage shall be used on each pistol. When the minimum gage is used the slide shall fully close and when the maximum gage is used the slide shall not fully close. Only light finger pressure shall be applied to the slide during this test.

4.4.2 *Trigger pull.* Pistols shall be tested for trigger pull requirement (see 3.3.21) using inspection equipment of the contractor's design, drawings of which shall be furnished the responsible technical agency (see 6.2). A magazine shall be inserted in the pistol, the hammer shall be in the full cock position, and the safety lock and grip shall be in the "off" position when the load is gradually applied at the middle of the trigger bow and exerted in a line parallel to the axis of the barrel bore. When the minimum load is applied the hammer shall not release and when the maximum load is applied the hammer shall release. The hammer shall be recocked each time after a load is applied. The trigger pull shall also be tested for creep by applying pressure manually to the trigger at a uniform rate of increase over a period of not less than 3 seconds.

4.4.3 *Firing pin indent.* Pistols shall be tested for firing pin indent requirement (see 3.3.22) using the prescribed copper compression cylinder inserted in the recess of a holding fixture in accordance with Drawing C5520037. The pistol shall be held in a horizontal position and the holding fixture inserted in the barrel chamber while the slide is held open. The slide shall be manually returned to battery position and the trigger pulled to release the hammer. The indent shall be taken on three compression cylinders for each pistol. The indent shall be computed by measuring the distance from the original surface of the cylinder (before indentation) to the bottom of the firing pin impression. The average of the three indents shall be computed and the resulting value shall be the basis for acceptance or rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:06Z
Check the source to verify that this is the current version before use.

4.4.4 *Interchange of parts.* Pistols shall be tested for interchange of parts (see 3.3.23) by disassembling and then reassembling parts using the parts and prearranged system prescribed in SQAP 7265655.

4.4.5 *High-pressure resistance (proof-firing).*

4.4.5.1 Pistols shall be tested for high-pressure resistance requirement (see 3.3.24) by firing one round of Government standard high-pressure test ammunition. Proof firing shall be accomplished with the pistol held in a fixture simulating hand firing and has a protective shield of the contractor's design, drawings of which shall be furnished the responsible technical agency (see 6.2). Pistols shall be visually examined for cracks, deformation, and other evidence of damage and cartridge cases shall be visually examined for bulges, splits, rings, and other defects caused by defective barrels. Proof marks shall be applied as indicated on the applicable drawings on pistols that have passed this test.

4.4.5.2 Each barrel and slide shall be magnetic particle inspected as prescribed on the applicable drawings after proof firing, prior to acceptance, for evidence of cracks, seams, and other injurious defects. Magnetic particle inspection marks shall be applied as indicated on the applicable drawings on pistols that have passed this inspection.

4.4.6 *Function firing.* The pistols shall be tested for functioning requirement (see 3.3.25) by firing seven rounds of ammunition from a fully loaded magazine. Function firing shall be accomplished with the pistol held in a fixture simulating hand firing of the contractor's design, drawings of which shall be furnished the responsible technical agency (see 6.2). The magazine used shall be one to be shipped with the pistol. The first three rounds shall be fired slowly (each shot being deliberately spaced at approximately 2 second intervals); and the last four rounds shall be fired in rapid succession.

4.4.7 *Targeting and accuracy firing.* The pistols shall be tested for targeting and accuracy requirement (see 3.3.26) by firing seven rounds of ammunition from a fully loaded magazine with the pistol sights alined at 6 o'clock on a 3-inch circle (sighting image). Targeting and accuracy firing shall be accomplished with the pistol held in a fixture of the contractor's design, drawings of which shall be furnished the responsible technical agency (see 6.2). The target shall be checked to determine whether the targeting and accuracy requirements have been met.

4.4.8 *Endurance.*

4.4.8.1 Pistols shall be tested for endurance requirement (see 3.3.27) by firing 5,000 rounds of ammunition. Firing shall be accomplished with the pistol held in a fixture simulating hand firing of the contractor's design, drawings of which shall be furnished the responsible technical agency (see 6.2). Firing shall be in series of approximately 500 rounds using fully loaded magazines whenever possible. The first series shall be fired slowly (each shot being deliberately spaced at approximately 2 second intervals); and the remaining series shall be fired slowly or in rapid succession at the discretion of the inspector.

4.4.8.2 The pistol shall be cleaned and oiled after each series of approximately 500 rounds and at the close of each day's firing, but no part shall be altered. Only parts broken or worn to the extent that they are unserviceable shall be replaced.

4.4.8.3 A complete record shall be kept for each endurance test, showing each malfunction and part replacement including the number of the round at which each occurred.

4.4.8.4 The entire 5,000 rounds shall be fired in the initial test pistol from each endurance lot, regardless of the number of malfunctions or unserviceable parts.

4.4.8.5 Upon completion of the endurance test, the contractor may recondition the test

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:06Z
Check the source to verify that this is the current version before use.

pistols. Reconditioned pistols shall meet all of the requirements of this specification. Test pistols not suitably reconditioned shall be scrapped.

5. PREPARATION FOR DELIVERY

5.1 Pilot pack. A pilot pack shall be furnished in accordance with the applicable provisions of Specification MIL–P–14313.

5.2 Pistols. Pistols shall be prepared for delivery in accordance with Specification MIL–P–14313.

5.3 Repair parts. Repair parts shall be prepared for delivery in accordance with Specification MIL–P–14232 and other applicable documents.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.

(b) Lists of drawings and specifications pertinent to the pistol, showing applicable revision dates.

(c) Index of supplementary quality assurance provisions pertinent to the pistol, showing applicable revision dates.

(d) Index to lists of acceptance inspection equipment and parts pertinent to the pistol, showing applicable revision dates.

(e) Number of production samples required for tests (see 3.1).

(f) Shipping instruction for production samples (see 3.1).

(g) Applicable packaging instructions (see 5.2 and 5.3).

(h) Place of final inspection and acceptance. See "Notes" in Specification MIL–W–13855.

(i) Responsibilities for furnishing acceptance inspection equipment.

(j) Responsibilities for furnishing ammunition. See "Notes" in Specification MIL–W–13855.

(k) Quantity, shipping instructions, and test procedures for pistols and parts when an interplant interchangeability test is required.

(l) Procedures and methods for demilitarizing and disposing of rejected material.

(m) Disposition of Government furnished property including used ammunition components and packing materials.

6.2 Drawings of contractor's design for test fixtures should be forwarded to Springfield Armory, Springfield 1, Mass. Attn.: ORDBD–EG.

Notice. This specification, together with specifications and drawings pertaining to it and bearing a "Notice" of similar restrictions, is intended for use only in accordance with procurement by the United States Government, and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement, nor be used for any other purpose except when specifically authorized by the Chief of Ordnance, Department of the Army.

Custodians:
Army—Ordnance Corps
Navy—Bureau of Ordnance
Air Force

Other interest:
Navy—MC

Preparing activity:
Army—Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:06Z
Check the source to verify that this is the current version before use.