MIL-P-1299B
25 June 1975
SUPERSEDING
MIL-P-1299A
29 Aug 1955

MILITARY SPECIFICATION

PISTOL, PYROTECHNIC, AN-M8 AND MOUNT, M1

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of double-action single-loaded pyrotechnic pistol and mount known as Pistol, Pyrotechnic, AN-M8 and Mount, M1 (see 6.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

	Military		
	MIL-W-13855	-	Weapons, Small Arms and Aircraft Armament Subsystems, General Specification for.
*	MIL-P-14232	-	Parts, Equipment and Tools for Army Material, Packaging and Packing of.
*	MIL-I-45607	-	Inspection Equipment, Acquisition, Maintenance and Disposition of.

STANDARDS

	Military		
	MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
	MIL-STD-109	-	Quality Assurance Terms and Definitions.

FSC 1095

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:07Z
Check the source to verify that this is the current version before use.

DRAWINGS

Rock Island Arsenal
F-7265657 - Pistol, Pyrotechnic, AN-M8 and Mount, M1.

PUBLICATIONS

Rock Island Arsenal
P7265657 - Packaging Data Sheet for Pistol, Pyrotechnic, AN-M8 and Mount, M1.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

* 3.1 First article. Requirements for submission of first article shall be as specified in the contract (see 6.2). Unless otherwise specified (see 6.2), the first article shall include the pilot pack (see 5.1).

* 3.2 Materials, construction and design. The pistol and mount shall conform to the material, construction and design requirements specified herein, on drawing F7265657 and in MIL-W-13855.

3.2.1 Breech safety. The breech operating mechanism shall include a breech safety which shall prevent firing of the pistol unless the breech is securely locked. Testing shall be as specified in 4.5.3.2.

* 3.2.2 Trigger pull. Trigger pull shall be smooth and within a range of five to eight pounds. Testing shall be as specified in 4.5.3.3.

* 3.2.3 Mount impact. The mount shall be capable of absorbing the full dynamic recoil energy equivalent of the firing of a Government standard pyrotechnic cartridge, and have a remaining availability of 1/8 inch more of recoil distance. Testing shall be as specified in 4.5.3.4.

* 3.2.4 Assembleability. The pistol and mount shall be capable of interface assembly. Testing shall be as specified in 4.5.3.7.1.

3.3 Performance characteristics.

* 3.3.1 Functioning. The pistol and mount shall operate without malfunctions or unserviceable parts when the pistol is subjected to being dry snapped five times and fired once using a Government standard pyrotechnic cartridge. Testing shall be as specified in 4.5.3.5.

Source: https://assist.dla.mil - Downloaded: 2026-10-16T13:07Z
Check the source to verify that this is the current version before use.

3.3.2 Endurance.

* 3.3.2.1 Pistol. The pistol shall be capable of dry snapping 3000 times and firing 50 Government standard pyrotechnic cartridges without malfunction or unserviceable components. Testing shall be as specified in 4.5.3.6.1.

* 3.3.2.2 Mount. The mount shall be capable of withstanding the pistol recoil during firing of 100 Government standard pyrotechnic cartridges without malfunction or unserviceable components. Testing shall be as specified in 4.5.3.6.2.

* 3.4 Interchangeability. Unless otherwise specified, all parts shall be interchangeable. Testing shall be as specified in 4.5.3.7.

* 3.5. Marking. The pistol and mount shall be marked in accordance with MIL-W-13855. The pistol and the mount shall be identified by a serial number issued by the procuring activity (see 6.2)

* 3.6 Workmanship. The workmanship shall be in accordance with MIL-W-13855.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 Quality assurance terms and definitions. Quality assurance terms and definitions used herein are in accordance with MIL-STD-109.

* 4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

* 4.4 First article inspection. The first article (initial production unit(s) shall be submitted for inspection in accordance with the contract (see 6.2). The first article shall be representative of the production processes to be used during quantity production. The first article shall be subjected to the quality conformance inspection specified herein and such other inspection as necessary to determine that all requirements of the contract have been met.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:07Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance inspection.

* 4.5.1 Inspection lots. The formation, size, and presentation of inspection lots of pistols and mounts shall be in accordance with MIL-STD-105 and MIL-W-13855.

4.5.2 Examination.

* 4.5.2.1 Component parts and concurrent repair parts. Examination of component parts and concurrent repair parts shall be performed in accordance with the criteria specified in the contract (see 6.2). The contractor's examination of these parts shall be accomplished prior to their assembly into the end item or submission for acceptance as repair parts.

* 4.5.2.2 Pistol and Mount. Each pistol and mount shall be visually and manually examined to determine conformance with the material, construction, and design requirements of 3.2 thru 3.2.4. Each step in the examination shall include a visual examination for proper cleaning and presence of the specified protective coating and to determine the general quality, completeness of manufacture, assembly, clarity and legibility of markings, and workmanship. The chamber shall be examined for rust, pits, powder fouling, burrs, and other defects. The examination provisions shall be applied at the earliest practical point in manufacture at which it is feasible to inspect for acceptance without risk of change in the characteristic by subsequent operations. Reinspections of these characteristics on the completed product is not required provided assurance exists that the characteristic has not been changed, degraded or damaged by subsequent manufacturing, assembly or handling, and that adequate inspection records are maintained. Pistols or mounts failing to meet the requirements shall be rejected.

4.5.3 Testing.

* 4.5.3.1 Failure data. Unless otherwise specified herein, all tests shall be conducted on a complete pistol and mount. Failure of the pistol and mount to meet the test requirements specified herein shall be cause for rejection of the pistol or mount, or the inspection lot of pistols or mounts. Acceptance of pistols or mounts shall be deferred and the contractor shall accomplish the following actions:

a. Conduct a failure analysis study performing a dimensional, physical and visual examination of the components which are suspected to be the cause of failure or malfunction.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:07Z
Check the source to verify that this is the current version before use.

b. Evaluate and correct the applicable production processes and procedures to prevent recurrence of the same defect(s) in future production.

c. Examine pistol and mount assemblies, partial assemblies, and components in process or at final assembly to insure that items containing the defect are purged from the system and not presented to the Government for acceptance.

d. The government representative shall verify the results of failure analysis and assure that corrective action has been accomplished prior to submission as a reconditioned lot or reconditioned pistol or mount for retest.

* 4.5.3.2 Breech safety testing. Each pistol shall be tested for breech safety (see 3.2.1) using the test method specified in 4.6.1. Failure to meet the requirement shall cause rejection of the pistol.

* 4.5.3.3 Trigger pull testing. A sample of pistols shall be tested for trigger pull (see 3.2.2) using the test method specified in 4.6.2. Acceptance shall be based on an AQL of 1.5 percent defective of the double sampling plan. Failure to meet the requirement shall cause rejection of the represented lot.

* 4.5.3.4 Mount impact testing. A sample of mounts shall be tested for impact recoil (see 3.2.3) using the test method specified in 4.6.3. Acceptance shall be based on an AQL of 0.65 percent defective of the double sampling plan. Failure to meet the requirement shall cause rejection of the represented lot.

* 4.5.3.5 Function Testing. Each pistol and mount shall be tested for functioning (see 3.3.1) using the test method specified in 4.6.4. Failure to meet the requirement shall cause rejection of the pistol or mount.

4.5.3.6 Endurance testing.

* 4.5.3.6.1 Pistol. One pistol shall be selected from each inspection lot and tested for endurance (see 3.3.2.1) using the test methods specified in 4.6.5.1. Failure to meet the requirements shall cause rejection of the represented lot.

* 4.5.3.6.2 Mount. One mount shall be selected from each inspection lot and tested for endurance (see 3.3.2.2) using the test method specified in 4.6.5.2. Failure to meet the requirement shall cause rejection of the represented lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:07Z
Check the source to verify that this is the current version before use.

4.5.3.7 Interchangeability testing.

* 4.5.3.7.1 Pistols and Mounts. A sample of 10 pistols and 10 mounts shall be selected from each inspection lot and tested for interchangeability (see 3.4) using the test method specified in 4.6.6. Pistols and mounts shall have been found satisfactory in all other examinations and tests. Pistols and mounts shall be function tested (see 4.5.3.5) after interchange of parts. Failure to meet the requirements shall cause rejection of the represented lot of pistols or mounts.

* 4.5.3.7.2 Concurrent repair parts. The interchangeability test for concurrent repair parts may be performed concurrently with the interchangeability test for component parts (see 4.5.3.7.1) using the test method specified in 4.6.6. Two pistols and mounts that have had designated repair parts components removed, shall be assembled using repair parts designated (see 6.2). The pistols and mounts shall be function tested (see 4.5.3.5) and shall meet the requirements as specified in 3.3.1. The pistols and mounts shall have been found satisfactory in all other examinations and tests. Failure to meet the requirements shall cause rejection of the represented lot.

* 4.5.4 Certification. Unless otherwise specified, the contractor shall furnish the Government representative with certified statements that each inspection lot conforms to the materials and processes specified on the applicable drawings and specifications.

* 4.5.5 Packaging examination and testing. Unless otherwise specified (see 6.2), the packaging examination and testing shall be in accordance with MIL-P-14232.

* 4.5.6 Inspection equipment. Unless otherwise specified (see 6.2), responsibilities for acquisition, calibration, maintenance, and disposition of measuring and testing equipment, and for all other equipment for performing inspections required by applicable specifications, shall be in accordance with MIL-I-45607.

* 4.5.6.1 Accuracy of standard measuring equipment. When commercial and modified commercial inspection and test equipment is used, it shall be capable of repetitive measurements to an accuracy of ten percent of the total tolerance of the characteristic being inspected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:07Z
Check the source to verify that this is the current version before use.

4.6 Test Methods.

* 4.6.1 Breech safety test. The pistol breech safety shall be tested by pulling the trigger with the breech in the locked position, and then attempting trigger pull with the breech in the unlocked position.

* 4.6.2 Trigger pull test. The pistol shall be tested for trigger pull using a dead weight attached to a hooked wire. The prescribed weights shall be applied pendent from the middle of the trigger bow and parallel to the bore axis, withthe pistol in a vertical position.

* 4.6.3 Mount impact test. The pistol shall be installed on the mount, and the mount shall be tested for recoil impact by firing one Government standard pyrotechnic cartridge. The remaining recoil distance shall be measured using a contractor developed, Government approved test and recording method. This test shall be run concurrently with the function and endurance tests.

* 4.6.4 Function test. The pistol and mount shall be functionally hand operated. The pistol shall be dry snapped at least five times and test fired using one Government standard pyrotechnic cartridge. This test shall be run concurrently with the mount impact and endurance tests.

4.6.5 Endurance test. Endurance testing of the pistol and mount shall be run concurrently with the mount impact and function tests. Upon completion of mount impact, function, and endurance tests the pistol and mount shall be cleaned and oiled, and worn and defective components replaced.

4.6.5.1 Pistol. The pistol shall be installed on the mount and endurance tested by 3000 dry snappings of the trigger, and the firing of 50 Government standard pyrotechnic cartridges. The cartridges shall be fired upon completing the 3000 dry snappings. Each test cycle shall be recorded using a contractor developed, Government approved test and recording method.

* 4.6.5.2 Mount. The mount shall be endurance tested by firing 100 Government standard pyrotechnic cartridges in the pistol, using a contractor developed, Government approved test and recording method.

Source: https://assist.dla.mil - Downloaded: 2026-10-16T13:07Z
Check the source to verify that this is the current version before use.

* 4.6.6 Interchangeability test. The pistol and mount, component parts, and repair parts shall be tested for interchangeability, by disassembly then reassembly using a prearranged interchange system as specified in the contract (see 6.2).

5. PREPARATION FOR DELIVERY

* 5.1 Pilot pack. The pilot pack shall consist of a pistol and mount packaged in accordance with Packaging Data Sheet P7265657 for the level of protection specified in the contract (see 6.2), packed level C and forwarded in accordance with 3.1.

* 5.2 Preservation, packaging, packing and marking. Pistols and mourts shall be preserved, packaged, packed, and marked in accordance with Packaging Data Sheet P7265657 for the level of protection specified in the contract (see 6.2).

* 5.3 Repair parts. Repair parts shall be preserved, packaged, packed, and marked in accordance with Packaging Data Sheets or other requirements and for level of protection specified in the contract (see 6.2).

6. NOTES

6.1 Intended use. The pistol and mount is intended to be used for projecting flares to signal aircraft, troops, ships, rescuers, or other similar applications.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Lists of drawings and specifications pertinent to the pistol and mount, showing applicable revision date.
c. Whether procurement is for pistols, mounts, or both (see 1.1).
d. Requirements for submission of first article and pilot pack (see 3.1 and 5.1).
e. Block of serial numbers required (see 3.5).
f. Component parts and concurrent repair parts examination criteria (see 4.5.2.1).
g. List of repair parts for interchangeability (see 4.5.3.7.2).
h. Packaging examination and testing, if different (see 4.5.5).
i. Responsibilities for acquisition, maintenance, calibration, and disposition of measuring and test equipment, if different (see 4.5.6).
j. Interchangeability test system (see 4.6.6).
k. Selection of applicable levels or preservation, packaging and packing (see 5.1 and 5.2).
l. Packaging instructions for repair parts (see 5.3).

Source: https://assist.dla.mil - Downloaded: 2026-10-16T13:07Z
Check the source to verify that this is the current version before use.

6.3 Contract data requirements. When warranted, requirements for reports of the results of examination and testing shall be specified on DD Form 1423 included in the contract.

6.4 Management control system requirements. When warranted, the contract should specify the application of MIL-Q-9858 or MIL-I-45208 on the Management Control Systems Summary List, DD Form 1660.

6.5 Unless otherwise specified (see 6.2), the contract should specify the application of MIL-I-45607 on the Management System Control Summary List, DD Form 1660.

* 6.6 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last issue.

Custodians:
Army - WC
Navy - OS
Air Force - 84

Review activities:
Navy - OS
Air Force - 84

Preparing activity:
Army - WC

Project number:
1095-0060

Source: https://assist.dla.mil - Downloaded: 2026-10-16T13:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-P-1299B; Pistol, Pyrotechnic, AN-M8 and Mount, M1

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:07Z
Check the source to verify that this is the current version before use.