MIL-D-3886F
25 November 1986
SUPERSEDING
MIL-D-3886E
17 February 1978

MILITARY SPECIFICATION

DOUGH DIVIDER, ROLL, HAND OPERATED, 36-PART AND DOUGH DIVIDER AND ROUNDING MACHINE, ROLL, 36-PART

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a 36-part, hand operated, dough divider machine and a 36-part, semi-automatic, electrically operated, dough divider and rounding machine.

1.2 Classification. The machines covered by this specification shall be of the following types as specified (see 6.2).

TYPES

Type I: Dough divider machine, bench or stand mounted, manually operated.

Type II: Dough divider and rounding machine, floor mounted, semi-automatic, electrically operated.

1.2.1 Part numbers. The part numbers for the machines covered by this specification shall be as follows:

a. Type I: M3886-01
b. Type II: M3886-02

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A | FSC 7320 |

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:54Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

UU-P-268 - Paper, Kraft, Wrapping.

MILITARY

MIL-B-2316 - Bakery Equipment, Including Unit Assemblies, Repair Parts and Tools, Preparation for Delivery of.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-461 - Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference.
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of.

(Copies of specifications and standards required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DODISS shall be the issue of the non-Government documents which is current on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:54Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip.
A240 - Free-Machining Stainless and Heat-Resisting Steel Bars, Hot-Rolled or Cold-Finish.

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

BAKING INDUSTRY SANITATION STANDARDS COMMITTEE (BISSC)

Standard No. 8 Dividers, Rounders, and Bun Machines.
Standard No. 29 Electric Motors and Accessory Equipment.

(Application for copies should be addressed to the Baking Industry Sanitation Standards Committee, Lincoln Building, Suite 858, 60 E. 42nd St., New York, NY 10017.)

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

MG 1 - Motors and Generators.
WC 5 - Thermoplastic-Insulated Wire and Cable for the Transmission and Distribution of Electrical Energy.
WC 7 - Cross-Linked-Thermosetting-Polyethylene Insulated Wire and Cable for the Transmission and Distribution of Electrical Energy.
WD 1 - General-Purpose Wiring Devices.

(Application for copies should be addressed to the National Electrical Manufacturers Association, 2101 L Street, NW, Washington DC 20037.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

70 - National Electrical Code.

(Applications for copies should be addressed to the National Fire Protection Association, 2101 L Street, NW, Washington, DC 20037.)

NATIONAL SANITATION FOUNDATION (NSF)

No. 51 - Plastic Material and Compounds Used in Food Service.

(Application for copies should be addressed to the National Sanitation Foundation, 3475 Plymouth Road, P.O. Box 1468, Ann Arbor, MI 48106.)

UNDERWRITERS LABORATORIES INC. (UL)

UL 498 - Electrical Attachment Plugs and Receptacles.

(Application for copies should be addressed to the Underwriters Laboratories Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:54Z
Check the source to verify that this is the current version before use.

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard commercial product. The dough dividers shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the dough divider being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection and approval (see 4.2.1 and 6.4).

3.3 Codes and standards. The dough dividers shall conform to the requirements of BISSC Standards No. 8 and No. 29 as applicable.

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using material produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means material which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.4.1 Stainless steel. Stainless steel shall conform to the 300 series of ASTM A167 or ASTM A240 as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:54Z
Check the source to verify that this is the current version before use.

3.5 Design and construction.

3.5.1 Type I (dough divider). The Type I machine shall be designed for bench mounting consisting of a base, an operating handle, a manually operated dough dividing mechanism (cutting head with stainless steel knives and pressure board), a yoke or support and a removable dough pan. The base of the Type I shall be provided with boltholes for mounting onto a stand or work bench. The overall dimensions of the Type I machine, excluding the operating handle, shall be 18 inches [457 millimeters (mm)] in length by 21 inches (533 mm) in width by 26 inches (660 mm) in height plus or minus 3 inches (76.2 mm) for each dimension.

3.5.1.1 Stand. When specified (see 6.2), the Type I machine shall be furnished with a stand. The stand shall be fabricated from chrome plated or stainless steel tubing and a stainless steel top plate with a thickness of not less than 0.0747 inch (1.90 mm). Four 2-inch (50.8 mm) toe locked swivel casters, suitable for food service, shall be mounted on the bottom of the stand. The stand shall be equipped with a welded under shelf in the lower part of the stand for storage of spare dividing pans and for better rigidity.

3.5.1.2 Pan. The Type I machine shall be provided with a circular dough pan of one piece, deep drawn stainless steel. The pan shall be easily removable and shall have not less than one handle.

3.5.2 Type II (dough divider and rounding machine). The Type II machine shall be semi-automatic consisting of a floor mounted support or stand with integral housing, a manually operated dough divider mechanism (cutting head with stainless steel knives and pressure pad), an electric motor operated rounding mechanism (rounder plate), a yoke or support, and a removable work pallet. The Type II machine shall divide the dough by manual operation and shall round the dough by an automatic operation. The handle shall be fully depressed manually to engage the rounding mechanism for the rounding operation. The return of the handle shall disengage the rounding mechanism. Boltholes shall be provided at the base of the support or stand for bolting the Type II to the floor. The overall dimensions, excluding the operating handle, shall be 34-1/2 inches (876 mm) in length by 28-1/2 inches (724 mm) in width by 53 inches (1346 mm) in height plus or minus 2 inches (50.8 mm) for each dimension.

3.5.2.1 Rounder plate and work pallets. The Type II shall be provided with a rounder plate and four work pallets of stainless steel or of polyurethane plastic conforming to NSF No. 51 and approved by the BISSC. The rounder plate shall be attached to and driven by an electric motor as specified in 3.5.4.1. Thirty-six recesses shall be stamped or embossed on each work pallet for forming the rolls during the rounding operation. Each work pallet shall have one handle and shall nest in a fixed position on the rounder plate during operation. Work pallets shall be removable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:54Z
Check the source to verify that this is the current version before use.

3.5.3 Trip lever and trip lever catch. The Type I and Type II machines shall be provided with a trip lever and trip lever catch. The trip lever shall be designed so that when engaged it shall prevent operation of the handle and release of the knives to the full cutting distance. The trip lever catch shall be designed so that when engaged it shall prevent the trip lever from being released. All mechanisms shall be located in the front of the machine for ease of operation.

3.5.4 Electrical characteristics. Unless otherwise specified (see 6.2), the Type II machine shall be wired to be operated on a nominal 120 volts, 60 Hertz, single phase power source. Means shall be provided for grounding the machine.

3.5.4.1 Motor. The electric motor used on the Type II machine shall be a capacitor type or split-phased type and shall conform to NEMA MG 1 and BISSC No. 29. The motor shall be of sufficient horsepower and speed to meet the production capacity specified in 3.6.3. The motor shall have thermal overload protection of the manual reset type and conform to NFPA 70.

3.5.4.2 Electrical components. The Type II machine shall have a manual switch conveniently located with a connected rubber jacketed cord. Unless otherwise required (see 3.5.4), the cord shall be a 2-wire with ground and shall have a 3-prong grounding type plug. Unless otherwise required (see 3.5.4), the plug shall conform to NEMA WD 1 configuration 5-15P; shall meet the requirements of UL 498; and shall extend not less than 8 feet (2.4 meters) beyond the machine. Wiring shall be in accordance with NEMA WC 5 or NEMA WC 7.

3.5.4.3 Electromagnetic interference suppression. When specified (see 6.2), the Type II machine shall be designed to meet the UM05 requirements of MIL-STD-461 for Class C3, Group II equipment.

3.6 Performance.

3.6.1 Operation. The Type I and Type II machines shall be capable of operating, without a load, for not less than 25 cycles and meet the following requirements as applicable:

a. Proper operation of motor starting and stopping devices.
b. Proper operation of adjusting and operating devices.
c. Proper operation of parts.
d. No overheating of bearings.
e. No binding.

3.6.2 Type I performance. The Type I machine shall divide a pan full of whole dough into 36 separate and equal pieces by weight $\pm$5 percent, depending upon the amount of whole dough placed in the dough pan (see 4.6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:54Z
Check the source to verify that this is the current version before use.

3.6.3 Type II performance. The Type II machine shall be capable of dividing and rounding a pallet full of whole dough into 36 separate and equal pieces by weight ±5 percent at a rate of not less than 4,500 pieces per hour, depending upon the amount of whole dough placed in the work pallet (see 4.6.4).

3.7 Lubrication. Unless otherwise specified (see 6.2), means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Where use of high-pressure lubricating equipment, 1,000 pound-force per square inch or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location. The unit shall be lubricated prior to delivery with type of lubricant specified in the operator's manual and grade of lubricant recommended for ambient temperature at the delivery point. The unit shall be conspicuously tagged to identify the lubricants and their temperature range.

3.7.1 Lubrication instruction. The machine shall have a lubrication chart indicating points requiring lubrication, and the time interval of lubrication.

3.8 Finish. Unless otherwise specified (see 6.2), the machine shall be finished in accordance with the manufacturer's standard practice. All surfaces of the machine shall present a neat appearance.

3.9 Data name plates. Data name plates shall be made of minimum 20 gauge corrosion-resisting metal and attached to each item in such a manner as to meet the applicable sanitary requirements for this equipment. The plate shall contain the following information stamped, engraved or applied by photosensitive means:

National Stock Number
Procurement Instrument Identification Number
Manufacturer's Name, Address, Phone Number
Manufacturer's Model Number

Each plate shall be placed so that it is readily visible to the operator during normal operating use. Each plate shall be placed in a manner so as to not adversely affect the life and utility of the item.

3.10 Interchangeability. All machines of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.11 Workmanship.

3.11.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:54Z
Check the source to verify that this is the current version before use.

3.11.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.11.3 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.1.3 Standards compliance. The contractor shall make available to the contracting officer or his authorized representative evidence of compliance with the applicable standard(s) cited in 3.3 and 6.5. The Government reserves the right to examine and test all machines to determine the validity of the certification.

4.1.3.1 BISSC. Acceptable evidence of meeting the requirements of the BISSC Standards No. 8 and No. 29 shall be the BISSC certification symbol or label, or a certified test report, acceptable to the contracting officer with the advice of the Army Surgeon General, from a recognized independent testing laboratory indicating the machines have been tested and conform to the BISSC.

Source: https://assist.dla.mil -- Downloaded: 202640-16T21:54Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one complete machine when a first article is required (see 3.2 and 6.2). This inspection shall include the examination of 4.4, the tests of 4.5.1, and, when specified, the preproduction pack inspection of 4.7 (see 4.7 and 6.2). The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.4, the tests of 4.5.2, and the packaging inspection of 4.7. This inspection shall be performed on the samples selected in accordance with 4.3.

4.3 Sampling. Sampling and inspection procedures shall be in accordance with MIL-STD-105. The unit of product shall be one complete machine of the type required. All machines offered for delivery at one time shall be considered a lot for the purpose of inspection. If an inspection lot is rejected, the contractor may rework it to correct the defects, or screen out the defective units, and resubmit for a complete reinspection. Resubmitted lots shall be reinspected using tightened inspection. If the rejected lot was screened, reinspection shall be limited to the defect causing rejection. If the lot was reprocessed, reinspection shall be performed for all defects. Rejected lots shall be separate from new lots, and shall be clearly identified as reinspected lots.

4.3.1 Sampling for dimensional examination. Dimensional examination shall be based on inspection level S-2 and an Acceptable Quality Level (AQL) of 4.0 percent defective.

4.3.2 Sampling for visual examination. Visual examination shall be based on inspection level II and an AQL of 2.5 percent defective.

4.4 Examination. Each sample selected in accordance with 4.3 shall be examined for compliance with the requirements in section 3 of this specification. This element of inspection shall encompass all visual examinations and dimensional measurements.

4.4.1 Dimensional measurement. Each sample shall be examined for the dimensional measurement requirements in section 3 of this specification. Any dimension not within the specified requirement shall constitute one defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:54Z
Check the source to verify that this is the current version before use.

4.4.2 Visual examination. Each sample shall be examined for defects listed in Table I. Each attribute within each classification of multiple defects shall constitute one defect.

TABLE I. Classification of defects.

Classification	Defects	Requirement paragraph
Major		
101	Not in accordance with manufacturers standard product, except for changes necessary to comply with the requirements of this specification.	3.1
102	Not in accordance with codes and standards.	3.3
103	Material not as specified.	3.4
104	Boltholes in base of stand missing.	3.5.1 and 3.5.2
105	Casters missing from stand of Type I.	3.5.1.1
106	Casters on Type I stand not suitable for food service use.	3.5.1.1
107	Type I pan not readily removable.	3.5.1.2
108	Type I pan does not have at least one handle.	3.5.1.2
109	Work pallet of Type II does not have 36 recesses.	3.5.2.1
110	Four work pallets not provided with Type II.	3.5.2.1
111	Work pallet of Type II does not have at least one handle.	3.5.2.1
112	Work pallet of Type II not easily removable.	3.5.2.1
113	Rounder plate of Type II does not allow nesting of work pallet in a fixed position during rounding operations.	3.5.2.1
114	Trip handle allows handle to operate fully.	3.5.3
115	Lubrication not as specified.	3.7
116	Workmanship not as specified.	3.11
Minor		
201	Marking missing, incomplete, or not legible.	3.9

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:54Z
Check the source to verify that this is the current version before use.

4.5 Tests.

4.5.1 First article tests. The first article sample shall receive the tests of 4.6 applicable to the type of machine being furnished. Failure of the first article to pass any of the tests shall constitute cause for rejection.

4.5.2 Quality conformance tests. Each machine offered for acceptance at one time shall receive the test of 4.6.1 or 4.6.2 as applicable. Failure to pass this test shall be cause for rejection of the machine. One representative sample of the Type I shall then receive the test of 4.6.3 and one representative sample of the Type II shall then receive the test of 4.6.4. Failure to pass the applicable test shall be cause for rejection of the lot.

4.6 Test methods.

4.6.1 Operational test (Type I). The Type I machine shall be operated without a load for not less than twenty-five cycles to determine compliance with the proper operation of adjusting and operating devices, operational parts, and without binding, as specified in 3.6.1. Inability of the machine to operate as specified herein shall constitute failure of the test.

4.6.2 Operational test (Type II). The Type II machine shall be connected to a power supply and operated without a load for not less than twenty-five cycles to determine compliance with the proper operation of adjusting and operating devices, operational parts, presence of binding and the operation of the motor and rounding mechanism to start and stop without indication of overheating of bearings to determine compliance with 3.6.1. Inability of the machine to operate as specified herein shall constitute failure of the test.

4.6.3 Performance test (Type I). After successfully passing the test of 4.6.1 the Type I machine shall be subjected to the performance test. Test for the Type I machine shall be as follows. The pan, containing 3 pounds (1.36 kg) of whole dough shall be placed in the machine. The machine shall be operated to perform the dough dividing operation on the pan of whole dough to determine compliance with 3.6.2. The test shall be repeated by dividing a piece of whole dough weighing 7-1/2 pounds (3.40 kg). The weight of each piece of divided dough shall comply with the requirements specified in 3.6.2. Inability of the machine to divide dough into pieces, with the weight variances specified, shall constitute failure of the test.

4.6.4 Performance test (Type II). After successfully passing the test of 4.6.2, the Type II machine shall be subjected to the performance test. The performance test for the Type II machine shall be as follows. The work pallet containing 1 pound 11 ounces (0.76 kg) of dough shall be placed in the machine. The machine shall be operated to perform the dough dividing and rounding operation on the pallet of dough to determine compliance with 3.6.3. The test shall be repeated for a piece of whole dough weighing 5 pounds 10 ounces (2.55 kg). The rate of rounded dough pieces produced and weight

Source: https://assist.dla.mil -- Downloaded: 202610-16T21:54Z
Check the source to verify that this is the currentversion before use.

variance of each dough piece shall comply with the requirements specified in 3.6.3. Inability of the machine to divide dough into pieces, with the weight variances specified, shall constitute failure of the test.

4.6.5 Electromagnetic interference suppression. When electromagnetic interference suppression is required (see 3.5.4.3), the Type II machine shall be tested to meet the requirements of 3.5.4.3 in accordance with MIL-STD-462.

4.7 Packaging inspection. The inspection of the preservation, packing, and marking shall be in accordance with the requirements of section 4 of MIL-B-2316. The inspection shall consist of the quality conformance inspection; and, when specified (see 6.2), a preproduction pack shall be furnished for examination and test within the time frame required (see 6.2).

5. PACKAGING

5.1 Preservation, packing, and marking. Preservation, packing, and marking shall be in accordance with the requirements of MIL-B-2316 with the level of preservation and the level of packing as specified (see 6.2). In addition, the dough pan or pallets shall be removed, securely and compactly wrapped in not less than 30 pound basis weight (24 by 36 - 500) (48.8 grams per square meter) kraft paper conforming to grade B of UU-P-268, and then replaced in the original position and firmly blocked, braced, or wired in place, to prevent movement while in transit. Each removed handle shall be wrapped in kraft paper as specified herein. Knives shall be positioned at the top of the stroke. The trip lever and trip lever catch shall be secured with 0.072 inch (1.83 mm) diameter annealed wire, or securely blocked and braced to prevent movement.

6. NOTES

6.1 Intended use. The Type I and Type II machines are intended for use in bakeries to divide whole pieces of dough into 36 equal roll-sized portions. Additionally, the Type II also performs a rounding operation on each piece of divided dough.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Number and type machine required (see 1.2).
c. When the Type I machine is to be furnished with a stand (see 3.5.1.1).
d. Electrical characteristics, if other than as specified (see 3.5.4).
e. When electromagnetic interference suppression is required (see 3.5.4.3).
f. Means for lubrication, if other than as specified (see 3.7).
g. Finish of machine, if other than as specified (see 3.8).
h. When a first article sample and inspection is required. When a preproduction pack inspection is required and the time frame required (see 4.2.1 and 4.7).
k. Level of preservation and level of packing (see 5.1).

Source: https://assist.dla.mil -- Downloaded: 202610-16T21:54Z
Check the source to verify that this is the current version before use.

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), and invokes the provisions of DOD Federal Acquisition Regulations (FAR) Supplement 27.410-6, the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of DOD FAR 27.410-6 are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 First article. When a first article inspection is required, the item will be tested and should be a first article sample or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one unit of the type required. The contracting officer should include specific instruction in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.5 Subject term (key word) listing.

Appliance, commercial
Dough divider, 36-part
Equipment, bakery
Food service equipment

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:
Navy - YD
Air Force - 99

Preparing Activity:
Navy - YD
(Project 7320-0780)

Review Activities:
Army - MD
Navy - MC, SA
Air Force - 84
DLA - GS

Source: https://assist.dla.mil -- Downloaded: 202610-16T21:54Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commanding Officer (Code 156)
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer (Code 156)
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

Source: https://assist.dla.mil -- Downloaded: 202610-16T21:54Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-D-3886F	DOUGH DIVIDER, ROLL, HAND OPERATED, 36-PART AND DOUGH DIVIDER AND ROUNDING MACHINE, ROLL, 36-PART

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 202610-16T21:54Z
Check the source to verify that this is the current version before use.