INCH/POUND

FF-B-187B
SUPPLEMENT 1
10 September 1993

FEDERAL SPECIFICATION

BEARINGS, ROLLER, TAPERED

This specification is approved by the Administrator, Federal Supply Service, General Services Administration, for the use of all Federal Agencies.

SPECIFICATION SHEETS

FF-B-187/1	Bearing, Roller, 'Tapered, Single Row, Normal Angle. (Type TS)
FF-B-187/2	Bearing, Roller, Tapered, Single Row, Normal Angle, Flanged Cup. (Type TSF)
FF-B-187/3	Bearing, Roller, Tapered, Single Row, Steep Angle. (Type TSS)
FF-B-187/4	Bearing, Roller, Tapered, Single Row, Steep Angle, Flanged Cup. (Type TSSF)
FF–B-187/5	Bearing, Roller, Tapered, Double Row, One Double Cone, Two Single Cups. (Types TDI and TDIS)
FF-B-187/6	Bearing, Roller, Tapered, Double Row, Normal Angle, Two Single Cones, One Double Cup. (Type TOO)
FF-B-187/7	Bearing, Roller, Tapered, Double Row, Steep Angle, Two Single Cones, One Double CUP. (Type TDOS)
FF–B-187/8	Bearing, Roller, Tapered, Double Row, Normal Angle, TWO Single Cones, One Double Cup, Nonadjustable. (Type TNA)
FF-B-187/9	Bearing. Roller. Tapered, Double Row, Steep Angle, Two Single Cones, One Double Cup, Nonadjustable. (Type TNAS)
FF-B-187/10 -	Bearing, Roller, Tapered, Double Row, Straight Bore. Two Single Cones with Contacting Front Faces Slotted and Chamfered For Lubrication, One Double Cup with Lubrication, Holes and Groove. (Type TNASW)
FF-B-187/11 –	Bearing, Roller, Tapered, Double Row, Straight Bore, Two Single Cones, Cone Back Face Rib Ground on the Outer Diameter For Sealing Purposes, One Double Cup with Lubrication Holes and Groove. (TYPE TNASWE)

AMSC N/A

FSC 3110

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:46Z
Check the source to verify that this is the current version before use.