MILITARY SPECIFICATION

CHARGE, PROOF, 155MM, PXR-6297
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-C-63372 (AR) dated 5 September 1979, and is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 3.7: Delete in its entirety and substitute the following:

"3.7 Proving ground. Twenty propelling charges will be fired at 145°F and twenty at 70°F for information".

PAGE 24

* 4.4.2.21, Charge, Proof, PXR-6297 for 155mm Cannon M199 and M185:

Special category a: Delete number of sample units "20" and substitute "40".

PAGE 33

* 4.5.6: Delete in its entirety and substitute the following:

"4.5.6 Proving ground (see 3.7). This test shall be conducted at a Government proving ground in accordance with the applicable acceptance test procedure using PXR-6325 projectile simulators or M549, RA projectiles inert loaded within 0.1 pound of an as fired weight of 96.0 pounds and M483A1 projectiles inert loaded (103.0 pounds) using primer, M82 and fired in cannon M199 or M185 with 75 percent (minimum) remaining life. Firing shall be conducted with a spindle to charge base stand-off of 1 inch (plus or minus 1/4 inch). Prior to firing, all charges shall be temperature conditioned in a large conditioning box with adequate air circulation at the required temperature for a minimum of 24 hours and assurance will be made that, when fired, the charges are at the conditioning temperature. The following tolerances shall

FSC: 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

apply to all 145°F and 70°F conditioning: 145°F from 140°F to 145°F; 70°F from 68°F to 72°F. Copper crusher gages (2) shall be used to measure the maximum chamber pressure of each charge. Velocity coils will be used to measure the muzzle velocity of each charge. Temperature indicator (thermometer) strips shall be placed on the side (lacing jacket) of all charges or on the side of the metal containers, as applicable, conditioned at 145°F as a further assurance of the proper conditioning temperature. If any indicator strip shows the charge has been exposed to a temperature greater than 145°F, that charge will not be fired."

* 4.5.6.1: Delete in its entirety and substitute the following:

"4.5.6.1 Pressure. Two pressure-time gages at different locations (one in the spindle and one at the projectile base) will be used to record pressure-time traces. Differential pressure traces will be obtained by subtracting the projectile gage output from the spindle gage output. The maximum differential pressure of any charge will be defined as the maximum amplitude of the first negative wave of the differential pressure trace prior to peak pressure. Any trace which contains no amplitude in the negative direction will be considered to have a differential pressure of zero. Ignition delay will be recorded on all differential pressure firings. Twenty (20) charges will be conditioned to 145°F and twenty (20) charges at 70°F. Ten (10) charges will be fired with the PXR-6325 projectile simulators or M549 projectiles and ten (10) with the M483A1 projectiles, all charges conditioned at 145°F. In addition the twenty (20) charges conditioned at 70°F will be fired, ten (10) with the PXR-6325 or M549 projectiles and ten (10) with the M483A1 projectiles. Charges fired at 70°F shall be fired alternately with calibration charges (ten (10) with each projectile). Charges fired at 145°F shall be intermixed with calibration charges (five (5) with each projectile). The muzzle velocity and pressure of all test charges will be corrected to standard condtions. All projectiles and projectile simulators shall be inert loaded.

4.5.7: Delete entire paragraph and substitute new
• paragraph as follows:

"4.5.7 Teardown inspection. Each container and propelling charge will be subjected to each of the critical (except critical Special a, paragraph 4.4.2.21) and 100 percent major (except major defect 101, paragraph 4.4.2.9; major defect 103, paragraph 4.4.2.18; major defect 101, paragraph 4.4.2.21; major defect 104 paragraph 4.4.2.23) inspections

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

defined in 4.4.2 of this specification. Samples may be accumulated or inspected upon selection providing the selection remains random and represents the lot. The inspections will be performed by the contractor and witnessed by the Government. The detection of any one of the above defects shall be cause for rejection of the lot represented by the sample."

PAGE 35

* 6.6, Proving ground: Delete "DRDAR-QAR-Q" and substitute "DRDAR-QAR-R".

* 6.7, Teardown inspection: Delete "DRDAR-QAR-Q" and substitute "DRDAR-QAR-R".

* Add a new paragraph:

"6.8 Temperature indicator strips. The highest temperature reading from each indicator strip shall be recorded for informational purposes and reported on the applicable firing record."

* 6.9, Method of inspection submission: Delete "DRDAR-QAR-Q" and substitute "DRDAR-QAR-R".

* 6.10, Method of assuring alignment submission: Delete "DRDAR-QAR-Q" and substitute "DRDAR-QAR-R".

PAGE 36

* 6.11, Data cards: Delete "DRDAR-QAR-Q" and substitute "DRDAR-QAR-R".

NOTE: "The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320-A660)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.