INCH-POUND

MIL-C-63418 (AR)
AMENDMENT 1
6 April 1991

MILITARY SPECIFICATION

CANISTER SMOKE, ASSEMBLY
PARTS FOR ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-C-63418 (AR), dated 1 December 1980 and is approved for use by the US Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1: STANDARDS, MILITARY, add:

"MIL-STD-105 - Sampling Procedures and Table for Inspection by Attributes"

PAGE 2

2.1: Drawings, Army, add:

"12934724 - Alternate Canister Smoke, Assembly"

Add the following paragraph 2.3:

"2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets of MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained."

3.2 Add the following:

"3.2.1 Alternate Canister Smoke, Assembly. The assembly and components shall comply with all requirements specified on Drawing (Dwg.) 12934724 and with all requirements specified in applicable specifications."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:49Z
Check the source to verify that this is the current version before use.

PAGE 3

3.6 Add the following:

"3.6 Sealing. The alternate smoke canister assembly shall withstand a vacuum of 6.0 +/- 1.0 inches of mercury for a minimum period of 30 seconds without leakage."

PAGE 4

4.3.1 Add the following after "Pad 9342877 5":

"If the contractor has elected to produce the alternate smoke canister assembly, then the first article sample shall consist of the following items in sample quantities as indicated:

"Part Description	Drawing	Quantity
Alternate Canister Smoke, Assembly	12934724	20
Body	12934726	5
Lid	12934725	5
Felt	12934727	5"

PAGE 5

TABLE I - FIRST ARTICLE INSPECTION Add the following:

"Alternate Canister Smoke, Assembly (Dwg. 12934724) Examination for defects	20	3.2.1	4.4.2
Components Examination for defects	5	3.2.1	4.4.2"

PAGE 12

4.4.2, Add the included new tables: 4.4.2.7, 4.4.2.8, 4.4.2.9 and 4.4.2.10.

Source: https://assist.dla.mil -- Downloaded: 20261O-23T02:49Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.7	Body (Alternate Canister Smoke)		12934726
			NEXT HIGHER ASSEMBLY 12934724

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness through base, min.		0.40%	3.2.1	Gage
102	Inside diameter of neck		0.40%	3.2.1	Gage
103	Outside diameter of base end		0.40%	3.2.1	Gage
104	Outside diameter of lip		0.40%	3.2.1	Gage
105	Wall thickness, min.		0.40%	3.2.1	Gage
106	Total length		0.40%	3.2.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-02-20T02:40Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Lid (Alternate Canister Smoke)	1 OF 1	12934725
			NEXT HIGHER ASSEMBLY: 12934724

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.2.1	Gage
102	Outside diameter of neck		0.40%	3.2.1	Gage
103	Outside diameter		0.40%	3.2.1	Gage
Minor					
201	Thickness of lining compound		0.65%	3.2.1	Gage
202	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

4 (12b)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:49Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63418 (AR)
AMENDMENT 1

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12934727
4.4.2.9	Felt (Alternate Canister Smoke)				NEXT HIGHER ASSEMBLY 12934724
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Diameter		0.65%	3.2.1	Gage
202	Thickness		0.65%	3.2.1	Gage
203	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:10Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Alternate Canister Smoke, Assembly	1 OF 1	12934724
			NEXT HIGHER ASSEMBLY: 9331795

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Batch formulation incorrect		4.4.3.1	3.2.1	4.5.1
102	Moisture content over max.		4.4.3.2	3.5	4.5.2
103	Canister not sealed		4.4.3.3	3.6	4.5.3
104	Length		0.40%	3.2.1	Gage
105	Any component missing or incorrectly assembled		0.40%	3.2.1	Gage
106	Weight of composition		0.40%	3.2.1	Balance
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual
202	Marking missing, misleading, or unidentifiable		0.65%	3.2.1	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:49Z
Check the source to verify that this is the current version before use.

PAGE 14

4.4.3 Add the following:

"4.4.3.3 Sealing. Each shift's production of smoke canister assemblies shall be tested for leakage. Acceptance for this test shall be in accordance with MIL-STD-105, Inspection Level I, AQL 1.0% with the inspection lot equal to the number of smoke canister assemblies produced by one seaming machine during one shift. Component parts selected for assembly into leak test samples shall be loaded with inert composition and marked as inert prior to seaming. The leak test samples shall not be returned to the inspection lot."

PAGE 18

4.5.3 Add the following:

"4.5.3 Sealing. Place inert smoke canister assembly in fixture and close lid. Start vacuum. Lower canister into water. After gage shows 6.0 +/- 1" of mercury, observe canister for a minimum of 30 seconds. Raise the canister out of the water. Release vacuum. Raise the lid, remove the canister, and dry off. Set aside the canister for scrap. If the canister is a reject, then identify the seaming machine that produced the reject, and reject all canisters produced by that seaming machine since the last acceptable leak test sample."

5.2 Delete in its entirety.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1320-AC41)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:49Z
Check the source to verify that this is the current version before use.