MIL-D-50908B(AR)
23 March 1983
SUPERSEDING
MIL-D-50908A(PA)
1 April 1974

MILITARY SPECIFICATION

DEMOLITION KIT, CRATERING: M180 ASSEMBLING AND PACKING

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for the assembling and packing of the Demolition Kit, Cratering: M180.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.1), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed. to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS (See 6.4)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9241167	-	Packing and Marking For Box, Wirebound, Packing, Ammunition For Demolition Kit, Cratering: M180.
9244400	-	Demolition Kit, Cratering: M180 Assy.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 1556 (Part 19)	-	Density of soil in place by the Sand-Cone Method.

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings, specifications and standards

3.2 Parts. All parts shall comply with applicable drawings, specifications and standards.

3.3 Assembly. The Demolition Kit assembly shall comply with all requirements specified on Drawing (Dwg.) 9244400, all associated drawings, and with all requirements specified in applicable specifications and standards.

3.4 Functioning. The Demolition Kit assembly shall function in proper sequence and produce a crater in virgin or compacted clay-type soil when tested as specified in 4.5.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

3.5 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.6 Workmanship. All parts and assemblies shall be fabricated and assembled in a thorough, workmanlike manner. They shall be free of burrs, chips, weld spatter, sharp edges, chipped edges, gouges, cracks, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat and sharply defined. External threads shall be full, complete and undamaged for their entire length. All soldering shall be performed in a thorough, workmanlike manner with no evidence of burning or charring. Paintings and coatings on all parts and assemblies shall be restored when such have been removed or obliterated.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the first three (3) Demolition Kits assembled.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-D-50908B(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Demolition Kit, Cratering: M180 Assy				See below
					NEXT HIGHER ASSEMBLY
					-
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	M57 Firing Device, Modified (Dwg. 9244458)				
	Examination for Defects	3	-	3.3	4.4.2.1
	Rocket Motor-Detonator Assemoly (Dwg. 9244401)				
	Examination for Defects	3	-	3.3	4.4.2.2
	Demolition Kit, Cratering: M180 (Dwg. 9244400)				
	Examination for Defects	3	-	3.3	4.4.2.3
	Functioning	Note 1	-	3.4	4.5.1

NOTES:

1. The first three (3) assemblies shall be subjected to the examination for defects then functioned at a proving ground specified by the Contracting Officer.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot shall contain:

a. Rocket motor-detonator assemblies from not more than one lot interfix number from one manufacturer.

b. Warhead loading assemblies from not more than one lot interfix number from one manufacturer.

c. M57 firing devices (modified) from not more than one lot interfix number from one manufacturer.

d. M2A4 shaped charge loading assemblies from not more than one lot interfix number from one manufacturer.

e. Tripod assemblies from not more than one lot interfix number from one manufacturer.

f. Demolition circuits from not more than one lot interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Tests Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-50908B(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	M57 Firing Device (Modified) on Tripod Assembly	1 OF 1	9244458
			NEXT HIGHER ASSEMBLY: 9244403

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Safety pin loose or missing		100%	3.3	Visual-Manual
2	Bail not in vertical slot		100%	3.3	Visual
Major	None defined				
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-50908B(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Rocket Motor-Detonator Assembly	1 OF 1	9244401
			NEXT HIGHER ASSEMBLY 9244400

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Shorting (safety) and continuity plugs improperly installed or missing		100%	3.3	Visual
2	Warning tags (2) incorrect, illegible or missing		100%	3.3	Visual
Major					
101	Marking incorrect, illegible or missing		0.40%	3.3	Visual
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Demolition Kit, Cratering: M180	1 OF 2	9244400
			NEXT HIGHER ASSEMBLY: -

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Nut holding bands around warhead loading assembly turns when min torque is applied (2 nuts)		100%	3.3	Gage
Major					
101	Assembly fit of warhead to rocket motor		100%	3.3	Note 1
102	Retaining set screw holding shaped charge to leg turns when min torque is applied		0.40%	3.3	Gage
103	Distance between M57 Firing Device (Modified) and warhead assembly		0.40%	3.3	Gage
104	Part improperly assembled (warhead loading assembly shaped charge, M57 Firing Device (Modified) and Tripod Assembly		0.40%	3.3	Visual

NOTE: 1. Any demolition kit failing to show a snug fit shall be classed defective and the flush-latch coupling or the defective component replaced. Following successful completion of the test, the End Cover (Dwg. 9244436) and Flush Latch Coupling shall then be reassembled on the warhead and the entire kit packed as specified on Dwg. 9241167.

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-50908B(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Demolition Kit, Cratering: M180	2 OF 2	9244400
			NEXT HIGHER ASSEMBLY: —

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
105	Part or assemoly damaged (bent, distorted, cracked, etc)		0.40%	3.3	Visual
106	Part or assemoly missing		0.40%	3.3	Visual
107	Functioning	4.4.3.1		3.4	4.5.1
Minor					
201	Touch-up paint where required missing		0.65%	3.3	Visual
202	Poor workmanship (excl. 105 above)		1.0%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-50908B(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Box, Wirebound, Packing (Prior to Closing)	1 OF 1	9241167
			NEXT HIGHER ASSEMBLY: —

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Part missing (Technical Manual containing instructions for assembling and firing the kit; rocket motor-detonator assembly, warhead end cover and flush latch coupling and demolition circuit suopack)		0.40%	3.3	Visual
102	Packing arrangement of demolition kit assembly incorrect		0.40%	3.3	Visual
103	Packing material improperly positioned or missing (Filler, liner, pad, spacers and desiccant bags)		0.40%	3.3	Visual
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil - Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-50908B(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Box, Wirebound, Packing (Sealed)	1 OF 1	9241167
			NEXT HIGHER ASSEMBLY: —

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box damaged to the extent that contents are exposed		0.40%	3.3	Visual
102	Board broken or split		0.40%	3.3	Visual
103	Sealing tape missing or peeling		0.40%	3.3	Visual
Minor					
201	Contents loose when box is tilted		0.65%	3.3	Manual
202	Marking incorrect, unidentifiable or missing (including storage temperature limits)		0.65%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.3.1 Functioning. Following acceptance of the first article (see 4.3.1), sampling for this test shall be as follows: from the next fifty (50) demolition kits produced, two (2) kits shall be selected and tested. If any kit fails this test, two (2) additional kits shall be selected and tested. If there is no failure, the population from which the kits were selected shall be considered acceptable. From each subsequent one hundred and fifty (150) kits produced, two (2) kits shall be selected and tested. If there is no failure, the population shall be accepted. If any kit fails the test, an additional two (2) kits shall be tested. If there is no failure, the population shall be accepted.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraph (See 4.5). The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.2 herein.

4.5 Methods of inspection.

WARNING. This specification covers sampling/testing of explosive materiels which pose a potential explosive hazard to personnel. In order to minimize the risk, all applicable safety regulations, rules, and approved procedures must be followed in handling, inspection, and function testing.

Function testing presents a potential hazard to personnel and must be performed with personnel protected by a suitable barricade.

4.5.1 Functioning. The demolition kit shall be assembled and fired in accordance with the Technical Manual specified on Dwg. 9241167. The test shall be performed in virgin or compacted clay-type soil. For informational purposes, soil compaction shall be determined as specified in ASTM D 1556 or any other approved method. The functioning test procedure shall include monitoring by high-speed (fastex) movie camera using high-speed color film, or high-speed video tape, to record the functioning sequence of all components. Films and tapes shall be forwarded as specified in 6.3. For information purposes, the profile of the crater shall be determined and included with the test results.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation - packaging.

5.1.1 Level A. The demolition kits shall be preserved and packaged in accordance with Dwg. 9241167.

5.1.2 Level B. Preservation and packaging of the demolition kits shall be as specified in 5.1.1.

5.1.3 Level C. Preservation and packging of the demolition kits shall be as specified in 5.1.1.

5.2 Packing.

5.2.1 Level A. The demolition kits shall be packed in accordance with Dwg. 9241167.

5.2.2 Level B. Packing of the demolition kits shall be as specified in 5.2.1.

5.2.3 Level C. Packing of the demolition kits shall be as specified in 5.2.1

5.3 Marking. Marking shall be in accordance with Dwg. 9241167.

5.4 Shipping. When demolition kits from more than one lot are shipped at one time, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-I, Dover, New Jersey 07801. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects and tests paragraph number.

6.3 Test data submission. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested films, tapes and test results, as generated, to: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-M, Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARRADCOM.

6.5 Data cards. (See MIL-A-48078). Distribution of data cards shall include the address specified in 6.3.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A264)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions -- Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* -- Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* -- Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* -- Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.