MIL-L-51365A(EA)
19 April 1977
SUPERSEDING
MIL-L-51365(EA)
18 February 1975

MILITARY SPECIFICATION

LAUNCHER AND GRENADES, SMOKE: HC, M226

This specification is approved for use by US Army Armament Research and Development Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a launcher for dispensing grenades.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

TT-W-572 - Wood-Preservative; Water-Repellent.

MILITARY

MIL-G-12327 - Grenade, Hand, Smoke, HC, AN-M8.

FSC 1330

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn: DRDAR-TSC-S, Aberdeen Proving Ground, MD 21010 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168 - Lot Numbering of Ammunition.

DRAWINGS

US ARMY ARMAMENT RESEARCH & DEVELOPMENT COMMAND

EDGEWOOD ARSENAL

D13-12-26 - Launcher and Grenades, Smoke: HC, M226.

PUBLICATIONS

EDGEWOOD ARSENAL

R14-16 - Inspection Standard for Fluoroscopic or Radiographic Evaluation of; Launcher and Grenade, HC, M226.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing D13-12-26 and on the subsidiary drawings shall conform to the specifications thereon or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components shall conform to the specifications and drawings listed on D13-12-26 and subsidiary drawings, as applicable. The AN-M8 grenades produced more than 90 days prior to assembly into launchers shall be tested within 90 days prior to assembly into launchers and meet the functional requirements of MIL-G-12327.

3.2 Assembly. The launcher shall be assembled as shown on Drawing D13-12-26.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

3.3 Radiographic or fluoroscopic evaluation. The launcher shall be radiographed or fluoroscoped for missing components in accordance with 4.4.4.1.

3.4 Leakage. The launcher shall not leak air when submerged in water at a temperature of 170° ± 10° F, for a period of 30 to 35 seconds when tested in accordance with 4.4.4.2.

3.5 Functioning. The launcher shall eject the grenades to an average impact distance of 80 to 150 feet, based on the average of the entire sample that functioned. However, no grenades shall impact at a distance of less than 70 feet. In addition, the two components of the sabot (holder and cover) shall separate on or before impact, and the grenades shall ignite and emit a smoke cloud. Angle of elevation for firing test stand shall be 62 1/2 ± 2 1/2 degrees above the horizontal and the front underside of the launcher shall be 77 ± 1 inch above the average impact area, 80 to 150 feet down range. Test shall be in accordance with 4.4.4.3.

3.6 Low temperature. The launcher shall function subsequent to a conditioning period of 48 ± 1 hours at a temperature of -25° ± 2° F, when tested in accordance with 4.3.3.1.

3.7 High temperature. The launcher shall function subsequent to a conditioning period of 48 ± 1 hour at a temperature of 125° ± 5° F, when tested in accordance with 4.3.3.2.

3.8 Water immersion. The launcher shall function subsequent to being submerged in water at ambient temperature for 60 ± 5 minutes and then removed from the water and fired after 24 to 25 hours in accordance with 4.3.3.3.

3.9 Preproduction. Prior to the start of regular production, a preproduction sample of launchers shall be produced in accordance with this specification for examination and test (see 4.3).

3.10 Workmanship. The launcher shall be free from foreign matter and damage which could affect functioning.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisified.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3)
(b) Quality conformance inspection (see 4.4)

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of 30 launchers shall be manufactured using the same methods, materials, equipment and processes as will be used during regular production.

4.3.2 Inspection procedure.

4.3.2.1 For examination. The preproduction sample launchers shall be examined in accordance with the classification of defects, the AQL's are not applicable.

4.3.2.2 For destructive test. Sample launchers shall be tested in accordance with table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

TABLE I. Preproduction

Quantity	Requirements	Test	Defect to be observed
10	3.6 Low temperature	4.3.3.1 and 4.4.4.3	Duds, misfires, short Ranges, or sabot
10	3.7 High temperature	4.3.3.2 and 4.4.4.3	Fails to separate
10	3.8 Water immersion	4.3.3.3 and 4.4.4.3	

4.3.3 Test.

4.3.3.1 Low temperature. The launcher shall be placed in a cold chamber at the specified temperature for the required period of time, and fired 5 to 6 minutes after removal from the chamber, or from an insulated transport container.

4.3.3.2 High temperature. The launcher shall be placed in a hot chamber at the specified temperature for the period of time, and fired 5 to 6 minutes after removal from the chamber, or from an insulated transport container.

4.3.3.3 Water immersion. The launcher shall be submerged in water to a depth of 6 to 7 inches, at the specified temperature for the required period of time and then stored for the required period of time.

4.3.4 Acceptance/Rejection Criteria. The preproduction sample shall comply with the examination and all of the tests specified herein to be acceptable, with the exception of dud M8 grenades. The preproduction lot shall be acceptable if it contains a total of 3 or less dud M8 grenades. The supplier shall obtain written approval from the Contracting Officer prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. Each lot shall be identified and controlled in accordance with MIL-STD-1168. However, no more than one lot number of each component (M8 grenades and M225 propellant cartridges) from one manufacturer shall be contained in any one lot of assembled launchers.

4.4.2 Sampling.

4.4.2.1 For examination and radiographic or fluoroscopic evaluation. Sampling shall be conducted in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

4.4.2.2 For destructive test. Sampling shall be conducted in accordance with MIL-STD-105, level S-3 using an AQL of 4.0 and shall be taken from the sample used for examination (see 4.4.2.1).

4.4.3 Inspection procedure.

4.4.3.1 For examination. Sample launchers and the preparation for delivery shall be examined with the classification of defects and with MIL-STD-105.

4.4.3.2 For leakage. Each launcher in the lot shall be tested in accordance with 4.4.4.2.

4.4.3.3 For destructive test. Sample launchers shall be tested in accordance with table II and MIL-STD-105 using an AQL of 4.0 percent defective with the following exceptions.

(1) M8 grenade dud. Launcher sample size of 13: Accept 3, reject 4. Launcher sample size of 20: Accept 4, reject 5.

(2) Any launcher lot sample which fails to eject the grenades to the specified impact distance shall be cause for rejection.

TABLE II. Functioning

Attribute	Test
Misfires	4.4.4.3
Short range	4.4.4.3
Sabot fails to separate	4.4.4.3

4.4.3.4 Classification of defects.

(a) Launcher and grenades, smoke: HC, M226 (Dwg D13-12-26).

Categories	Defects	Acceptance standard
Critical:	None defined	
Major:	AQL 0.10 percent defective	
101	Component missing or incorrectly assembled	4.4.4.1

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

AQL 1.0 percent defective

102	Gasket seal missing
*103	Excessive scoring of cap crimp
104	Marking incorrect or illegible
105	Dent in surface of cap
106	Workmanship (3.10)

*Definite cut or groove on the crimped metal surface of the cap caused by excessive pressure or misalignment of the roller.

(b) Preparation for delivery (section 5).

Categories	Defects
Critical:	None defined
Major:	AQL 4.0 percent defective
101	Loose pack
102	Loose strap
103	Marking incorrect or illegible

4.4.4 Tests.

4.4.4.1 Radiographic or fluoroscopic evaluation. The launcher shall be evaluated in accordance with Inspection Standard R14-16.

4.4.4.2 Leakage. The launcher shall be submerged in a horizontal position in water at the specified temperature, to a depth of 1 ± 1/4 inch for the required period of time. The water shall contain a wetting agent to prevent bubbles from clinging to the surface of the launcher.

4.4.4.3 Functioning. The launcher shall be fired from the APE1951-0000 test fixture at the specified elevation. The range shall be measured from the aft end of the launcher.

5. PREPARATION FOR DELIVERY

5.1 Packaging, level A. Eight grenade launchers shall be packed in accordance with Drawing D13-12-28. The box or the wood parts thereof shall be preserved by completely immersing in a water-repellent wood preservative conforming to type I or II, composition A, of TT-W-572 for a minimum period of 3 minutes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

5.2 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with Drawing D13-12-29.

5.3 Palletization. When specified in the contract or order, grenade launchers packed in accordance with 5.1 shall be palletized and marked in accordance with Drawing D13-12-30.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification
(b) The shipment group size and marking when required.
(c) Palletization when required.
(d) Preproduction.

(1) Time allowed for supplier's submission of samples for Government test and evaluation after award of contract.
(2) Destination of samples when testing is performed by the Government.
(3) Packing, shipping and marking instruction when applicable.
(4) Time required for the Government to notify the supplier whether to proceed with production.

6.2 Definitions.

(1) Dent. Surface irregularity not introduced during normal manufacturing process.
(2) Dud. Grenade malfunction due to a mechanical or pyrotechnic failure.
(3) Misfire. Launcher does not eject grenades when functioned.

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 1330-A120

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

DOD-314

OFFICIAL BUSINESS

Commander
US ARMY ARMAMENT RESEARCH &
DEVELOPMENT COMMAND
Attn: DRDAR-TSC-S
Aberdeen Proving Ground, MD 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.