MILITARY SPECIFICATION

LAUNCHER AND GRENADES, SMOKE:

HC, M226, COMPONENTS FOR

This specification is approved for use by US Army Armament Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the components of the M226 launcher.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-1168	-	Lot Numbering of Ammunition.

FSC 1330

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn: DRDAR-TSC-S, Aberdeen Proving Ground, MD 21010 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter. :

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:00Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY ARMAMENT RESEARCH & DEVELOPMENT COMMAND

EDGEWOOD ARSENAL

D13-12-26 - Launcher and Grenades, Smoke: HC M226.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules and regulations should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM Standards

D883-65aT .. Tentative Nomenclature Relating to Plastics.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

3. REQUIREMENTS

3.1 Materials. All materials cited on Drawing D13-12-26 and on the subsidiary drawings shall conform to the specification thereon or to the specific characteristics set forth on the drawings. All plastic material (glass fiber reinforced polypropylene) shall contain 40 ± 5 percent glass fiber by weight.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:00Z
Check the source to verify that this is the current version before use.

3.2 Tube burst pressure. The tube (Drawing D13-12-31) shall withstand a minimum internal hydrostatic pressure of 325 pounds per square inch gage (psig) at a distance of 2 ± 1/16 inch from the inside surface of the base when tested in accordance with 4.4.4.1.

3.3 Cap leakage. The assembled and sealed cap shall not leak nor become distorted when subjected to an internal air pressure of 5.5 ± 0.5 psig in accordance with 4.4.4.2.

3.4 Cap hardness. The final material condition of the cap body shall be temper 0 with a maximum hardness limit of 50 when tested in accordance with 4.4.4.3.

3.5 Preproduction. Prior to the start of regular production, a preproduction sample of components shall be produced in accordance with this specification for examination and test (see 4.3).

3.6 Cap push-out. The assembled and sealed cap shall require a force of no less than 1,900 pounds (lb) nor greater than 1,700 lb to push out the cap end disc when tested in accordance with 4.4.4.4.

3.7 Workmanship. The components shall be free from foreign matter and damage (chips, breaks and cracks) that would adversely affect normal assembly and subsequent functioning.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:00Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of 5 plastic components plus a minimum total of 30 additional sets of each plastic component (for Government test) shall be produced and selected in equal quantities from each mold cavity, using the same methods, materials, equipment, and processes as will be used in regular production. In addition, a preproduction sample of 5 aluminum caps plus a minimum total of 30 additional caps (for Government test) shall be produced from the same dies, using the same methods, materials, equipment and processes as will be used in regular production. Each of the additional 30 plastic components and aluminum caps shall be subjected to all the applicable examinations and non-destructive tests.

4.3.2 Inspection procedure.

4.3.2.1 For examination and nondestructive tests. The preproduction sample shall be examined in accordance with the list of defects and tested in accordance with 4.4.4.2.

4.3.2.2 For destructive test, (tube pressure, cap hardness and cap push-out). The preproduction sample shall be tested in accordance with 4.4.4.1, 4.4.4.3 and 4.4.4.4 as applicable; these tubes shall not be used for production purposes.

4.3.3 Acceptance/rejection criteria. The preproduction sample shall comply with the examinations and tests specified herein to be acceptable. The supplier shall obtain written approval from the contracting officer prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. Each lot shall be identified and controlled in accordance with MIL-STD-1168. However, no more than one batch (see 6.2) from one manufacturer shall be contained in any one lot of plastic components.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:00Z
Check the source to verify that this is the current version before use.

4.4.2 Sampling.

4.4.2.1 For examination. At the beginning and at the completion of production, one or more components shall be taken from each die producing the end item, and from each mold cavity for examination. In the event of a failure or repair to the mold, one or more components shall be taken to requalify the mold. During production, the quantity and frequency of these examinations shall be at the discretion of the supplier, but shall be no less than one component from each mold cavity in every six hours of production.

4.4.2.2 For destructive tests (tube pressure, cap hardness, and cap push-out). Sampling shall be conducted in accordance with MIL-STD-105, level S-4, using an AQL of 2.5 for each test.

4.4.3 Inspection procedure.

4.4.3.1 For examination. Sample components shall be examined in accordance with the list of defects. If one or more than one component fails to comply with the applicable requirement, the components represented shall be rejected back to the last acceptable examination.

4.4.3.2 For tests.

(a) Nondestructive (cap leakage). Each cap in the lot shall be tested in accordance with 4.4.4.2.

(b) Destructive (tube pressure, cap hardness and cap push-out). Sample caps and tubes shall be tested in accordance with 4.4.4.1, 4.4.4.3, and 4.4.4.4 and MIL-STD-105, using an AQL of 2.5 percent defective for each test.

4.4.3.3 List of defects.

(a) Tube (Dwg D13-12-31).

*1. Cracks
2. Thread missing or incorrect
3. Eccentricity between O.D. of boss and pitch diameter of thread excessive
4. Eccentricity between O.D. and pitch diameter of thread excessive
5. Wall thickness (2 places) minimum
6. Flatness plane on I.D. excessive

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:00Z
Check the source to verify that this is the current version before use.

7. Taper on I.D. incorrect
8. Inside depth of tube incorrect
9. Cartridge hole diameter incorrect
10. Groove incorrect or incorrectly located
11. Dimension 0.359 incorrect
12. Tape missing or incorrectly applied
13. Workmanship (3.7)

...ned in ASTM designation D883-65aT.

(b) Holder (Dwg D13-12-3).

1. Grenade cradle I.D. incorrect
2. Length of grenade cradle incorrect
3. Locating hole spacing incorrect
4. Overall length incorrect
5. Eccentricity among O.D., undercut and extreme diameter of cavity section incorrect
6. Workmanship (3.7)

(c) Cover (Dwg D13-12-4).

1. I.D. incorrect
2. Locating pin spacing incorrect
3. Overall length incorrect
4. Cutout location incorrect
5. Locating tab incorrect
6. Workmanship (3.7)

(d) Spacer (Dwg B13-12-27).

1. O.D. incorrect
2. Thickness incorrect
3. Location of riser incorrect
4. Overall height 0.81 incorrect
5. Diameter 2.48 incorrect
6. Diameter 2.13 incorrect
7. Workmanship (3.7)

(e) Retainer (Dwg C13-12-6).

1. Thread incorrect
2. Eccentricity among thread, counterbore and hole excessive
3. Counterbore diameter incorrect

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:00Z
Check the source to verify that this is the current version before use.

4. Counterbore depth incorrect
5. Length incorrect
6. Wrench pocket incorrect
7. Wrench pocket location incorrect
8. Radius missing
9. Workmanship (3.7)

(f) Cap (Dwg C13-12-17)

1. Min I.D. incorrect
2. Max I.D. incorrect
3. I.D. at offset incorrect
4. Dimension 1.812 incorrect
5. Dimension 0.410 incorrect
6. Angle 45 degree incorrect
7. Protective coating and sealer missing or incorrectly applied
8. Dents in surface
9. Workmanship (3.7)

(g) Seal (Dwg B13-12-10).

1. Width incorrect
2. I.D. incorrect
3. Thickness incorrect

4.4.4 Tests.

4.4.4.1 Tube pressure. The tube shall be placed in a test fixture so that the tube is sealed at a distance of 2 ± 1/16 inch from the inside surface of the base. The internal section of the tube shall then be subjected to the specified pressure at a uniform rate within a period of 5 seconds. Test shall be conducted at ambient temperature. These tubes shall be identified as test items and shall not be used for production purposes.

4.4.4.2 Cap leakage. The assembled and sealed cap shall be placed in a test fixture and subjected to the specified pressure for a period of 15 to 20 seconds. Visual observation shall start when the gage reaches the required pressure and continues through the entire time cycle. Upon completion of the test, the caps shall be thoroughly cleaned and dried.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:00Z
Check the source to verify that this is the current version before use.

4.4.4.3 Hardness. The hardness of the cap body shall be determined by using a superficial hardness tester with a 15-T scale, 1/16 inch ball and a 15-kilogram load. A minimum of two readings shall be taken at various points - on the skirt along the bottom of the cap and at a point half way up the cap.

4.4.4.4 Cap push-out test. The cap shall be placed in a test fixture and subjected to the required force. The force shall be applied to a minimum diameter of 3.05 inches to the inside surface of the disc at a rate of 1/2 inch per minute.

5. PREPARATION FOR DELIVERY

5.1 Packaging, level C. The components shall be packaged to provide adequate protection against corrosion, deterioration and damage from the supply source to the first receiving activity for immediate use or for storage under controlled humidity conditions.

5.2 Packing, level C. The components, packaged as specified in 5.1 shall be packed to insure carrier acceptance and safe delivery to the first domestic destination. Containers shall be in compliance with Uniform Freight Classification rules or the regulations of other common carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages, intermediate packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Preproduction.

(1) Time allowed for supplier's submission of samples for Government test and evaluation after award of contract.
(2) Destination of samples when testing is performed by the Government.
(3) Packing, shipping and marking instructions when applicable.
(4) Time required for the Government to notify the supplier whether to proceed with production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:00Z
Check the source to verify that this is the current version before use.

6.2 Batch. A batch is defined as that quantity of material which has been manufactured by some chemical process and subjected to some physical mixing operation intended to make the final product substantially uniform.

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 1330-A119

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:00Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DOD-314

OFFICIAL BUSINESS

Commander
US ARMY ARMAMENT RESEARCH &
DEVELOPMENT COMMAND
Attn: DRDAR-TSC-S
Aberdeen Proving Ground, MD 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:00Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:00Z
Check the source to verify that this is the current version before use.