MILITARY SPECIFICATION

WIRING HARNESS, RELAY ASSEMBLY, TRAINING, FOR M109E1

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of relay assembly wiring harness entitled Wiring Harness, Relay Assembly Training for M109E1K which is used with the Nike Hercules warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1167	- Ammunition Data Card.
MIL-STD-1168	- Lot Numbering of Ammunition.
MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components.
MIL-STD-1460	- Soldering of Electrical Connections and Printed Wiring Assemblies, Procedure For.

DRAWINGS

ORDNANCE CORPS

8825043	- Wiring Harness, Relay Assembly, M109E1.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The training wiring harness shall comply with all requirements specified on the drawing (dwg) 8825043, with all requirements specified herein and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Painting and marking. All exterior surfaces except wiring and electrical components shall be painted black.

3.5 Continuity. There shall be point-to-point continuity in accordance with dwg 8825043 when tested as specified in 4.4.1.

3.6 Circuit and contact resistance. The resistance of each circuit together with the connectors associated with it shall not exceed the values specified in Table V when tested as specified in 4.4.2.

3.7 Insulation resistance. The resistance between electrically isolated circuits and ungrounded circuits shall not be less than 20 megohms when subjected to a direct current (dc) potential of 500 ± 50 volts when tested as specified in 4.4.3.

3.8 Soldering. All soldering shall comply with the requirements specified in MIL-STD-1460.

3.9 Workmanship.

3.9.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.9.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.9.3 Burrs. Parts shall be free from burrs.

3.9.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.9.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

3.9.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 3 complete assemblies (see dwg 8825043) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests shall be conducted in order specified in Table I.

Table I

First article inspection and tests

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics (see 4.3.2.1)		X
2. Continuity (see 3.5)		X
3. Circuit and contact resistance (see 3.6)		X
4. Insulation resistance (see 3.7)		X

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table II
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Wiring harness, relay assembly (see dwg 8825043).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Marking misleading or unidentifiable	Visual
102.	Solder loose, inadequate, or cold solder joints (see 3.8)	Visual
103.	Solder loose on terminals	Manual
104.	Any operation incomplete or missing	Visual/Manual
105.	Any component damage, insecure, or missing	Visual/Manual
106.	Connector pins damaged or improperly positioned	Visual
107.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.9)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Preservation, packing, and packaging not in accordance with MIL-STD-1169	Visual
	102. Marking not in accordance with MIL-STD-1169	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.9)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Continuity	Major
b. Circuit and contact resistance	Major
c. Insulation resistance	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Continuity, circuit and contact resistance, and insulation resistance. Each training wire harness shall be tested in accordance with 4.4.1, 4.4.2 and 4.4.3. If any item fails to comply with 3.5, 3.6 and 3.7, the item shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major and Minor characteristics and tests. Inspection and testing shall be performed with the acceptance test equipment, operating instructions and calibration instructions prepared by the contractor. The contractor shall obtain approval of such designs, operating instructions and special calibration instructions as specified in 6.3 prior to use on the contract.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.4.1 Continuity. The training wiring harness shall be tested for electrical continuity of all circuits and for proper function of relays (see dwg 8825051) using an approved testing device.

4.4.2 Circuit and contact resistance. The resistance of each circuit together with the connectors associated with it shall be tested with a current flow of 100 milliamperes at a potential of 5.5 ± 0.5 volts dc. The values of resistance for the various circuits shall be as specified in Table V. Each relay coil shall be operated at its rated power when specified in Table V. The procedure for energizing relay coils shall be as specified in Table IV.

Table IV

To Energize	Apply Rated Current at	From	To
K101	28 ± 2 volts dc	J8-N	Ground
K102	15 ± 2 volts dc	J8-M	Ground
K103	28 ± 2 volts dc	J8-X	J8-B
K104	28 ± 2 volts dc	J2-A	J6-f
K105	28 ± 2 volts dc	P3-C	Ground
K201	28 ± 2 volts dc	J8-W	Ground
K202	15 ± 2 volts dc	J8-M	J2-f
K203	28 ± 2 volts dc	J8-E	J8-G
K204	28 ± 2 volts dc	J2-c	J7-f
K205	28 ± 2 volts dc	P4-C	Ground

Table V

From	To	Ohms (Max)	From	To	Ohms (Max)
J1-T	J1-U	0.1	J1-G	J1-H	0.1
J1-T	J1-U	0.1	J1-G	J3-E	0.1
J1-T	J3-N	0.1	J1-G	P4-H	0.1
J1-T	J4-A	0.1	J1-A	J1-R	0.1
J1-T	J4-C	0.1	J1-A	J6-F	0.1
J1-T	J5-E	0.1	J1-C	J3-I	0.1
J1-T	J5-G	0.1	J1-C	J7-S	0.1
J1-T	J5-J	0.1	J1-E	J1-V	0.1
J1-T	J5-S	0.1	J1-T	J8-C	0.1
J1-T	J6-E	0.1	J1-T	J8-V	0.1
J1-T	J7-R	0.1	J1-T	J9-O	0.1
J1-a	J7-a	0.1	J1-T	J9-P	0.1
J1-D	J2-I	0.1	J1-T	J9-R	0.1
J1-D	J6-a	0.1	J1-T	J9-T	0.1
			J1-T	Ground	0.1
J1-T	J9-g	0.1	J2-g	J8-B	220 ± 11

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table V (Cont)

From	To	Ohms (Max)	From	To	Ohms (Max)
J1-T	P2-M	0.1	J2-g	P3-H	0.15 Eng. K102
J1-T	P2-V	0.1	J2-k	P3-H	0.15 Eng. K202
J1-L	J2-G	0.1	J2-J	J5-F	0.1
J1-L	J3-J	0.1	J2-J	J6-G	0.1
J1-W	J1-X	0.1	J2-J	J6-c	0.15 Eng. K103
J1-W	J3-F	0.1	J2-J	J6-c	0.15 Eng. K203
J1-W	P3-D	0.1	J2-O	J6-X	0.1
J1-N	J1-P	0.1	J2-M	J6-c	0.1
J1-N	J3-M	0.1	J2-R	J4-D	0.1
J1-a	J2-b	0.1	J2-R	J5-D	0.1
J1-S	J7-G	0.1	J2-R	J6-d	0.1
J1-Y	J8-P	0.1	J2-R	J2-U	0.15 Eng. K104
J2-V	J6-h	0.1	J2-R	J2-U	0.15 Eng. K204
J2-S	J8-X	0.15 Eng. K105	J2-N	J6-b	0.1
J1-E	J3-O	0.1	J2-N	J7-E	0.15 Eng. K103
J1-B	J3-K	0.1	J2-N	J7-E	0.15 Eng. K203
J1-B	J6-S	0.1	J2-h	J9-N	0.1
J1-d	J5-L	0.1	J2-Z	J9-N	0.1
J1-b	J5-N	0.1	J2-Z	J7-N	0.1
J1-M	J6-R	0.1	J2-L	J6-P	0.1
J1-M	J2-C	0.15 Eng. K104	J2-L	J9-c	0.1
J1-M	J2-C	0.15 Eng. K204	J2-L	J6-N	0.1
J1-Z	J2-H	0.1	J2-Y	J9-K	12 $\pm$ .36
J1-Z	J2-B	0.2	J2-K	J9-B	12 $\pm$ .36
J1-J	J5-P	0.15 Eng. K101	J2-D	J8-E	0.1 $\pm$
J1-J	J5-P	0.15 Eng. K201	J2-D	J7-T	0.1
J1-F	J9-C	0.1	J2-D	J2-T	0.15 Eng. K105
J1-S	J3-P	0.1	J2-D	J2-T	0.15 Eng. K205
J1-K	J5-T	0.15 Eng. K101	J2-j	P4-D	0.15 Eng. K202
J1-K	J5-T	0.15 Eng. K201	J2-f	J8-M	66 $\pm$ 3.3
J1-F	J6-Y	0.1	J3-B	J6-V	0.1 $\pm$
J2-E	J6-j	0.1	J3-B	P3-B	50 + 1.5
J2-E	J9-D	0.1	J3-C	J7-b	0.1
J2-E	J6-k	0.1	J3-C	J8-M	0.1
J2-Z	J7-P	0.1	J3-C	J7-X	0.15
J2-S	J8-X	0.15 Eng. K205	J3-C	J3-N	66 $\pm$ 3.3
J2-g	J6-T	0.1	J3-G	J8-A	0.1 $\pm$
J2-g	J8-X	0.1	J3-A	J8-F	0.1
J2-P	J9-U	0.1	J6-Z	J9-b	0.1
J2-d	J5-H	0.1	J6-e	P3-E	0.1
J2-d	J7-E	0.1	J6-H	J9-d	0.1
J2-e	J4-B	0.1	J2-X	J7-k	0.1
J2-e	J5-K	0.1	J6-B	P1-E	0.1
J2-e	J7-d	0.1	J6-L	J8-K	0.1

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table V (Cont)

From	To	Ohms (Max)	From	To	Ohms (Max)
J2-e	J2-U	0.15 Eng. K104	J6-L	P2-T	0.1
J2-e	J2-U	0.15 Eng. K204	J6-f	P2-C	0.1
J2-a	P1-D	0.1	J6-M	J8-L	0.1
J2-a	P1-P	0.1	J6-M	P2-S	0.1
J2-a	J7-X	0.15	J6-g	P1-H	0.1
J2-A	P2-C	220 ± 11	J6-C	P1-J	0.1
J2-c	P2-W	220 ± 11	J6-A	P1-S	0.1
J2-W	J7-1	0.1	J6-J	J8-H	0.1
J2-W	J9-G	0.1	J6-J	P2-R	0.1
J2-W	J7-m	0.1	J6-K	J8-J	0.1
J2-F	J6-I	0.1	J6-K	P2-K	0.1
J2-F	J9-L	0.1	J7-e	P4-L	0.1
J2-F	J6-m	0.1	J7-H	J9-A	0.1
J2-X	J7-j	0.1	J7-F	J9-F	0.1
J2-X	J9-I	0.1	J7-A	P1-R	0.1
J3-L	J8-B	0.1	J7-Z	J8-D	0.1
J3-L	J3-N	0.15 Eng. K103	J7-Z	J9-k	0.1
J3-D	J7-V	0.1	J6-W	J9-f	0.1
J3-D	P4-D	50 ± 1.5	J7-h	J8-Y	0.1
J3-H	J8-G	0.1	J7-h	J7-R	0.2
J3-H	J8-E	220 ± 11	J7-U	P4-E	0.1
J3-H	J3-N	0.15 Eng. K203	J7-Y	J8-R	0.1
J5-R	J6-D	0.1	J7-Y	P1-B	0.1
J5-C	P1-C	0.1	J7-D	J2-C	0.1
J5-C	P1-M	0.1	J8-N	P3-H	0.1
J5-C	P1-V	0.1	J8-N	J8-C	220 ± 11
J5-C	P1-W	0.1	J8-N	P3-D	0.15 Eng. K101
J5-M	P2-D	0.1	J8-N	P3-D	0.15 Eng. K201
J5-M	P2-L	0.1	J8-W	P4-D	0.1
J5-M	P2-N	0.1	J8-W	J8-C	220 ± 11
J5-M	P2-P	0.1	J8-W	J8-E	0.15 Eng. K102
J6-U	P3-L	0.1	J8-W	P4-H	0.15 Eng. K101
J6-Z	J8-U	0.1	J8-W	P4-H	0.15 Eng. K201
J9-h	P3-C	0.1	J7-B	P1-K	0.1
J9-h	P3-F	0.1	J7-C	P1-T	0.1
J9-h	J9-O	220 ± 11	J9-h	P3-D	0.15 Eng. K105
J9-h	J9-M	0.15 Eng. K102	J9-Y	P4-C	0.1
J7-J	J8-Z	0.1	J9-Y	P4-F	0.1
J7-J	P2-E	0.1	J9-Y	J9-O	220 ± 11
J7-g	P1-A	0.1	J9-Y	J9-e	0.15 Eng. K202
J7-f	P2-W	0.1	J9-Y	P4-H	0.15 Eng. K205
J7-K	J8-a	0.1	J9-J	P1-L	0.1
J7-K	P2-J	0.1	J9-J	P1-N	0.1
J7-L	J8-S	0.1	J9-J	J9-O	0.1

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table V (Cont)

From	To	Ohms (Max)	From	To	Ohms (Max)
J7-L	P2-H	0.1	J9-H	P4-J	0.1
J7-M	J8-T	0.1	P1-X	P2-X	0.1
J7-M	P2-A	0.1	P1-F	P1-U	Inf.
J7-c	J9-E	0.1	P2-B	P3-J	0.1
J7-W	J8-b	0.1	P2-F	P2-U	Inf.
J7-W	J9-j	0.1	P3-K	P4-K	0.1

4.4.4 Insulation resistance. Each connector contact listed in Table VI shall be subjected to the dc potential until a steady reading is obtained, using an insulation resistance tester from which a direct reading in megohms can be made.

Table VI

Pin Energized	All Other Pins to Ground Except	Megohms (Min)
J1-L	J2-G and J3-J	100
J1-W	J1-X, J3-F and P3-D	100
J1-N	J1-P and J3-M	100
J1-a	J2-b and J7-a	100
J1-D	J2-I and J6-a	100
J1-G	J1-H, J3-E and P4-H	100
J1-A	J1-R and J6-F	100
J1-C	J3-I and J7-S	100
J1-E	J1-V and J3-O	100
J1-B	J3-K and J6-S	100
J1-d	J5-L	100
J1-b	J5-N	100
J1-M	J6-R	100
J1-Z	J2-H and J2-B	100
J1-J	None	100
J1-K	None	100
J1-F	J6-Y and J9-C	100
J1-S	J3-P and J7-G	100
J1-Y	J8-P	100
J2-V	J6-h	100
J2-S	None	100
J2-T	None	100
J2-j	None	100
J2-k	None	100
J2-J	J5-F and J6-G	100
J2-O	J6-X	100
J2-M	J6-c	100
J2-C	J7-D	100
J2-R	J4-D, J5-D, and J6-d	100

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table VI (Cont)

Pin Energized	All Other Pins to Ground Except	Megohms (Min)
J2-N	J6-b	100
J2-h	J9-V	100
J2-P	J9-u	100
J2-d	J5-H and J7-E	100
J2-e	J4-B, J5-K and J7-d	100
J2-W	J7-1, J7-m and J9-G	100
J2-F	J6-1, J6-m and J9-L	100
J2-X	J7-j, J7-k and J9-1	100
J2-E	J6-j, J6-k and J9-D	100
J2-Z	J7-P, J7-N and J9-N	100
J2-L	J6-P, J6-N and J9-c	100
J2-Y	J9-K	100
J2-K	J9-B	100
J3-G	J8-A	100
J3-A	J8-F	100
J5-T	None	100
J5-P	None	100
J5-R	J6-D	100
J5-C	P1-C, P1-M, P1-V and P1-W	100
J5-M	P2-D, P2-L, P2-N and P2-P	100
J6-U	P3-L	100
J6-Z	J8-u and J9-b	100
J6-e	P3-E	100
J6-H	J9-d	100
J6-W	J9-f	100
J6-B	P1-E	100
J6-L	J8-K and P2-T	100
J6-M	J8-L and P2-S	100
J6-C	P1-J	100
J6-g	P1-H	100
J6-A	P1-S	100
J6-J	J8-H and P2-R	100
J6-K	J8-J and P2-K	100
J7-e	P4-L	100
J7-H	J9-A	100
J7-F	J9-F	100
J7-A	P1-R	100
J7-Z	J8-D and J9-k	100
J7-J	J8-Z and P2-E	100
J7-g	P1-A	100
J7-K	J8-a and P2-J	100
J7-L	J8-S and P2-H	100
J7-M	J8-T and P2-A	100
J7-c	J9-E	100
J7-W	J8-b and J9-j	100

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table VI (Cont)

Pin Energized	All Other Pins to Ground Except	Megohms (Min)
J7-B	P1-K	100
J7-C	P1-T	100
J7-U	P4-E	100
J7-Y	J8-R and P1-B	100
J9-M	None	100
J9-e	None	100
J9-H	P4-J	100
P1-X	P2-X	100
P2-B	P3-J	100
P3-K	P4-K	100

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The training wire harness shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.1.2 Level C. The training wire harness shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.2 Packing.

5.2.1 Levels A and C. The training wire harness shall be packed in accordance with the applicable instructions contained in MIL-STD-1169.

5.3 Marking. Marking shall be in accordance with MIL-STD-1169.

5.4 Data cards. Data cards shall be prepared in accordance with MIL-STD-1167.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.

b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 and 5.4 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description X-PA-PD-1762 dated 8 October 1959 and Amendment 1 dated 16 May 1962.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1135-A193

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.