MILITARY SPECIFICATION

RECEIVER, OXYGEN MASK, ASSEMBLY OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the oxygen mask receiver assembly used to attach the MBU-5/P oxygen mask to the protective helmet assembly for air crewmembers.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

QQ-A-591	Aluminum Alloy Die Castings
QQ-A-250	Aluminum Alloy Plate and Sheet, General Specification for
QQ-W-321	Wire, Copper Alloy
TT-E-491	Enamel, Gloss, Synthetic

Military

MIL-P-116	Preservation, Methods of
MIL-A-8625	Anodic Coatings for Aluminum and Aluminum Alloys
MIL-S-5059	Steel, Corrosion Resistant (18-8), Plate, Sheet and Strip
MIL-P-8585	Primer Coating, Zinc Chromatic, Low-Moisture-Sensitivity

STANDARDS

Military

MIL-STD-100	Engineering Drawing Practices
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of U.S. Military Property

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

MIL-STD-143	Standards and Specifications, Order of Precedence for the Selection of
MIL-STD-794	Parts and Equipment, Procedures for Packaging and Packing of
MIL-STD-831	Test Reports, Preparation of
MS122118	Insert, CRES, Helical Coil Coarse Thread, 1-1/2 dia Nominal Length
MS35335	Washer, Lock, Flat-External Tooth
MS51957	Screw, Machine-Pan Head, Cross Recessed, Corrosion-Resisting Steel UNC-2A

DRAWINGS

60B4462	Bottom Mounting Plate, Jaw Assembly
60B4464	Top Mounting Plate, Jaw Assembly
60B4465	Back Plate, Housing
60B4466	Nameplate, Receiver
60C4459	Receiver, Oxygen Mask, Assembly of
60C4461	Jaw,Receiver, Assembly of
60C4463	Jaw, Receiver
60D4460	Housing, Oxygen Mask Receiver
62A4257	Rivet, Tubular, Receiver Jaw
70280	Bayonet, Offset, Double Eyelet

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing Materials Standard

B303	Copper Infiltrated Sintered Carbon Steel

(Application for copies should be addressed to the American Society for Testing Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

3. REQUIREMENTS

3.1 Qualification. The receiver assembly furnished under this specification shall be products which have been subjected to and which have passed the qualification tests specified herein, and which have been listed on or approved for listing on the applicable Qualified Products List.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

3.2 Selection of specification and standards. Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

3.3 Materials. Materials shall conform to applicable specifications and shall be as specified herein and on applicable drawings. Materials which are not covered by specifications, or which are not specifically described herein, shall be of the best quality, of the lightest practicable weight, and suitable for the purpose intended.

3.3.1 Metals. Metals shall be of the corrosion-resistant type or suitably treated to resist corrosion due to fuels, salt spray, or atmospheric conditions likely to occur in storage or normal service. Metals shall be protected against such corrosion in a manner that will in no way prevent compliance with the performance requirements of this specification. The use of any protective treatment that will crack, chip, or scale with age or extremes of atmospheric conditions shall be avoided.

3.4 Design and construction. The oxygen mask receiver assembly shall be complete when the receiver jaw assembly is in position within the receiver housing and the nameplate attached to the top of the housing with lock washers, MS35335-58, and machine screws, MS51957-28. Also, the backplate must be attached to the housing with lock washers, MS35335-58, and machine screws MS51957-26 and MS51957-28. The receiver assembly shall conform to AF Drawing 60C4459.

3.4.1 Nameplate. The nameplate shall be made of aluminum alloy, temper T4, 0.020 inches thick, per Federal Specification QQ-A-250/4 and shall conform to AF Drawing 60B4466.

3.4.2 Backplate. The backplate shall be made of stainless steel, composition 301, 1/4 hard, per MIL-S-5059 and shall conform to AF Drawing 60B4465.

3.4.3 Receiver housing. The housing shall be made of aluminum alloy 380.0 per Federal Specification QQ-A-591 and shall conform to AF Drawing 60D4460 complete with helical coil inserts per MS122118. The housing (prior to installing helical coil inserts) shall be anodized per MIL-A-8625, type II, class 1. The exterior surface of the housing shall be coated with zinc chromate primer per MIL-P-8585 after anodizing. The exterior surface shall then be painted with white enamel, class B per TT-E-491.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

3.4.4 Jaw assembly. The jaw assembly shall be assembled in accordance with AF Drawing 60C4461. The jaw assembly is composed of a top mounting plate, 60B4462, a bottom mounting plate, 60B4464, jaws, 60C4463, and rivets, 62A4257.

3.4.4.1 Mounting plates. Both mounting plates shall be made of stainless steel, composition 301, 1/4 hard per MIL-S-5059 and shall conform to AF Drawings 60B4462 and 60B4464.

3.4.4.2 Jaws. The jaws shall be made of copper infiltrated sintered carbon steel, class C per ASTM B303.

3.4.4.3 Rivets. The rivets shall be made of copper alloy, alloy number 260, temper 1/2 hard per QQ-W-321. The rivets shall conform to AF Drawing 62A4257.

3.5 Performance.

3.5.1 Receiver assembly. The receiver assembly when fully prepared according to this specification shall pass the visual examination and the pull test specified in paragraph 4.5.1 and 4.5.2.

3.6 Interchangeability. All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable. The drawing number requirements of MIL-STD-100 shall govern changes in the manufacturer's part numbers.

3.7 Identification of product. The receiver assembly shall have the following information impregnated or stamped on the nameplate surface in accordance with AF Drawing 60B4466.

*Manufacturer's Name or Code
P/N 60C4459
*Contract No

* Manufacturer shall include the applicable information.

3.8 Workmanship. The receiver assembly shall be uniform in quality and shall be free from irregularities, defects or foreign matter which could adversely affect safety, performance, reliability or durability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any other commercial laboratory acceptable to the Government. The Government reserves the right

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The examination and testing of the receiver assembly shall be classified as follows:

(a) Qualification inspection. Qualification inspection consists of examinations and tests performed on samples submitted for approval as qualified products.

(b) Quality conformance inspection consists of examinations and tests performed on individual products or lots to determine conformance of the products or lots with the requirements set forth in this specification.

4.3 Qualification inspection. Qualification inspection shall consist of all the examinations and tests of this specification.

4.3.1 Qualification samples. Three receiver assemblies shall be prepared in accordance with this specification and shall be submitted to the procuring activity for qualification. The receiver assembly shall be representative of the production item.

4.3.2 Qualification test report. The contractor shall prepare three copies of a test report in accordance with MIL-STD-831 and submit it to the qualifying activity. The test report shall contain detailed statements, identified by the applicable paragraph number of this specification, of compliance or non-compliance with each requirement of this specification.

4.4 Quality conformance inspection. Quality conformance inspection shall consist of the following examinations and tests.

4.4.1 Individual tests. Each receiver assembly shall be visually examined per paragraph 4.5.1.

4.4.2 Sampling tests. Three receiver assemblies selected at random from each lot of 100 or less, shall be subjected to the pull test per paragraph 4.5.2.

4.4.2.1 Rejection and retest. When one or more items from a lot fail to meet the specification, acceptance of all items in the lot shall be withheld until the extent and cause of failure have been determined. The contractor shall explain fully to the Government representative the cause of failure and the action taken to preclude recurrence. After correction, all of the sampling tests shall be repeated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

4.4.2.2 Individual tests may continue. For production reasons, individual tests or other sampling plans may be continued pending the investigation of a sampling test failure. But final acceptance of the entire lot or lots produced later shall not be made until it is determined that all items meet all the requirements of the specification.

4.4.3 Defects in items already accepted. The investigation of a test failure could indicate that defects may exist in items already accepted. If so, the contractor shall fully advise the procuring activity of all the defects likely to be found and the method of correcting them.

4.5 Test methods.

4.5.1 Visual examination. The receiver assembly shall be visually examined according to Table I. One major defect or 10 minor defects out of a lot shall constitute rejection.

TABLE I. CLASSIFICATION OF DEFECTS FOR VISUAL EXAMINATION

MAJOR	MINOR
1. Dimensions not within tolerance limits.	101. Identification illegible or missing.
2. Screws missing or threads stripped.	102. Screws not tight or securely attached to the receiver.
3. Jaw assembly not in proper position within housing.	103. Color not conforming to specification.
4. Any material not conforming to specification.	
5. Any part or component missing from receiver assembly.	
6. Any defect which hinders the function of the receiver assembly.	

4.5.2 Pull test. The receiver assembly with a bayonet per AF Drawing numbers 70280 inserted shall withstand a maximum separating force of 500 pounds without damage to the receiver. A pull force shall be applied to the receiver engagement, while the bayonet is being rocked in a plane coinciding with the receiver jaw assembly, in increments of 25 pounds until the force reaches 200 pounds. The receiver shall then be subjected to a pull force of 500 pounds and the connection shall not fail.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

Any damage or distortion to the receiver assembly during any part of the test constitutes rejection.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Unless otherwise specified by the procuring activity, each Oxygen Mask Receiver shall be prepared for delivery in accordance with MIL-STD-794, Level A, B or C (See 6.2 for level.)

5.1.1 Level A.

5.1.1.1 Cleaning. Each Oxygen Mask Receiver shall be cleaned in accordance with Method C1 of Specification MIL-P-116.

5.1.1.2 Drying. Each Oxygen Mask Receiver shall be dried to remove any residue moisture or cleaning solution by utilizing any of the drying methods of Specification MIL-P-116, providing the method is not injurious to the item.

5.1.1.3 Preservation application. Preservation of each Oxygen Mask Receiver shall be accomplished without the use of preservative compounds, oil or grease.

5.1.1.4 Unit packaging. All wrapping, cushioning, dunnage and containers used in the packaging shall be completely free of contamination by oil and grease. The Oxygen Mask Receiver shall be packaged in accordance with Method III of MIL-P-116, in a greaseproof-waterproof bag without preservatives.

5.1.1.5 Intermediate Packaging. Intermediate containers shall not exceed a maximum of 40 pounds net weight, and a maximum of 1.5 cubic feet with either of the two dimensions exceeding 16 inches.

5.1.2 Level B. (Same as Level A)

5.1.3 Level C. Cleaning, drying, preservation and packaging shall be in accordance with the manufacturer's commercial practice.

5.2 Packing. Packing shall be Level A, B, or C as specified (See 6.2 for level.)

5.2.1 Level A. Each Oxygen Mask Receiver preserved and packaged as specified in 5.1.1.4 shall be packed in exterior type containers. The containers used shall be closed, sealed and reinforced in accordance with the applicable specification thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. All Oxygen Mask Receivers preserved and packaged as specified in paragraph 5.1.1.4 shall be packed in domestic type containers. The containers used shall be closed, sealed and reinforced in accordance with the applicable specification thereto.

5.2.3 Level C. All packaged Oxygen Mask Receivers which require overpacking for acceptance by the carrier, shall be packed in exterior type shipping containers in a manner that will insure safe transportation at the lowest freight rate, to the point of delivery. Containers shall meet the uniform freight classification rules or regulations of the common carrier as applicable to the mode of transportation.

5.3 Marking. In addition to any special markings required by the contract or order, unit packages, intermediate packages and shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

5.4 Precautionary markings. Caution: Do not allow oil or contaminants of any kind to be used on or about Oxygen Mask Receivers.

6. NOTES

6.1 Intended use. The receiver assembly mentioned herein shall be used as an attachment to the aircrew member's helmet assembly and shall use the oxygen mask bayonet assembly as its mating connection.

6.2 Ordering data. Procurement documents shall specify the following:

(a) Title, number and date of this specification.

(b) List of interchangeable components and assemblies.

(c) Copy of QPL test report (see 4.3.2).

(d) Level of packing.

6.3 Data. For the information of contractors and contracting officers, any of the data specified in applicable documents listed in Section 2 of this specification or referenced lower-tier documents need not be prepared for the Government and shall not be furnished to the Government unless specified in the contract or order. The data to be furnished shall be listed on DD Form 1423 (Contractor Data Requirements List), which shall be attached to and made a part of the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

6.4 Qualification. With respect to products requiring qualification, awards will be made only for such products as have, prior to the time set for the opening of bids, been tested and approved for inclusion in the applicable Qualified Products List, whether or not such products have actually been so listed by that date. The attention of the suppliers is called to this requirement, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the Qualified Products List is the Oklahoma City ALC/MMEO Tinker AFB Oklahoma 73145 and information pertaining to qualification of products may be obtained from that activity.

Custodian:
Air Force - 71

Preparing Activity:
Air Force - 71

Reviewer:
Air Force - 11

Project Number:
1660-F111

☆ U. S. GOVERNMENT PRINTING OFFICE: 1974-603-109/1040

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

FOLD

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE AIR FORCE
DoD-318

Oklahoma City ALC/MMEO
Tinker AFB, OK 73145

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

C 16061

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.