NOTICE OF CANCELLATION

INCH-POUND

MS24392F
NOTICE 2
21 January 2009
SUPERSEDING
NOTICE 1
28 September 1999

MILITARY STANDARD

NIPPLE, TUBE, PRECISION TYPE

MS24392F, dated 16 April 1982, is hereby canceled. Future acquisitions for this item should refer to SAE-AS5174, "Fitting, Union and Reducer, Flared."

(Copies of these documents are available online at http://www.sae.org or from the SAE World Headquarters, 400 Commonwealth Drive, Warrendale, PA 15096-0001.)

Reason for NOTICE 2: SAE inactivated Part or Identifying Numbers (PIN) with material code letter D for replacement parts and for new design to use code letter W. This is because code letter W is stronger in tensile strength than code letter D. This is based on the previous PA's revision, as a result of lessons learned. Plus to add back material code letter S for replacement parts and for new design to use code letter R. The code letter R is better for applications requiring higher temperature.

Table l provides a detailed cross-reference of cancelled MS24392F PINs and replacement SAE-AS5174 PINs.

CAUTION: The supersession information is valid as of the date of this notice and may be superseded by subsequent revisions of the superseding document.

CONCLUDING MATERIAL

Custodians:
Army - AV
Navy - AS
Air Force - 99
DLA - CC

Preparing activity:
DLA - CC

(Project 4730-2008-084)

Review activities:
Army - AR, CR4
Navy - CG, MC, SA, SH
Air Force - 71

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

AMSC N/A

FSC 4730

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:53Z
Check the source to verify that this is the current version before use.

TABLE I. MS24392F to SAE-AS5174, cross-reference data.

Cancelled MS PIN	Tube Size	Replacement AS PIN
MS24392-2	.125	AS5174-0202
MS24392D2	.125	AS5174D0202 1/
MS24392D2	.125	AS5174W0202 2/
MS24392J2	.125	AS5174J0202
MS24392K2	.125	AS5174K0202
MS24392S2	.125	AS5174S0202 3/
MS24392S2	.125	AS5174R0202 4/
MS24392T2	.125	AS5174T0202
MS24392W2	.125	AS5174W0202
MS24392-3	.188	AS5174-0303
MS24392D3	.188	AS5174D0303 1/
MS24392D3	.188	AS5174W0303 2/
MS24392J3	.188	AS5174J0303
MS24392K3	.188	AS5174K0303
MS24392S3	.188	AS5174S0303 3/
MS24392S3	.188	AS5174R0303 4/
MS24392T3	.188	AS5174T0303
MS24392W3	.188	AS5174W0303
MS24392-4	.250	AS5174-0404
MS24392D4	.250	AS5174D0404 1/
MS24392D4	.250	AS5174W0404 2/
MS24392J4	.250	AS5174J0404
MS24392K4	.250	AS5174K0404
MS24392S4	.250	AS5174S0404 3/
MS24392S4	.250	AS5174R0404 4/
MS24392T4	.250	AS5174T0404
MS24392W4	.250	AS5174W0404
MS24392-5	.312	AS5174-0505 5/
MS24392D5	.312	AS5174D0505 1/,5/
MS24392D5	.312	AS5174W0505 2/,5/
MS24392J5	.312	AS5174J0505 5/
MS24392K5	.312	AS5174K0505 5/
MS24392S5	.312	AS5174S0505 3/,5/
MS24392S5	.312	AS5174R0505 5/,4/
MS24392T5	.312	AS5174T0505 5/
MS24392W5	.312	AS5174W0505 5/
MS24392-6	.375	AS5174-0606
MS24392D6	.375	AS5174D0606 1/
MS24392D6	.375	AS5174W0606 2/
MS24392J6	.375	AS5174J0606
MS24392K6	.375	AS5174K0606
MS24392-8	.500	AS5174-0808
MS24392D8	.500	AS5174D0808 1/
MS24392D8	.500	AS5174W0808 2/
MS24392J8	.500	AS5174J0808
MS24392K8	.500	AS5174K0808
MS24392S8	.500	AS5174S0808 3/
MS24392S8	.500	AS5174R0808 4/
MS24392T8	.500	AS5174T0808
MS24392W8	.500	AS5174W0808
MS24392-10	.625	AS5174-1010
MS24392D10	.625	AS5174D1010 1/
MS24392D10	.625	AS5174W1010 2/
MS24392J10	.625	AS5174J1010
MS24392K10	.625	AS5174K1010
MS24392S10	.625	AS5174S1010 3/
MS24392S10	.625	AS5174R1010 4/
MS24392T10	.625	AS5174T1010
MS24392W10	.625	AS5174W1010
MS24392-12	.750	AS5174-1212
MS24392D12	.750	AS5174D1212 1/
MS24392D12	.750	AS5174W1212 2/
MS24392J12	.750	AS5174J1212
MS24392K12	.750	AS5174K1212
MS24392S12	.750	AS5174S1212 3/
MS24392S12	.750	AS5174R1212 4/
MS24392T12	.750	AS5174T1212
MS24392W12	.750	AS5174W1212
MS24392-16	1.000	AS5174-1616
MS24392D16	1.000	AS5174D1616 1/
MS24392D16	1.000	AS5174W1616 2/
MS24392J16	1.000	AS5174J1616
MS24392K16	1.000	AS5174K1616
MS24392S16	1.000	AS5174S1616 3/
MS24392S16	1.000	AS5174R1616 4/
MS24392T16	1.000	AS5174T1616
MS24392W16	1.000	AS5174W1616
MS24392-20	1.250	AS5174-2020
MS24392D20	1.250	AS5174D2020 1/
MS24392D20	1.250	AS5174W2020 2/
MS24392J20	1.250	AS5174J2020
MS24392K20	1.250	AS5174K2020

See notes at end of tables.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:53Z
Check the source to verify that this is the current version before use.

TABLE I. MS24392F to SAE-AS5174, cross-reference data – Continued.

Cancelled MS PIN	Tube Size	Replacement MS PIN
MS24392S6	.375	AS5174S0606 3/
MS24392S6	.375	AS5174R0606 4/
MS24392T6	.375	AS5174T0606
MS24392W6	.375	AS5174W0606
MS24392-24	1.500	AS5174-2424
MS24392D24	1.500	AS5174D2424 1/
MS24392D24	1.500	AS5174W2424 2/
MS24392J24	1.500	AS5174J2424
MS24392K24	1.500	AS5174K2424
MS24392S24	1.500	AS5174S2424 3/
MS24392S24	1.500	AS5174R2424 4/
MS24392T24	1.500	AS5174T2424
MS24392W24	1.500	AS5174W2424
MS24392-28	1.750	AS5174-2828
MS24392D24	1.750	AS5174D2424 1/
MS24392D24	1.750	AS5174W2424 2/
MS24392J28	1.750	AS5174J2828
MS24392K28	1.750	AS5174K2828
MS24392S28	1.750	AS5174S2828 3/
MS24392S28	1.750	AS5174R2828 4/
MS24392T28	1.750	AS5174T2828
MS24392W28	1.750	AS5174W2828
MS24392-32	2.000	AS5174-3232
MS24392D32	2.000	AS5174D3232 1/
MS24392D32	2.000	AS5174W3232 2/
MS24392J32	2.000	AS5174J3232
MS24392K32	2.000	AS5174K3232
MS24392S32	2.000	AS5174S3232 3/
MS24392S32	2.000	AS5174R3232 4/
MS24392T32	2.000	AS5174T3232
MS24392W32	2.000	AS5174W3232

Cancelled MS PIN	Tube Size	Replacement MS PIN
MS24392S20	1.250	AS5174S2020 3/
MS24392S20	1.250	AS5174R2020 4/
MS24392T20	1.250	AS5174T2020
MS24392W20	1.250	AS5174W2020
MS24392-40	2.500	AS5174-4040
MS24392D40	2.500	AS5174D4040 1/
MS24392D40	2.500	AS5174W4040 2/
MS24392J40	2.500	AS5174J4040
MS24392K40	2.500	AS5174K4040
MS24392S40	2.500	AS5174S4040 3/
MS24392S40	2.500	AS5174R4040 4/
MS24392T40	2.500	AS5174T4040
MS24392W40	2.500	AS5174W4040
MS24392-48	3.000	AS5174-4848
MS24392D40	3.000	AS5174D4040 1/
MS24392D40	3.000	AS5174W4040 2/
MS24392J48	3.000	AS5174J4848
MS24392K48	3.000	AS5174K4848
MS24392S48	3.000	AS5174S4848 3/
MS24392S48	3.000	AS5174R4848 4/
MS24392T48	3.000	AS5174T4848
MS24392W48	3.000	AS5174W4848

1/ For replacements parts, use code letter “D”. Reason: SAE G3 and DoD-SAE liaisons agreed to use code “D” for replacement PINs.

2/ For new design parts, use code letter “W” . Reason: SAE G3 and DoD-SAE liaisons agreed to use code “W” for new design.

3/ For replacement parts use code letter “S”. Reason: SAE G3 and DoD-SAE liaisons agreed to use code “S” for replacement PINs.

4/ For new design parts use code Letter “R”. Reason: SAE G3 and DoD-SAE liaisons agreed to use code “R” for new design.

5/ Users are cautioned that the overall length of the "AS" part is less than the overall length of the "MS" part.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:53Z
Check the source to verify that this is the current version before use.