NOTICE OF CANCELLATION

INCH-POUND

MS24395G
NOTICE 2
1 December 2010
SUPERSEDING
NOTICE 1
22 April 1999

MILITARY STANDARD

# TEE, TUBE, BULKHEAD, PRECISION TYPE

MS24395G, dated 16 April 1982, is hereby cancelled. Future acquisitions for this item should refer to SAE-AS1039, " Fitting, Tee, Standard and Reducer, Bulkhead On Side, Flared".

(Copies of these documents are available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), www.sae.org.)

Reason for NOTICE 2: SAE inactivated Part or Identifying Number (PIN) with material code letter D for replacement parts and for new design to use code letter W. This is because code letter W is stronger in tensile strength than code letter D. This is based on the previous PA's revision, as a result of lessons learned. Plus to add back material code letter S for replacement parts and for new design to use code letter R. The code letter R is better for applications requiring higher temperature.

Table l provides a detailed cross-reference of cancelled MS24395G PINs and replacement SAE-AS1039 PINs.

CAUTION: The supersession information is valid as of the date of this notice and may be superseded by subsequent revisions of the superseding document.

## CONCLUDING MATERIAL

Custodians:
Army - AV
Navy - AS
Air Force – 99
DLA - CC

Preparing activity:
DLA - CC

(Project 4730-2010-054)

Review activities:
Army – AR, CR4
Navy – MC, SA
Air Force – 11, 71

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

AMSC N/C

FSC 4730

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:53Z
Check the source to verify that this is the current version before use.

TABLE I. MS24395G to SAE-AS1039, cross-reference data.

| Cancelled AN PIN | Tube Size | Replacement AS PIN | New Design | Cancelled AN PIN | Tube Size | Replacement AS PIN | New Design |
|---|---|---|---|---|---|---|---|
| MS24395-2 | .125 | AS1039-020202 | | MS24395-8 | .500 | AS1039-080808 | |
| MS24395D2 | .125 | AS1039D020202 | AS1039W020202 | MS24395D8 | .500 | AS1039D080808 | AS1039W080808 |
| MS24395J2 | .125 | AS1039J020202 | | MS24395J8 | .500 | AS1039J080808 | |
| MS24395K2 | .125 | AS1039K020202 | | MS24395K8 | .500 | AS1039K080808 | |
| MS24395S2 | .125 | AS1039S020202 | AS1039R020202 | MS24395S8 | .500 | AS1039S080808 | AS1039R080808 |
| MS24395T2 | .125 | AS1039T020202 | | MS24395T8 | .500 | AS1039T080808 | |
| MS24395W2 | .125 | AS1039W020202 | | MS24395W8 | .500 | AS1039W080808 | |
| MS24395-3 | .188 | AS1039-030303 | | MS24395-10 | .625 | AS1039-101010 | |
| MS24395D3 | .188 | AS1039D030303 | AS1039W030303 | MS24395D10 | .625 | AS1039D101010 | AS1039W101010 |
| MS24395J3 | .188 | AS1039J030303 | | MS24395J10 | .625 | AS1039J101010 | |
| MS24395K3 | .188 | AS1039K030303 | | MS24395K10 | .625 | AS1039K101010 | |
| MS24395S3 | .188 | AS1039S030303 | AS1039R030303 | MS24395S10 | .625 | AS1039S101010 | AS1039R101010 |
| MS24395T3 | .188 | AS1039T030303 | | MS24395T10 | .625 | AS1039T101010 | |
| MS24395W3 | .188 | AS1039W030303 | | MS24395W10 | .625 | AS1039W101010 | |
| MS24395-4 | .250 | AS1039-040404 | | MS24395-12 | .750 | AS1039-121212 | |
| MS24395D4 | .250 | AS1039D040404 | AS1039W040404 | MS24395D12 | .750 | AS1039D121212 | AS1039W121212 |
| MS24395J4 | .250 | AS1039J040404 | | MS24395J12 | .750 | AS1039J121212 | |
| MS24395K4 | .250 | AS1039K040404 | | MS24395K12 | .750 | AS1039K121212 | |
| MS24395S4 | .250 | AS1039S040404 | AS1039R040404 | MS24395S12 | .750 | AS1039S121212 | AS1039R121212 |
| MS24395T4 | .250 | AS1039T040404 | | MS24395T12 | .750 | AS1039T121212 | |
| MS24395W4 | .250 | AS1039W040404 | | MS24395W12 | .750 | AS1039W121212 | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:53Z
Check the source to verify that this is the current version before use.

TABLE I. MS24395G to SAE-AS1039, cross-reference data – Continued.

| Cancelled AN PIN | Tube Size | Replacement AS PIN | New Design | Cancelled AN PIN | Tube Size | Replacement AS PIN | New Design |
|---|---|---|---|---|---|---|---|
| MS24395-5 | .312 | AS1039-050505 | | MS24395-16 | 1.000 | AS1039-161616 | |
| MS24395D5 | .312 | AS1039 D050505 | AS1039 W050505 | MS24395D16 | 1.000 | AS1039 D161616 | AS1039 W161616 |
| MS24395J5 | .312 | AS1039 J050505 | | MS24395J16 | 1.000 | AS1039 J161616 | |
| MS24395K5 | .312 | AS1039 K050505 | | MS24395K16 | 1.000 | AS1039 K161616 | |
| MS24395S5 | .312 | AS1039 S050505 | AS1039 R050505 | MS24395S16 | 1.000 | AS1039 S161616 | AS1039 R161616 |
| MS24395T5 | .312 | AS1039 T050505 | | MS24395T16 | 1.000 | AS1039 T161616 | |
| MS24395W5 | .312 | AS1039 W050505 | | MS24395W16 | 1.000 | AS1039 W161616 | |
| MS24395-6 | .375 | AS1039-060606 | | MS24395-20 | 1.250 | AS1039-202020 | |
| MS24395D6 | .375 | AS1039 D060606 | AS1039 W060606 | MS24395D20 | 1.250 | AS1039 D202020 | AS1039 W202020 |
| MS24395J6 | .375 | AS1039 J060606 | | MS24395J20 | 1.250 | AS1039 J202020 | |
| MS24395K6 | .375 | AS1039 K060606 | | MS24395K20 | 1.250 | AS1039 K202020 | |
| MS24395S6 | .375 | AS1039 S060606 | AS1039 R060606 | MS24395S20 | 1.250 | AS1039 S202020 | AS1039 R202020 |
| MS24395T6 | .375 | AS1039 T060606 | | MS24395T20 | 1.250 | AS1039 T202020 | |
| MS24395W6 | .375 | AS1039 W060606 | | MS24395W20 | 1.250 | AS1039 W202020 | |
| MS24395-24 | 1.500 | AS1039-242424 | | MS24395-28 | 1.750 | AS1039-282828 | |
| MS24395D24 | 1.500 | AS1039 D242424 | AS1039 W242424 | MS24395D28 | 1.750 | AS1039 D282828 | AS1039 W282828 |
| MS24395J24 | 1.500 | AS1039 J242424 | | MS24395J28 | 1.750 | AS1039 J282828 | |
| MS24395K24 | 1.500 | AS1039 K242424 | | MS24395K28 | 1.750 | AS1039 K282828 | |
| MS24395S24 | 1.500 | AS1039 S242424 | AS1039 R242424 | MS24395S28 | 1.750 | AS1039 S282828 | AS1039 R282828 |
| MS24395T24 | 1.500 | AS1039 T242424 | | MS24395T28 | 1.750 | AS1039 T282828 | |
| MS24395W24 | 1.500 | AS1039 W242424 | | MS24395W28 | 1.750 | AS1039 W282828 | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:53Z
Check the source to verify that this is the current version before use.

TABLE I. MS24395G to SAE-AS1039, cross-reference data – Continued.

| Cancelled AN PIN | Tube Size | Replacement AS PIN | New Design |
|---|---|---|---|
| MS24395-32 | 2.000 | AS1039-323232 | |
| MS24395D32 | 2.000 | AS1039 D323232 | AS1039 W323232 |
| MS24395J32 | 2.000 | AS1039 J323232 | |
| MS24395K32 | 2.000 | AS1039 K323232 | |
| MS24395S32 | 2.000 | AS1039 S323232 | AS1039 R323232 |
| MS24395T32 | 2.000 | AS1039 T323232 | |
| MS24395W32 | 2.000 | AS1039 W323232 | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:53Z
Check the source to verify that this is the current version before use.