
INCH POUND
MIL-DTL-9395/32C
30 May 2001
SUPERSEDING
MIL-S-9395/32B
23 September 1982

DETAIL SPECIFICATION SHEET

SWITCHES, PRESSURE, DIFFERENTIAL (TYPE III), 4 AMPERES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the pressure switches described herein shall consist of this specification sheet and the latest issue of MIL-DTL-9395.




WEIGTH: NOT TO EXCEED .8 lbs.

Configuration 1

FIGURE 1. Switches, pressure, differential, type III.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:16Z
Check the source to verify that this is the current version before use.




WEIGHT: NOT TO EXCEED .8 lbs

Configuration 2

FIGURE 1. Switches, pressure, differential, type III - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:16Z
Check the source to verify that this is the current version before use.




WEIGHT: NOT TO EXCEED .8 lbs

Configuration 3

FIGURE 1. Switches, pressure, differential, type III - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:16Z
Check the source to verify that this is the current version before use.



INCHES	MM
.03	.76
.050	1.27
.06	1.52
.225	5.71
.57	14.48
.70	17.78
.82	20.83
1.055	26.80
1.069	27.15
1.14	28.96
1.31	33.27
1.937	49.20
2.118	53.80
2.132	54.15
2.40	60.96
2.62	66.55
2.75	69.85
3.50	88.90

Configuration 4

WEIGHT: NOT TO EXCEED .97 lbs

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1 inch =25.4 mm.
3. Unless otherwise specified, tolerance is ±.02 (.51 mm).

FIGURE 1. Switches, pressure, differential, type III - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:16Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, weight, and electrical schematic: See figure 1.

Calibration: See tables I, II, III, and IV.

Proof pressure: 250 lb_f/in^2g high over low and simultaneously.

System pressure: 125 lb_f/in^2g high over low and simultaneously.

Burst pressure: 500 lb_f/in^2g high over low and simultaneously.

Electrical ratings: Operating voltage - 28 Vdc. Current rating - 4 amperes resistive, 2 amperes inductive.

Seal:

High pressure chamber: Media proof. During this test the low pressure chamber shall be open to atmosphere. Subject switches to proof pressure for 2 minutes using hydraulic fluid per MIL-H-5606 with chamber pressure continuously being monitored. Isolate the chamber at proof pressure with the chamber disconnected from the pressure source. Under that condition, the pressure shall not drop more than 1 lb_f/in^2g for the first 30 seconds to allow stabilization of test equipment; no pressure loss is allowed thereafter.

Low pressure chamber: Media proof. Test as above except low pressure port is connected to high pressure port.

Electrical chamber: See table I.

Electrical connector: See figure 1.

Pressure port: See figure 1.

Media: Dry air; nitrogen; fuel per MIL-DTL-5624; oil per MIL-PRF-7808; or hydraulic fluid per MIL-H-5606.

High temperature (operating and nonoperating): C (350°F).

Low temperature (operating and nonoperating): D (-65°F).

Altitude: C (70,000 feet).

Shock: C (100 G).

Vibration: S (test condition D, method 204 of MIL-STD-202).

Life mechanical: A (100,000 cycles).

Life electrical: C (50,000 cycles).

Acceleration: C (8 G).

Pulsation amplitude: A (0 percent).

Pulsation frequency: A (0 Hz).

Pressure rise: B (more than 1,000 $lb_f/in^2/s$).

Dielectric withstanding voltage (at reduced barometric pressure): Applicable.

Connector torque: Applicable.

Flame test: Applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:16Z
Check the source to verify that this is the current version before use.

Explosion: Applicable.


QUALIFICATION:

Single submission: Restricted to switch submitted.

Group submission: See table V.

Part number: Part numbers shall be as follows:

Example:



Note: Design limitations (actuation values and tolerances, deadband and deactuation values and tolerances) should be coordinated with the manufacturer(s) listed on the QPL for this specification sheet before specifying a particular "M" number. The fact that operating characteristics can be coded does not necessarily mean that it can be manufactured or acquired.

TABLE I. Codes for combinations of configurations and pressure setting modes.

	Configuration 1		Configuration 2		Pressure	
	Electrical chamber		Electrical chamber		High setting	High setting
	Hermetic	Unsealed	Hermetic	Unsealed		
Code	A	D	G	K	At (or max) 1/	At (or min) 1/
Code	B	E	H	L	At (or max) 1/	Deadband 2/
Code	C	F	J	M	Deadband 2/	At (or min) 1/
	Configuration 3		Configuration 4		Pressure setting mode	
	Electrical chamber		Electrical chamber		High	Low
	Hermetic	Unsealed	Hermetic	Unsealed	setting	setting
Code	N	R	U	X	At (or max) 1/	At (or min) 1/
Code	P	S	V	Y	At (or max) 1/	Deadband 2/
Code	Q	T	W	Z	Deadband 2/	At (or min) 1/

1/ Setting values are designated by codes from tables II and III.

2/ Setting values are designated by codes from tables II and IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:16Z
Check the source to verify that this is the current version before use.

TABLE II. Codes for coarse settings.

Code	Coarse value (lb_f/in^2d)	Code	Coarse value (lb_f/in^2d)	Code	Coarse value(lb_f/in^2d)
A	0	L	30	W	80
B	2-1/2	M	35	X	85
C	5	N	40	Y	90
D	7-1/2	P	45	Z	95
E	10	Q	50	1	100
F	12-1/2	R	55	2	105
G	15	S	60	3	110
H	17-1/2	T	65	4	115
J	20	U	70	5	120
K	25	V	75	6	125

TABLE III. Codes for combinations of fine settings and tolerances values.

	Fine value (lb_f/in^2d) for settings below 20 lb_f/in^2d					Tolerance (lb_f/in^2)
	0	½	1	1 1/2	2	
Code	A	B	C	D	E	±1/2 lb_f/in^2d
Code	F	G	H	J	K	±1 lb_f/in^2d
Code	L	M	N	P	Q	±2 lb_f/in^2d
Code	R	S	T	U	V	±3 lb_f/in^2d
Code	W	X	Y	Z	1	±5 lb_f/in^2d
Code	2	3	4	5	6	±8 lb_f/in^2d
Code	7	8	9	0	+	Min or Max
	Fine value (lb_f/in^2d) for settings below 20 lb_f/in^2d and above					Tolerance (lb_f/in^2)
	0	½	1	1 1/2	2	
Code	A	B	C	D	E	±1 lb_f/in^2d 1/
Code	F	G	H	J	K	±2 lb_f/in^2d 2/
Code	L	M	N	P	Q	±3 lb_f/in^2d 3/
Code	R	S	T	U	V	±5 lb_f/in^2d
Code	W	X	Y	Z	1	±8 lb_f/in^2d
Code	2	3	4	5	6	±15 lb_f/in^2d
Code	7	8	9	0	+	Min or Max

1/ Not applicable for pressure settings above 33 lb_f/in^2d.
2/ Not applicable for pressure settings above 66 lb_f/in^2d.
3/ Not applicable for pressure settings above 100 lb_f/in^2d.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:16Z
Check the source to verify that this is the current version before use.

TABLE IV. Codes for deadband settings.

Code	Deadband value (lb_f/in^2d)	Code	Deadband value (lb_f/in^2d)
A	0	T	11
B	1/2	U	12
C	1	V	13
D	1-1/2	W	14
E	2	X	15
F	2-1/2	Y	16
G	3	Z	18
H	3-1/2	1	20
J	4	2	22
K	4-1/2	3	24
L	5	4	26
M	5-1/2	5	28
N	6	6	30
P	7	7	35
Q	8	8	40
R	9	9	45
S	10	0	50

TABLE V. Extent of qualification.

Part number M9395/32-	Number of samples required	Tests	Qualifies
ABAAC GBAAC A6R3M N6R3M	2 each resistive 2 each resistive 2 each inductive 2 each inductive	Complete per qualification inspection of MIL-DTL-9395	ALL

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AT, AV
Navy - AS, MC, SH
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5930-1730-12)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:16Z
Check the source to verify that this is the current version before use.