INCH-POUND
MIL-DTL-9395/38D
24 September 2018
SUPERSEDING
MIL-DTL-9395/38C
3 October 2006

DETAIL SPECIFICATION SHEET

SWITCHES, PRESSURE, (GAGE) TYPE II, LOW LEVEL TO 5 AMPERES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the switches described herein shall consist of this document and MIL-DTL-9395.





FIGURE 1. Switches.

AMSC N/A

FSC 5930

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:17Z
Check the source to verify that this is the current version before use.



Inches	mm
.055	1.40
.12	3.0
.55	14.0
.688	17.48
.813	20.65
2.5	64.
2.8	71.

WEIGHT: NOT TO EXCEED 0.3 POUNDS

CONFIGURATION 2

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Exact shape of switch is optional provided outline dimensions specified are not exceeded and connector locations are as specified.
4. Schematics shown are for switches with pressure ports exposed to zero lb_f/in^2.
5. MS27467T11B989S details are found in MS27467. MS33656E3 and MS33656E4 details are found in SAE-AS4395.

FIGURE 1. Switches - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:17Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, configurations, and electrical schematic: See figure 1.

Weight: See figure 1.

Calibration: See tables I, II, III, and IV.

System pressure: 125 lb_f/in^2.

Proof pressure: 250 lb_f/in^2.

Burst pressure: 500 lb_f/in^2.

Electrical ratings: See table I.
Minimum current: 25,000 cycles.
Low level: 50,000 cycles.
NOTE: Switches shall be subjected only to low level loads prior to delivery.

Seal:
Electrical chamber: See table I.
Pressure chamber: Hermatic.
Reference chamber: Unsealed.

Electrical connector: See figure 1.

Pressure port: See figure 1.

Media: Dry air; nitrogen gas; fuel IAW MIL-DTL-5624; lubricating oil IAW MIL-PRF-7808; hydraulic fluid IW MIL-PRF-6083 or MIL-PRF-83282; oxygen; or Coolanol 25R, or equal.

High temperature (operating and nonoperating): D (400°F and 500°F for 30 minutes).

Low temperature (operating and nonoperating): D (-65°F).

Altitude: C (except 80,000 ft).

Shock: C (100 G).

Vibration: S (test condition D of MIL-STD-202-204, except 10 to 2,000 Hz, 20 G).

Life (mechanical): A (100,000 cycles).

Life (electrical): C (50, 000 cycles).

Acceleration: C (8 G).

Pulsation amplitude: A (0 %).

Pulsation frequency: A (0 Hz).

Pressure rise: A (less than 100 lb_f/in^2).

Dielectric withstanding voltage (at reduced barometric pressure): Applicable at 350 V rms.

Electrical connector torque: 8 foot-pounds.

Switch mounting torque: 15 foot-pounds.

Terminal strength: Applicable.

Flame test: Applicable.

Explosion: Applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:17Z
Check the source to verify that this is the current version before use.

QUALIFICATION:

Single submission: Restricted to switch submitted.
Group submission: See table V.

PART NUMBER: Consists of "M" prefix followed by specification sheet number; a dash (-); and a five-letter code. The five-letter code identifies the configuration, electrical rating, and pressure setting mode (code from table I); high-pressure setting (coarse value code from table II) followed by fine value with applicable tolerance (code from table III); and low-pressure setting (coarse value code from table II) followed by fine value with applicable tolerance (code from table III). The five-letter code used in the following example identifies a switch of configuration 1, low level to 1 ampere resistive at 28 V dc, which actuates on increasing pressure at 1.5 ±0.5 lb_f/in^2 and deactuates on decreasing pressure at 0.5 ±0.5 lb_f/in^2.

EXAMPLE:

M9395/38- A AJ AG

"M" PREFIX AND SPECIFICATION SHEET NUMBER

CONFIGURATION, ELECTRICAL, RATING, AND PRESSURE SETTING MODE = Code "A" of table I

HIGH-PRESSURE SETTING = Code "A" of table II (coarse value of 0 lb_f/in^2 and Code "J" of table III (fine value of 1.5 ± 0.5 lb_f/in^2).

LOW-PRESSURE SETTING = Code "A" of table II (coarse value of 0 lb_f/in^2 and code "G" of table III (fine value of 0.5 ± 0.5 lb_f/in^2).

NOTE: Design limitations (actuation values and tolerances, deadband and deactuation values and tolerances) should be coordinated with the manufacturer(s) listed on the QPL for this spec sheet before specifying a particular "M" number. The fact that operating characteristics can be coded does not necessarily mean that it can be manufactured or procured.

TABLE I. Codes for combinations of configurations, electrical ratings, and pressure settings modes.

	Low level to 1 A resistive at 28 Vdc				1.5 to 5 A resistice at 28 Vdc				Pressure setting mode	
	Configuration				Configuration					
	1		2		1		2			
	Electrical chamber		Electrical chamber		Electrical chamber		Electrical chamber		High setting	Low setting
	Hermetic	Unsealed	Hermetic	Unsealed	Hermetic	Unsealed	Hermetic	Unsealed		
Code	A	D	G	K	N	R	U	X	At (or max) 1/	At (or min) 1/
Code	B	E	H	L	P	S	V	Y	At (or max) 1/	Differential 2/
Code	C	F	J	M	Q	T	W	Z	Differential 2/	At (or min) 1/

1/ Setting values are designated by codes from table II and III.
2/ Setting values are designated by codes from table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:17Z
Check the source to verify that this is the current version before use.

TABLE II. Codes for coarse settings.

Code	Coarse value (lb_f/in^2)	Code	Coarse value (lb_f/in^2)	Code	Coarse value (lb_f/in^2)
A	0	L	30	W	80
B	2.5	M	35	X	85
C	5	N	40	Y	90
D	7.5	P	45	Z	95
E	10	Q	50	1	100
F	12.5	R	55	2	105
G	15	S	60	3	110
H	17.5	T	65	4	115
J	20	U	70	5	120
K	25	V	75	6	125

TABLE III. Codes for combinations of fine settings and tolerance values.

	Fine value (lb_f/in^2) for settings below 20 lb_f/in^2					Tolerance (lb_f/in^2)
	0	0.5	1	1.5	2	
Code	A	B	C	D	E	±0.25
Code	F	G	H	J	K	±0.5
Code	L	M	N	P	Q	±1.0
Code	R	S	T	U	V	±1.5
Code	W	X	Y	Z	1	±2.0
Code	2	3	4	5	6	±2.5
Code	7	8	9	0	-	Min or Max
	Fine value (lb_f/in^2) for settings of 20 lb_f/in^2 and above					Tolerance (lb_f/in^2)
	0	1	2	3	4	
Code	A	B	C	D	E	±1.0 1/
Code	F	G	H	J	K	±2.0 2/
Code	L	M	N	P	Q	±3.0 3/
Code	R	S	T	U	V	±4.0
Code	W	X	Y	Z	1	±5.0
Code	2	3	4	5	6	±6.0
Code	7	8	9	0	-	Min or Max

1/ Not applicable for pressure settings above 33 lb_f/in^2.
2/ Not applicable for pressure settings above 66 lb_f/in^2.
3/ Not applicable for pressure settings above 100 lb_f/in^2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:17Z
Check the source to verify that this is the current version before use.

TABLE IV. Codes for differential settings. 1/

Code	Differential value (lb_f/in^2)	Code	Differential value (lb_f/in^2)
A	0	T	11
B	0.5	U	12
C	1	V	13
D	1.5	W	14
E	2	X	15
F	2.5	Y	16
G	3	Z	18
H	3.5	1	20
J	4	2	22
K	4.5	3	24
L	5	4	26
M	5.5	5	28
N	6	6	30
P	7	7	35
Q	8	8	40
R	9	9	45
S	10	0	50

1/ Differential settings require two codes, minimum differential and maximum differential.

TABLE V. Extent of qualification.

Part number	No. of samples required	Tests	Qualifies
ELECTRICAL CHAMBERS EITHER HERMETICALLY SEALED OR UNSEALED			
M9395/38-AAEAH -NAEAH -N6R4R A6R4R	2 ea. resistive 2 ea. intmd current 2 ea. low level 2 ea. resistive	Complete IAW qualification inspection on MIL-DTL-9395	All
ELECTRICAL CHAMBERS UNSEALED			
M9395/38-BAEAH -DAEAH -D6R4R -X6R4R	2 ea. resistive 2 ea. intmd current 2 ea. low level 2 ea. resistive	Complete IAW qualification inspection of MIL-DTL-9395	Configuration codes D, E, F, K, L, M, R, S, T, X, Y, Z.

NOTE: Revision letters are not used to denote changes due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:17Z
Check the source to verify that this is the current version before use.

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced Documents:
- MIL-DTL-9395
- MIL-DTL-5624
- MIL-PRF-6083
- MIL-PRF-7808
- MIL-DTL-38999
- MIL-PRF-83282
- MIL-STD-202-204
- MS27467
- SAE-AS4395

Custodians:
- Army - CR
- Navy - EC
- Air Force - 85

Preparing activity:
- DLA - CC

(Project 5930-2018-045)

Review activities:
- Navy - MC, SH

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:17Z
Check the source to verify that this is the current version before use.