
INCH-POUND
MIL-DTL-9395/40E
12 August 2024
SUPERSEDING
MIL-DTL-9395/40D
24 September 2018

DETAIL SPECIFICATION SHEET

SWITCHES, PRESSURE, (GAGE), TYPE II, LOW LEVEL TO 5 AMPERE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the switches described herein shall consist of this document and MIL-DTL-9395.




CONFIGURATION 1

FIGURE 1. Switches.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.
FSC 5930

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:17Z
Check the source to verify that this is the current version before use.



DETAIL A

NOTES:
1. Dimensions are in inches.
2. Exact shape of switch is optional provided outline dimensions specified are not exceeded and connector location area is as specified.
3. Schematic shown is for switches with pressure ports exposed to zero lb_f/in^2.
4. Packing groove in accordance with MIL-G-5514.
5. Surface finish 125 roughness height reference, except where otherwise specified.
6. Surface finish IAW ASME B46.1.
7. Switch shall incorporate a redundant seal.
8. MS27467T11B35S details are found in MS27467.

FIGURE 1. Switches - Continued.

REQUIREMENTS:

Dimensions, weight, and electrical schematic: See figure 1.

Materials: All external parts including pressure port, housing, and electrical connector shall be fabricated from corrosion-resistant (stainless) steel suitable for welding. External parts shall be joined by welding; solder joints shall not be allowed.

Calibration: See tables I, II, III, and IV.

Proof pressure: 4,500 lb_f/in^2. If a vent is not used, the electrical chamber shall withstand 4500 lb_f/in^2 without rupture.

System pressure: 3,000 lb_f/in^2.

Burst pressure: 7,500 lb_f/in^2.

Vent port leakage:
Leakage rate: Shall not exceed .15 cubic centimeters in 250 cycles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:17Z
Check the source to verify that this is the current version before use.

Electrical ratings: See table I.
Minimum current: 25,000 cycles.
Low level: 50,000 cycles

NOTE: Switches shall be subjected only to low level loads prior to delivery.

Seal:
Pressure chamber: Media proof, except leakage of .15 cubic centimeters (maximum) in 250 cycles is allowed.
Electrical chamber: Hermetic.

Pressure port: See figure 1.

Media: Hydraulic fluid IAW MIL-PRF-6083 or MIL-PRF-83282.

High temperature (operating and nonoperating): B (+275°F).

Low temperature (operating and nonoperating): D (-65°F) ambient; and (-40°F) fluid.

Altitude: C (70,000 ft).

Shock: C (100 G).

Vibration: S (test condition D of MIL-STD-202-204, except 10 to 2,000 Hz, 10 G).

Life (mechanical): F (50,000 cycles).

Life (electrical): B (25,000 cycles).

Acceleration: C (8 G).




FIGURE 2 Pressure rise requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:17Z
Check the source to verify that this is the current version before use.

Pulsation amplitude: 50 to 4,050 lb_f/in^2 and back to 50 lb_f/in^2 (applied IAW figure 2).

Pulsation frequency: 65 ±5 cycles per minute.

Pressure rise: 300,000 lb_f/in^2 minimum.

Dielectric withstanding voltage (at reduced barometric pressure): Applicable.

Electrical connector torque: Applicable.


Pressure port mounting torque: 15 foot-pounds.

QUALIFICATION:

Single submission: Restricted to switch submitted.
Group submission: See table V.

PART NUMBER: Consists of "M" prefix followed by specification sheet number; a dash (-); and a five-letter code. The five-letter identifies the configuration, electrical rating, and pressure setting mode (code from table I); high-pressure setting to within 100 lbf/in1 (code from table II) followed by high-pressure setting to within 25 lb_f/in^2 and applicable tolerance (code from table III); and low-pressure setting to within 100 lb_f/in^2 (code from table II) followed by low-pressure setting to within 25 lb_f/in^2 and applicable tolerance (code from table III). The five-letter code used in the following example identifies a switch of configuration 1, low level to 1 ampere electrical rating, which actuates on increasing pressure at 300 ±25 lb_f/in^2, and deactuates on decreasing pressure at 150 ±25 lb_f/in^2.

EXAMPLE:



"M" PREFIX AND SPECIFICATION SHEET NUMBER

CONFIGURATION, ELECTRICAL RATING AND PRESSURE SETTING MODE = Code "A" of table I

HIGH-PRESSURE SETTING = Code "C" of table III (300 lb_f/in^2) and Code "A" of table II (0, ±25 lb_f/in^2).

LOW-PRESSURE SETTING = Code "A" of table II (100 lb_f/in^2) and Code "C" of table III (+50, ±25 lb_f/in^2).

NOTE: Design limitations (actuation values and tolerances, deadband and deactuation values and tolerances) should be coordinated with manufacturer(s) listed on the QPL for this specification sheet before specifying a particular "M" number. The fact that operating characteristics can be coded does not necessarily mean that it can be manufactured or acquired.

TABLE I. Codes for configurations, electrical ratings, and pressure setting modes.

	Configuration 1		Pressure setting mode	
	Low level to 1 A resistive	1.5 to 5 A resistive	High setting	Low setting
Code - -	A	D	At (or max) 1/	At (or min) 1/
Code - -	B	E	At (or max) 1/	Differential 2/
Code - -	C	F	Differential 2/	At (or min) 1/

1/ Setting values are designated by characters from tables II and III.
2/ Setting values are designated by characters from table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:17Z
Check the source to verify that this is the current version before use.

TABLE II. Codes for pressure settings to within 100 lb_f/in^2.

Code	Pressure (lb_f/in^2)	Code	Pressure (lb_f/in^2)	Code	Pressure (lb_f/in^2)	Code	Pressure (lb_f/in^2)
A	100	J	900	S	1,700	1	2,500
B	200	K	1,000	T	1,800	2	2,600
C	300	L	1,100	U	1,900	3	2,700
D	400	M	1,200	V	2,000	4	2,800
E	500	N	1,300	W	2,100	5	2,900
F	600	P	1,400	X	2,200	6	3,000
G	700	Q	1,500	Y	2,300		
H	800	R	1,600	Z	2,400		

TABLE III. Codes for pressure settings to within 25 lb_f/in^2 and tolerances.

	Unit				Tolerance
	0	+25	+50	+75	(lb_f/in^2)
Code	A	B	C	D	±25
Code	E	F	G	H	±50
Code	J	K	L	M	±75
Code	N	P	Q	R	±100
Code	S	T	U	V	±150
Code	W	X	Y	Z	±200
Code	1	2	3	4	±300
Code	5	6	7	8	±400
Code	9	0	1	-	Min or Max

TABLE IV. Codes for differential pressure settings. 1/

Code	Differential value (lb_f/in^2)	Code	Differential value (lb_f/in^2)
A	0	M	275
B	25	N	300
C	50	P	325
D	75	Q	350
E	100	R	375
F	125	S	400
G	150	T	425
H	175	U	450
J	200	V	475
K	225	W	500
L	250		

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:17Z
Check the source to verify that this is the current version before use.

TABLE V. Extent of qualification.

Part number	Number of samples required	Tests	Qualifies
M9395/40-DADAA AADAA A6N3U D6N3U	2 each resistive 2 each intermediate current 2 each low level 2 each resistive	Complete IAW qualification inspection of MIL-DTL-9395	All

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced Documents:

- MIL-DTL-9395
- MIL-G-5514
- MIL-PRF-6083
- MIL-DTL-38999
- MIL-PRF-83282
- MIL-STD-202-204
- MS27467
- ASME B46.1

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5930-2024-054)

Review activities:
Navy - MC, SH

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:17Z
Check the source to verify that this is the current version before use.