L-H-580A
April 3, 1972
SUPERSEDING
Int. Fed. Spec. L-H-00580(GSA-FSS)
July 7, 1966

FEDERAL SPECIFICATION

HOLDER, NAMEPLATE, DESK, PLASTIC

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the requirements for plastic nameplate holders. Each holder shall be supplied with a transparent nameplate cover (see 6.1).

1.2 Classification. The desk nameplate holders shall be of one type and of a color specified (see 3.3 and 6.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

L-P-504 - Plastic Sheet and Film, Cellulose Acetate.
QQ-S-781 - Strapping, Steel, Flat and Seals.
PPP-B-636 - Box, Fiberboard.
PPP-T- 97 - Tape, Pressure-Sensitive Adhesive, Filament Reinforced.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents U. S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:10Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials.

3.1.1 Nameplate holder. The nameplate holder shall be made of a suitable plastic not less than 0.100 inch thick, excluding tapered or rounded edges. The plastic shall be nonflammable, flame resistant, or slow burning, when tested as specified in 4.4.3. The nameplate holder shall retain its design contour without warping, crazing, softening, or discoloring during normal service or storage, and shall not break, crack or chip when subjected to the drop test specified in 4.4.1. The holder shall withstand the accelerated service test described in 4.4.2, without warpage or surface irregularities.

3.1.2 Nameplate cover. The nameplate cover shall be made of plastic conforming to L-P-504, type I, and shall have a thickness of 0.020 inch ± 0.002.

3.2 Design and construction.

3.2.1 Nameplate holder. The nameplate holder shall be triangular in design, but may have a hollow back. The holder shall be 9-1/2 ± 1/4 inches long, and the base, 2 ± 1/4 inches wide, and the face, 2-1/4 ± 1/4 inches wide. The face shall have a grooved slot to accommodate the paperboard nameplate and nameplate cover. The slot shall run the length of the holder and shall have an inside width dimension of 1-7/16 ± 1/16 inches. The groove shall be wide and deep enough to adequately hold and secure the paperboard nameplate (nominal thickness .056 inch) and the nameplate cover (see 3.1.2). The base of the nameplate holder shall rest evenly and squarely on a flat surface.

3.2.2 Transparent nameplate cover. The transparent nameplate cover shall be made of material as specified in 3.1.2. The nameplate cover shall be of such width so as to snugly fit the grooved slot, and the length of the cover shall be equal, or not more than 1/4 inch shorter than the length of the holder. At the option of the manufacturer, the end(s) of the cover may be folded.

3.3 Color. The color of the nameplate holders shall be gray or walnut, as specified (see 6.2).

3.4 Finish. The nameplate holder shall have a smooth and uniform surface. Extruded edges shall be rounded, and cut edges shall be smooth and free from burrs. The nameplate holder shall be free from cold bonds, delaminations, porosity, warpage, cracks, chips, blisters, or scratches. The nameplate cover shall be devoid of sharp corners and edges.

3.5 Identification marking. Each nameplate holder shall be permanently and legibly marked with the manufacturer's name or trademark.

3.6 Workmanship. The nameplate holder and cover shall be free from defects or imperfections which adversely affect appearance, or which might impair serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Size of lot. All desk nameplate holders of the same color presented for inspection at one time shall be considered a lot for the purpose of examination.

4.2.2 Sampling for inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise specified.

4.2.3 Sampling for visual and dimensional examination. Random sample desk nameplate holders shall be taken from each lot in accordance with MIL-STD-105. The sample unit shall be one desk nameplate holder. The holders shall be examined for defects listed in table I. The Inspection Level shall be S-4, and the Acceptable Quality Level (AQL) shall be 4.0 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:10Z
Check the source to verify that this is the current version before use.

4.2.4 Sampling for preparation for delivery requirements. Sampling shall be in accordance with MIL-STD-105. For examination of exterior packaging, the sample unit shall be one shipping container fully prepared for delivery and selected at random just prior to closing operation. Shipping containers fully prepared for delivery shall be examined for closure defects. The Inspection Level shall be S-4 and the AQL shall be 6.5 defects per hundred units.

4.2.5 Sampling for tests. For each test, random sample desk nameplate holders shall be selected from each lot in accordance with MIL-STD-105. The sample unit shall be one holder. The tests shall be performed as specified in 4.4. The Inspection Level shall be S-2 with an AQL of 4.0 percent defective.

4.3 Examination.

4.3.1 Visual and dimensional examination. Samples taken in accordance with 4.2.3 shall be examined for defects listed in table I. Any sample having one or more defects shall be rejected. If the number of defective units in the sample exceeds the acceptance number for that sample, the entire lot represented by the sample shall be rejected.

TABLE I. Classification for defects

Examine	Defects
Material	Material not as specified (see 3.1).
Design and construction	Design and construction not as specified (see 3.2.1 and 3.2.2).
Color	Color not as specified (see 3.3).
Finish	Finish not as specified (see 3.4).
Identification marking	Identification marking not as specified (see 3.5).
Workmanship	Workmanship not in accordance with 3.6.

4.3.2 Examination of preparation for delivery requirements. Samples selected in accordance with 4.2.4 shall be examined for defects listed in table II, to determine that packaging, packing, and marking requirements of section 5 of this specification are complied with.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Marking (exterior and interior)	Omitted; incorrect, illegible; or improper size, location, sequence, or method of application.
Material	Any component missing, or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping. Distortion of container.

4.4 Performance tests. Samples selected in accordance with 4.2.5 shall be subjected to the following tests. Any desk nameplate holder in the sample failing one or more tests shall be considered defective. If the number of defective units in the sample exceeds the acceptance number for that sample, the entire lot represented by the sample shall be rejected.

4.4.1 Drop test. Drop the holder on a concrete floor 5 times from a height of 3 feet. Position the holder so it will hit the floor at a different angle each drop. After the fifth drop examine the holder for compliance with 3.1.1. Repeat this test after subjecting the holder to the accelerated service test in 4.4.2.

4.4.2 Accelerated service test. Place the nameplate holder in a circulating air oven at a temperature of $60^{\circ} \pm 1^{\circ}C$ ($140^{\circ} \pm 1.8^{\circ}F.$) for 24 hours. Then remove the holders from the oven, cool to room temperature and check for compliance with 3.1.1. Repeat the drop test in 4.4.1 and again check for compliance with 3.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:10Z
Check the source to verify that this is the current version before use.

4.4.3 Flammability. Cut pieces of plastic approximately 3 inches long and 1/2 inch wide from the nameplate holder. In a draft free area hold the plastic specimen horizontally above a bunsen burner having a 1 to 1-1/4 inches blue flame just touching the end of the specimen until it ignites, or for a period not over 30 seconds. Remove the flame. If the specimen will not support combustion, it is non-flammable. If the specimen burns when in contact with the flame but will not continue to burn when flame is removed, it is flame resistant. If the specimen continues to burn at a rate of 2.5 inches per minute, or less, it is slow burning. If the specimen bursts into flame, or burns at a rate faster than 2.5 inches per minute it is to be considered as not meeting the requirements of this specification. (See 3.1.1.)

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Unit packaging. Each nameplate holder shall be packaged in a paperboard sleeve or plastic bag. The bag shall be closed.

5.1.1.2 Intermediate packaging. Forty-eight unit packages of nameplate holders of like description shall be intermediate packaged in a close-fitting box conforming to PPP-B-636, class weather-resistant. The box shall be closed in accordance with the appendix to the box specification.

5.1.2 Level B. The nameplate holder shall be packaged as specified in 5.1.1.1 and 5.1.1.2, except the PPP-B-636 box shall be class domestic.

5.1.3 Level C. The nameplate holders shall be packaged to afford protection against deterioration and damage from the supplier to the initial destination. The supplier may use his commercial practice provided it fulfills the above requirements.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Three intermediate packages of nameplate holders of like description shall be packed in a close-fitting box conforming to PPP-B-636, class weather-resistant. The box shall be closed, water-proofed, and strapped in accordance with the appendix to the box specification.

5.2.2 Level B. Three intermediate packages of nameplate holders of like description shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification. Alternatively, three intermediate packages of nameplate holders of like description may be banded together with flat steel strapping or tape conforming to QQ-S-781 or PPP-T-97, respectively.

5.2.3 Level C. The nameplate holders shall be packed to insure carrier acceptance and safe delivery at destination at the lowest rates, in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Standard packaging (Civil agencies). The standard packaging for civil agencies shall be as specified in 5.1.2 and 5.2.2, respectively.

5.4 Marking.

5.4.1 Civil agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.4.2 Military activities. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:10Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The nameplate holders are intended for desk top use, to hold and display printed or embossed nameplates.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents.

(a) Title, number, and date of this specification.
(b) Color required (see 3.3).
(c) Selection of applicable levels of packaging and packing and applicable marking requirements (see 5.1, 5.2, 5.3, and 5.4).

6.3 Standard pack for civil agencies. The standard pack requirements in 5.3 are intended for use in procurement of stores stock replenishments. Procuring officers should use the standard pack requirements when it is known that the material will be shipped from a supplier to a domestic warehouse, supply depot or intermediate storage point for temporary, subsequent issue, or shipment to eventual user.

DOD HAS WAIVED COORDINATION INTEREST:

Preparing activity:

GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:10Z
Check the source to verify that this is the current version before use.