L-P-00665a (GSA-FSS)
February 15, 1968
SUPERSEDING
Int. Fed. Spec. L-P-00665 (GSA-FSS)
February 20, 1964

INTERIM FEDERAL SPECIFICATION

PROTECTOR, DUPLICATING STENCIL

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20405, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE

1.1 This specification covers sheets of transparent film for placing over duplicating stencils.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specification:

PPP-B-636 - Box, Fiberboard.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).
Fed Test Method Std. No. 406 - Plastics: Methods of Testing.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Auburn, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. The duplicating stencil protector shall be made of transparent rubber hydrochloride film having a matte finish on one side and a glazed finish on the other side. The film shall conform to the physical requirements of table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:10Z
Check the source to verify that this is the current version before use.

Table I. Physical charateristics of transparent film

Property	Value 1/
Thickness, inch	0.00106
Area (yield) factor, sq. in. per lb.	22,500
Tensile strength, p. s. i.:	
Lengthwise direction	3,900
Crosswise direction	3,400

1/ A tolerance of plus or minus 10 percent will be permitted.

3.2 Length and width. The protectors shall be 18 inches long and 8-1/2 inches wide. A tolerance of plus or minus 1/16 inch in each direction of the film will be permitted.

3.3 Workmanship. The protectors shall be flat, squarely cut, and free from foreign matter, scrtches, scuffs, cracks, blisters, pits, tears, cuts, dents, holes, or other defects which may affect serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibilty for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. For purposes of sampling, a lot shall consist of all duplicating stencil protectors offered for delivery at one time.

4.2.2 Sampling for visual examination. A random sample of protectors shall be taken from each lot in accordance with MIL-STD-105, Inspection Level I, Acceptable Quality Level (AQL) of 4.0 percent defective. The sample unit shall be one box, except that three protectors, taken at random from the box, shall be examined as described in 4.3. If there are one or more defects in the sample of three protectors taken from the box, the whole box shall be considered defective and shall be rejected.

4.2.3 Sampling for tests. A random sample of protectors shall be taken from each lot in accordance with MIL-STD-105, Inspection Level S-2, AQL 2.5 percent defective. The sample unit and the rejection basis shall be as described in 4.2.2.

4.2.4 Sampling for preparation or delivery requirements. For examination of interior packages the sample unit shall be one shipping container fully prepared for delivery, and selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be II with an AQL of 4.0 defects per hundred units.

4.3 Visual examination. Samples, taken in accordance with 4.2.2., snall be examined for defects listed in table II. Any sample unit containing one or more visual defects shall be rejected. If the number of defective protectors in the sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:10Z
Check the source to verify that this is the current version before use.

Table II. Classification of protector defects

Examine	Defects
Material	Not transparent. Not rubber hydrochloride (see 4.4). Without matte finish on one side and glazed finish on the other side.
Length and width	Not within the dimensions and tolerances specified in 3.2.
Workmanship	Protector not flat and squarely cut. Protector not free from foreign matter. Protector not free from scratches, scuffs, cracks, blisters, pits, tears, cuts, dents or holes.

4.4 Certification. Unless otherwise specified, the contractor shall forward to the procuring agency for each order of protectors a certified statement (1) identifying the film by manufacturer's name, trade name, identification number and chemical nature, (2) certifying that the film of the delivery to be the same as to manufacturing process and composition as that which was tested in accordance with 4.1 and found to conform to all of the requirements of this specification, and (3) presenting the results of the material acceptance tests made by the contractor and by the producer of the film.

4.5 Test procedures. Samples, taken in accordance with 4.2.3, shall be subjected to the following tests and under the conditions specified in 4.3 of Federal Test Method Standard No. 406. Any sample failing one or more tests shall be considered defective. If the number of defective protectors in the sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.5.1 Film thickness. Thickness measurements shall be made with a calibrated micrometer or other equivalent instrument capable of measuring to 0.0005 inch.

4.5.2 Area factor. The specimen of film shall consist of not less than 100 square feet of area. Determine the weight of the specimen with a calibrated balance. Calculate the area factor from the measured area of the specimen and its weight.

4.5.3 Tensile strength. Tensile strength shall be determined in accordance with procedure B, method 1013 of Federal Test Method Standard No. 406.

4.5.4 Length and width. The length and width of the protector shall be measured with a calibrated steel rule.

4.6 Inspection of preparation for delivery requirements. An inspection shall be made to determine that packaging, packing, and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:10Z
Check the source to verify that this is the current version before use.

Table III. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; or improper size, location, sequence, or method of application.
Materials	Any component missing, or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Bulging or distortion of container.

5 PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. One hundred protectors shall be packaged in a commercial-type paperboard folding box of one-piece construction.

5.1.2 Level B. The protectors shall be packaged as specified in 5.1.1.

5.1.3 Level C. The protectors shall be packaged in accordance with the supplier's commercial practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. The protectors shall be packed in a close-fitting box conforming to PPP-B-636, class weather-resistant. The box shall be closed in accordance with the appendix of the box specification. The weight shall not exceed the weight limitations of the box specification.

5.2.2 Level B. Ten unit packages shall be packed together in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

5.2.3 Level C. The protectors shall be packed to insure carrier acceptance and safe delivery to destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The protectors covered by this specification are intended for use as a protective covering in the preparation (cutting) of duplicating machine stencils.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:10Z
Check the source to verify that this is the current version before use.