L-P-00528a (GSA-FSS)

October 15, 1964
Revision of
Int. Fed. Spec. L-P-00528 (GSA-FSS)
June 19, 1964

INTERIM FEDERAL SPECIFICATION

PLASTIC SHEET, PRESSURE SENSITIVE ADHESIVE COATED; (FOR DOCUMENT PROTECTION)

This Interim Federal Specification was developed by the General Services Administration, Federal Supply Service, Washington, D. C. 20407, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope.--This specification covers cellulose acetate and polyester plastic sheet, adhesive coated, for use in the protection of documents and cards.

1.2 Classification

1.2.1 Types and sizes.--The plastic sheet covered by this specification shall be of the following types and sizes, as specified (see 6.2):

Type I - Cellulose acetate
Type II - Polyethylene terephthalate

Sheet sizes

Width, inches	Length, inches
3	4
6	8
9	11-3/8
10	12

Roll sizes

Width, inches	Length, feet
21	50 (type I only)
26	50 (type II only)

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 Specifications and Standards. The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification:

Federal Specifications:

L-P-377 - Plastic Film, Polyethylene Terephthalate.
L-P-504 - Plastic Sheet and Film, Cellulose Acetate.
QQ-A-362 - Aluminum Alloy Plate and Sheet, Alclad 2024.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-665 - Boxes; Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676 - Boxes, Set-Up, Paperboard.
PPP-B-636 - Box, Fiberboard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:10Z
Check the source to verify that this is the current version before use.

Federal Standards:

Fed. Std. No. 1 - Standard for Laboratory Atmospheric Conditions for Testing.
Fed. Std. No. 102 - Preservation, Packaging and Packing Levels.
Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publication.--The following document forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply:

American Society for Testing and Materials (ASTM) Standards:

D 883-64T - Nomenclature Relating to Plastics.

(Copies may be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa., 19103.)

3. REQUIREMENTS

3.1 Material

3.1.1 Plastic sheet.--Type I material shall be transparent cellulose acetate conforming to type I of L-P-504. Type II material shall be polyethylene terephthalate conforming to L-P-377. The nominal thickness of the type I cellulose acetate (uncoated) shall be 0.005 inches (actual thickness shall be a minimum of 0.0045 inches and a maximum of 0.006 inches). The nominal thickness of the type II polyethylene terephthalate (uncoated) shall be 0.002 inches (actual thickness shall be a minimum of 0.0016 inches and a maximum of 0.0024 inches.)

3.1.2 Adhesive coating.--One side of the plastic sheet shall be evenly coated with a minimum of 0.001 inch thick (dry) film of a pressure-sensitive adhesive. The adhesive shall have suitable characteristics of flexibility and tackiness for the purpose intended. The adhesive shall require no moisture, heat, or other preparation prior to use of the finished plastic sheet to develop manual pressure-sensitiveness.

3.1.3 Release paper (paper backing).--The adhesive side of the plastic sheet shall be covered with a suitable release paper (paper backing). Removal of the release paper at the time of use shall not detach the adhesive nor shall it in any way interfere with the function of the plastic sheet.

3.2 Sheet dimensions.--The sheet shall be furnished in the sizes as specified (see 1.2.1 and 6.2). The tolerances on the length and width shall be plus or minus 1/16 inch.

3.3 Finish and color.--The plastic sheet shall have a polish finish on both sides. Unless otherwise specified, the film shall be colorless.

3.4 Adhesive bond.--When tested as specified in 4.4.6, the adhesive shall produce a pressure-sensitive bond such that a one-pound load will be supported.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:10Z
Check the source to verify that this is the current version before use.

3.5 Workmanship.--The plastic sheet shall be free from ragged edges, die lines, cracks, holes, pits, gel marks, blisters, discolorations and other defects which would affect the serviceability of the item. The terms cited in this paragraph shall be defined as in ASTM D 883-64T.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Responsibility for inspection.--Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot.--A lot shall consist of the material processed by one manufacturer, subjected to the same manufacturing and processing conditions.

4.2.2 Sampling for inspection.--Sampling shall be accomplished in accordance with MIL-STD-105. The inspection level shall be level II.

4.3 Inspection.

4.3.1 Visual and dimensional examination.--Each of the sample sheets selected in accordance with 4.2.2 shall be visually and dimensionally examined to verify compliance with this specification.

4.3.2 Inspection of preparation for delivery.--The packaging, packing, and marking of the sheet material shall be examined to determine conformance with the requirements of section 5 of this specification. Examinations of packaging, packing, and marking requirements not covered by the referenced specifications shall be in accordance with MIL-STD-105 using an AQL of 4.0 percent defective.

4.3.2.1 Classification of defects.

4.3.2.1.1 Packaging.

101 Sheets not packaged as specified.

4.3.2.1.2 Packing and marking.

102 Closure of boxes incorrect.
103 Gross weight of shipping container exceeds limit specified.
104 Marking missing, illegible, or incorrect.

4.3.3 Testing of the end item.--The end item shall be tested for the applicable characteristics for each lot of material presented for delivery. The sample unit shall be one sheet and the acceptable quality level (AQL) shall be 2.5 percent.

4.3.4 Certification.--Unless otherwise specified, the contractor shall forward to the procuring agency for each order of sheets or rolls a certified statement (1) identifying the base sheet by manufacturer's name, trade name, and identification number, (2) certifying that the base sheet of the delivery to be the same as to manufacturing process and composition as that which was tested in accordance with 4.1 and found to conform to all of the requirements of this specification, and (3) presenting the results of the material acceptance tests made by the contractor and by the producer of the sheet.

4.4 Test procedures.

4.4.1 Conditioning test specimens and test conditions.--Test specimens shall be conditioned in accordance with Fed. Std. No. 1 and tested under these conditions, unless otherwise specified in the referenced specification.

4.4.2 Plastic sheet.--The plastic sheet before coating shall be tested in accordance with the test methods specified in L-P-504, or L-P-377 as applicable.

4.4.4 Length and width.--The length and width of the sheet shall be measured with a calibrated steel rule.

4.4.5 Finish and color.--Determine the finish and color by accepted visual or instrumental methods.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:10Z
Check the source to verify that this is the current version before use.

4.4.6 Adhesive bond.--Cut a 1-inch by 6- to 12-inch specimen and apply 4 inches of the adhesive side to a clean and smooth aluminum panel conforming to QQ-A-362, temper T3. Suspend the panel in a horizontal position with the sheet specimen facing downward. Attach a 1-pound weight to the free end of the specimen and allow it to hang free at an angle of 90 degrees to the panel surface for 5 minutes. If more than 2 inches of the specimen is peeled back at the end of the test, the sample shall be regarded as not having met the test and the lot represented by the sample shall be rejected.

5. PREPARATION FOR DELIVERY.

For civil agency procurement, the definitions and applications of the levels of packaging and packing shall be in accordance with Fed. Std. No. 102.

5.1 Packaging.--Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Levels A and B (Standard Pack for GSA).

5.1.1.1 Sheets.--Fifty units of the 6x8 inch sheet or the 9x11-3/8 inch sheet, or one hundred units of the 3x4 inch sheet or the 10x12 inch sheet, shall be packaged in a paperboard box conforming to PPP-B-566, PPP-B-665, or PPP-B-676. Each box shall be secured to prevent accidental opening. Each unit package shall be marked with the Federal stock number, nomenclature (including size), and quantity.

5.1.1.2 Rolls.--Fifty-foot rolls shall be packaged individually in fiberboard boxes conforming to PPP-B-636, type, class, and style optional. Closure shall be in accordance with the appendix to PPP-B-636. Each unit package shall be marked with the Federal stock number, nomenclature (including size), and quantity.

5.2 Packing.--Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Sheets.--Unit packages of one stock number assembled as specified in 5.1.1.1 shall be packed in class 2 fiberboard boxes conforming to PPP-B-636 type and style optional in the quantities specified in table I. The box shall meet the special requirements of table II of PPP-B-636. Closure shall be in accordance with the appendix to PPP-B-636.

TABLE I - Packing of sheet unit packages.

Size sheet	Number of sheets to unit package	Number of unit packages to shipping container
3x4 inch	100	40
6x8 inch	50	40
9x11-3/8 inch	50	10
10x12 inch	100	10

5.2.1.2 Rolls.--Rolls packaged as specified in 5.1.1.2 shall be packed in class 2 fiberboard boxes conforming to PPP-B-636, type and style optional, in the quantity of nine rolls to the box. The box shall meet the special requirements of table II of PPP-B-636. Closure shall be in accordance with the appendix of PPP-B-636.

5.2.2 Level B. (Standard Pack for GSA).

5.2.2.1 Sheets.--Unit packages of one stock number assembled as specified in 5.1.1.1 shall be packed in fiberboard boxes conforming to PPP-B-636, type, class and style optional in the quantities specified in table I. The box shall meet the special requirements of table I of PPP-B-636. Closure shall be in accordance with the appendix to PPP-B-636.

5.2.2.2 Rolls.--Rolls packaged as specified in 5.1.1.2 shall be packed in fiberboard boxes conforming to PPP-B-636, type, class and style optional in the quantity of nine rolls to the box. The box shall meet the special requirements of table I of PPP-B-636. Closure shall be in accordance with the appendix to PPP-B-636.

5.2.3 Level C.--The material shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Shipping containers shall comply with the carrier rules and regulations applicable to the mode of transportation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:10Z
Check the source to verify that this is the current version before use.

5.3 Marking.

5.3.1 Civil agencies.--In addition to any special marking required by the contract or order, marking shall be in accordance with Federal Standard No. 123.

5.3.2 Military agencies.--In addition to any special marking required by the contract or order, marking shall be in accordance with Military Standard MIL-STD-129.

6. NOTES

6.1 Intended use.--The plastic sheet covered by this specification is intended for use in the protection of cards and documents.

6.2 Ordering data.--Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type and size of sheet desired (see 1.2.1).
(c) If color and finish other than that specified is desired (see 3.3).
(d) Level of packaging and packing required (see 5.1 and 5.2).

6.3 Transportation description.--Transportation description and minimum weights applicable to this commodity are:

Rail:

Plastic sheet or film, not woven, not otherwise indexed by name.
Carload minimum weight 30,000 pounds.

Motor:

Plastic film or sheeting, not otherwise indexed.
Truckload minimum weight, 30,000 pounds, subject to Rule 115, National Motor Freight Classification.

GSA DC 65-5534

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:10Z
Check the source to verify that this is the current version before use.