L-T-776A
AMENDMENT-3
September 26, 1973
SUPERSEDING
Int. Amendment-2 (GSA-FSS)
April 5, 1971

FEDERAL SPECIFICATION

TRAY, SERVICE (LAMINATED FIBER GLASS, POLYESTER RESIN)

This amendment, which forms a part of Federal Specification L-T-776A, dated May 31, 1966, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 1

Paragraph 1.2, Type I, (rectangular) sizes 1 and 2 change to:

Size 1 - 20-3/8 by 15-1/8 inches.
Size 2 - 18 by 14 inches.

Paragraph 2.1, delete paragraph and substitute:

"The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:"

Under "Federal Specifications", delete "PPP-B-591 - Boxes, Fiberboard, Wood-Cleated" and "PPP-B-636 - Box, Fiberboard" and substitute the following:

"PPP-B-591 - Boxes, Shipping, Fiberboard, Wood-Cleated.
PPP-B-636 - Boxes, Shipping, Fiberboard."

Under "Federal Standards", delete "Fed. Std. No. 141" in its entirety and substitute:

"Fed. Test Method Std. No. 141/GEN - Paint, Varnish, Lacquer, and Related Materials; Methods of Inspection, Sampling, and Testing.
Fed. Test Method 141/6106 - 60-DEGREE Specular Gloss."

After source paragraph for Military Standards, add:

"Laws and Regulations:

21 CFR 121:

Subpart F - Food Additives Resulting from Contact with Containers or Equipment and Food Additives Otherwise Affecting Food.

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

PAGE 2

Paragraph 2.2, delete in its entirety and substitute:

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

FSC 7350

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

PAGE 2 (con.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. Thay are also distributed among technical groups and using Federal agencies.)

Paragraph 3.2, second sentence, delete and substitute: "Materials shall conform to subpart F of 21 CFR 121."

Paragraph 3.2.1.2, delete in its entirety and substitute:

3.2.1.2 Core. The core shall consist of either of the following constructions in mats of two to four flat layers for forming or one preformed shape: (1) glass fibers, 1/2 to 2 inches in length, or (2) randomly oriented continuous glass fibers. The weight of the core shall be 3 to 4.5 ounces per sq. ft.

PAGE 7

Paragraphs 5.1.3 and 5.2.3 delete in their entirety and substitute:

5.1.3 Level C. The trays shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2.3 Level C. The trays shall be packed to afford adequate protection against physical and environmental damage during shipment, handling, and limited storage. Containers shall be in accordance with Uniform Freight Classification rules or National Motor Freight Classification rules, as applicable.

Paragraph 5.3, delete in its entirety.

PAGE 8

Figure I, delete and substitute:

Size	A Length inches	B Width inches	C Depth ± 3/32 inch	D Corner radius ± 1/8 inches	E Side wall angle ± 2 degrees	F Side wall and bottom thickness ± 0.012 inch	G Lip thick-ness ± 0.020 inch	J Radius at base ± 1/32 inch	K Radius at base ± 1/32 inch
1	20-3/8 ± 3/32	15-1/8 ± 3/32	7/8	2-5/8	55	0.093	0.250	5/16	1/8
2	18 ± 3/32	14 ± 3/32	7/8	2-5/8	55	.093	.250	5/16	1/8

PAGE 10

Concluding material, delete data reflected thereunder and substitute:

Preparing activity:

GSA-FSS

Civil Agency Coordinating Activities:

GSA-FSS
VA-DMS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.