FED. SUP CLASS
4730

(B) CONNECTION END IN ACCORDANCE WITH MALE END OF MILITARY STANDARD MS 35925



PLUG
FIG. 1

(B) CONNECTION END IN ACCORDANCE WITH FEMALE END OF MILITARY STANDARD MS 35925



CAP
FIG. 2

(B)

DASH NO.		SIZE
FIG. 1	FIG. 2	
-2	-2U	1/4
-3	-3U	3/8
-4	-4U	1/2
-5	-5U	5/8
-7	-7U	7/8
-9	-9U	1 1/8
-11	-11U	1 3/8

NOTES:

1. PLUGS SHALL BE MADE FROM DRAWN BRASS ROD CONFORMING TO COPPER ALLOY NO. 360 OF QQ-B-626.
2. CAPS SHALL BE MADE FROM COPPER SHEET CONFORMING TO ASTM B152.
3. DIMENSIONS IN INCHES.
4. REFERENCED DOCUMENTS SHALL BE THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BIDS OR REQUEST FOR PROPOSAL.
5. (B) FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.
6. (B) PART NUMBER: THE MS PART NUMBER CONSISTS OF THE MS NUMBER PLUS THE DASH NUMBER WITH THE DASH NUMBER DENOTING THE SIZE IN INCREMENTS OF 1/8 INCH. EXAMPLES: MS 35924-2, MS35924-2U etc.

APPROVED 22 SEPT 1958 REVISED (A) 1 APR 1968 (B) 21 MAR 75

This Military Standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Review: Army MD, Navy MU, DSA CS
User: Army CR, Navy MC, DSA SH

P.A.	TITLE	MILITARY STANDARD
ARMY-GL Other Cust NAVY-YD USAF-82	PLUG AND CAP, TUBE, SOLDER-JOINT, REFRIGERATION	MS 35924
Procurement Specification: NONE	SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 67 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:31Z
Check the source to verify that this is the current version before use.