INCH-POUND

MIL-PRF-27/356D
25 July 2008
SUPERSEDING
MIL-PRF-27/356C
8 April 1992

PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS AND INDUCTORS (AUDIO, POWER AND HIGH-POWER PULSE), INDUCTORS, POWER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the transformer described herein shall consist of this document and the latest issue of specification MIL-PRF-27.




FIGURE 1. Dimensions and configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:21Z
Check the source to verify that this is the current version before use.

Dash number	A Max.	B Max. Dia.	C ±.010	Insert	Terminal Arrangement	Terminal diameter inches ±.002
01, 06, 11, 16, 21, 26, 31, 36, 41, 46, 51, 56, 61	.280 (7.11)	.410 (10.41)	.260 (6.6)		A	.012
02, 07, 12, 17, 22, 27, 32, 37, 42, 47, 52, 57, 62	.340 (8.63)	.500 (12.7)	.350 (8.89)		A	.012
03, 08, 13, 18, 23, 28, 33, 38, 43, 48, 53, 58, 63	.415 (10.54)	.630 (16.0)	.440 (11.17)		A	.016
04, 09, 14, 19, 24, 29, 34, 39, 44, 49, 54, 59	.500 (12.70)	.800 (20.32)	.560 (14.22)		B	.016
05, 10, 15, 20, 25, 30, 35, 40, 45, 50, 55, 60	.635 (16.12)	.950 (24.13)	.670 (17.0)	.138-32 UNC-2B .200 Min deep	B	.020

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking shall be on the side or on top.
4. For series connection join terminals 2 and 3, for parallel connection join terminals 1 and 3, 2 and 4.
5. Metric equivalents are in parentheses.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:21Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical ratings.

Dash number	1/ Series inductance (mH)	Series dc current (max) (amps)	Series dc resistance ±25% (ohms)	1/ Parallel inductance (mH)	Parallel dc current (max) (amps)	Parallel dc resistance ±25% (ohms)
-01	20	.06	54	5	.12	13.5
-02	20	.10	29	5	.20	7.25
-03	20	.14	20	5	.28	5.0
-04	20	.22	12.4	5	.44	3.1
-05	20	.29	10.2	5	.58	2.55
-06	15	.07	40.5	3.75	.14	10.125
-07	15	.12	22	3.75	.24	5.5
-08	15	.16	15	3.75	.32	3.75
-09	15	.25	9.3	3.75	.50	2.325
-10	15	.33	7.7	3.75	.66	1.925
-11	10	.08	27	2.5	.16	6.75
-12	10	.14	14.6	2.5	.28	3.65
-13	10	.20	10	2.5	.40	2.5
-14	10	.31	6.2	2.5	.62	1.55
-15	10	.40	5.1	2.5	.80	1.275
-16	7.5	.10	20.3	1.88	.20	5.075
-17	7.5	.17	11	1.88	.34	2.75
-18	7.5	.24	7.5	1.88	.48	1.875
-19	7.5	.38	4.7	1.88	.76	1.175
-20	7.5	.49	3.8	1.88	.98	0.95
-21	5.0	.12	13.5	1.25	.24	3.375
-22	5.0	.21	7.3	1.25	.42	1.825
-23	5.0	.30	5	1.25	.60	1.25
-24	5.0	.47	3.1	1.25	.94	.775
-25	5.0	.6	2.6	1.25	1.2	.65
-26	3.0	.16	8.1	.75	.32	2.025
-27	3.0	.27	4.4	.75	.54	1.1
-28	3.0	.38	3	.75	.76	.75
-29	3.0	.6	1.9	.75	1.2	.475
-30	3.0	.78	1.5	.75	1.56	.375
-31	2.0	.19	5.4	.5	.38	1.35
-32	2.0	.33	2.9	.5	.66	.725
-33	2.0	.47	2	.5	.94	.5
-34	2.0	.74	1.3	.5	1.48	.325
-35	2.0	.95	1	.5	1.9	.25

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:21Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical ratings – Continued.

Dash number	1/ Series inductance (mH)	Series dc current (max) (amps)	Series dc resistance ±25% (ohms)	1/ Parallel inductance (mH)	Parallel dc current (max) (amps)	Parallel dc resistance ±25% (ohms)
-36	1	.27	2.7	.25	.54	.675
-37	1	.47	1.5	.25	.94	.375
-38	1	.66	1	.25	1.32	.25
-39	1	1	.62	.25	2	.155
-40	1	1.3	.5	.25	2.6	.125
-41	.750	.31	2	.1875	.62	.5
-42	.750	.54	1	.1875	1.08	.25
-43	.750	.76	.75	.1875	1.52	.1875
-44	.750	1.2	.47	.1875	2.4	.1175
-45	.750	1.6	.38	.1875	3.2	.095
-46	.500	.38	1.3	.125	.76	.325
-47	.500	.66	.66	.125	1.32	.165
-48	.500	.93	.5	.125	1.86	.125
-49	.500	1.47	.31	.125	2.94	.0775
-50	.500	1.9	.25	.125	3.8	.0625
-51	.250	.53	.66	.0625	1.06	.165
-52	.250	.93	.33	.0625	1.86	.0825
-53	.250	1.3	.25	.0625	2.6	.0625
-54	.250	2.08	.16	.0625	4.16	.04
-55	.250	2.7	.13	.0625	5.4	.0325
-56	.100	.78	.30	.025	1.56	.075
-57	.100	1.35	.17	.025	2.7	.043
-58	.100	1.95	.11	.025	3.9	.028
-59	.100	3.08	.07	.025	6.16	.018
-60	.100	3.88	.06	.025	7.76	.015
-61	.040	1.18	.14	.01	2.36	.035
-62	.040	2.03	.07	.01	4.06	.018
-63	.040	2.68	.06	.01	5.36	.015

1/ The inductance must be at least 80 percent of the listed value when measured with rated dc current at 0.1 V rms, 10 kHz.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:21Z
Check the source to verify that this is the current version before use.

REQUIREMENTS: (When numbers in parentheses, i.e., (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings: See table I.

Design and construction:

Dimensions and configurations: See figure 1.

Duty cycle: Continuous.

Case: Epoxy.

Terminals: Printed circuit, solderable.

Weight: 1.25 ounces, maximum.

Altitude: 75,000 feet, maximum.

Operating temperature range: -55°C to +130°C.

Terminal strength: MIL-STD-202, method 211, test condition A, 2 pounds.

Dielectric withstanding voltage:

At sea level: 200 volts rms.

At reduced barometric pressure: 100 volts rms.

Vibration (high frequency): MIL-STD-202, method 204.

Magnetic shield: All units are magnetically shielded.

Temperature rise: 30°C with .1 volt rms, rated dc current as specified in table I at an ambient temperature of 100°C, maximum.

Marking location: See figure 1.

Part or Identifying Number (PIN): M27/356-(dash number from table I).

Qualification: Qualification testing and approval to M27/356-01 shall be sufficient to grant qualification approval to M27/356-01 through M27/356-63.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:21Z
Check the source to verify that this is the current version before use.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents.

MIL-PRF-27
MIL-STD-202

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5950-2008-058)

Review activities:
Army – AR, MI
Navy - AS, MC, OS
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:21Z
Check the source to verify that this is the current version before use.