PERFORMANCE SPECIFICATION SHEET

INDUCTOR, POWER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-27.



	Inch	mm
A	0.740 ±0.010	18.80 ±0.25
B	1.44 ±0.12	36.58 ±3.05
C	0.032 ±0.002	0.813 ±0.051
D	0.240 ±0.010	6.10 ±0.25

CIRCUIT DIAGRAM



CIRCUIT DIAGRAM

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking shall be on the side of the case.

FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:24Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics (initial).

Dash number	Inductance (μH) ±15% 1/	DC resistance ohms (max)	Current rating (Amps) (max)	Incremental current (Amps) 2/
-01	1.0	0.009	6.27	6.4
-02	1.2	0.010	5.95	5.8
-03	1.5	0.011	5.67	5.2
-04	1.8	0.012	5.43	4.8
-05	2.2	0.013	5.22	4.3
-06	2.7	0.014	5.03	3.9
-07	3.3	0.016	4.70	3.5
-08	3.9	0.017	4.56	3.2
-09	4.7	0.022	4.01	2.9
-10	5.6	0.024	3.84	2.7
-11	6.8	0.026	3.69	2.5
-12	8.2	0.028	3.55	2.2
-13	10.0	0.033	3.27	2.0
-14	12.0	0.037	3.09	1.8
-15	15.0	0.040	2.97	1.6
-16	18.0	0.044	2.84	1.5
-17	22.0	0.050	2.66	1.4
-18	27.0	0.070	2.25	1.2
-19	33.0	0.075	2.17	1.1
-20	39.0	0.084	2.05	1.0
-21	47.0	0.104	1.84	0.93
-22	56.0	0.130	1.65	0.85
-23	68.0	0.145	1.56	0.77
-24	82.0	0.152	1.53	0.71
-25	100.0	0.208	1.30	0.64
-26	120.0	0.283	1.12	0.58
-27	150.0	0.330	1.04	0.52
-28	180.0	0.362	0.99	0.48
-29	220.0	0.505	0.84	0.43
-30	270.0	0.557	0.80	0.39
-31	330.0	0.650	0.74	0.35
-32	390.0	0.770	0.68	0.32
-33	470.0	1.03	0.59	0.29
-34	560.0	1.14	0.56	0.27
-35	680.0	1.50	0.49	0.25
-36	820.0	1.98	0.42	0.22
-37	1000.0	2.30	0.39	0.20
-38	1200.0	2.55	0.37	0.18
-39	1500.0	3.00	0.34	0.16
-40	1800.0	4.00	0.30	0.15
-41	2200.0	4.40	0.28	0.14
-42	2700.0	5.80	0.25	0.12
-43	3300.0	6.56	0.23	0.11
-44	3900.0	8.63	0.20	0.10
-45	4700.0	10.1	0.19	0.09
-46	5600.0	11.2	0.18	0.09
-47	6800.0	15.0	0.15	0.08
-48	8200.0	20.8	0.13	0.07
-49	10000.0	23.4	0.12	0.06
-50	12000.0	26.0	0.12	0.06
-51	15000.0	36.0	0.10	0.05
-52	18000.0	40.0	0.09	0.05

1/ Measured at 1 V with no dc current.
2/ The current at which the inductance will decrease by a maximum of 5 percent from its initial zero dc value.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:24Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical characteristics (final).

Inspection group	Allowable percent variation from the initial measurement	
Qualification inspection:	Inductance	DC resistance
Group II	±5	±3 (+.001 ohm)
Group III	±5	±2 (+.001 ohm)
Group IV	±5	-----

REQUIREMENTS:

Electrical ratings: See table I

Electrical characteristics (final): See table II.

Dimensions and configuration: See figure 1.

Case: Encapsulated.

Material: Epoxy.

Weight: 2.5 grams maximum.

Operating temperature range: -55°C to +130°C.

Altitude: 70,000 feet.

Ambient temperature: 85°C.

Power: .50 watt maximum power dissipation at 85°C.

Temperature rise: 45°C maximum at an ambient temperature of 85°C.

Terminal strength: MIL-STD-202, method 211, test condition A, 5 pounds.

Barometric pressure: MIL-STD-202, method 105, test condition C, 70,000 feet with a test voltage 500 V rms.

Dielectric withstanding voltage:

At sea level: MIL-STD-202, method 301; test voltage of 1000 V rms.

At reduced barometric pressure: MIL-STD-202, method 301; test voltage of 500 V rms.

Electrical characteristics: See table I.

Inductance: With 1 V rms, 1 kHz across (1-2), the inductance shall be “X” μH ±15 percent.
(For “X”, see table I.)

DC resistance: See table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:24Z
Check the source to verify that this is the current version before use.

Part or Identifying Number (PIN): M27/369-(dash number from table I).

Referenced documents. In addition to MIL-PRF-27, this document references the following:

MIL-STD-202

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5950-1184)

Review activities:
Army - MI
Navy - AS, OS
Air Force – 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of this information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:24Z
Check the source to verify that this is the current version before use.