
PERFORMANCE SPECIFICATION SHEET

INDUCTOR, POWER, HIGH CURRENT, SURFACE MOUNT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-27.



	Inches	mm
A	0.840 to 0.880	21.34 to 22.35
B	0.310 to 0.330	7.87 to 8.38
C	0.266 to 0.286	6.76 to 7.26
D	0.050 min	1.27 min
E	0.070 to 0.110	1.78 to 2.79
F	0.750 (Ref. Only)	19.05 (Ref. Only)
G	0.120 (Ref. Only)	3.05 (Ref. Only)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking shall be on the top of the case.

FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:25Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics (initial).


Dash number	Inductance (μH) ±15% 1/	DC resistance ohms (max)	Current rating (Amps) (max)	Incremental current (Amps) 2/
-01	1.0	0.009	6.27	6.4
-02	1.2	0.010	5.95	5.8
-03	1.5	0.011	5.67	5.2
-04	1.8	0.012	5.43	4.8
-05	2.2	0.013	5.22	4.3
-06	2.7	0.014	5.03	3.9
-07	3.3	0.016	4.70	3.5
-08	3.9	0.017	4.56	3.2
-09	4.7	0.022	4.01	2.9
-10	5.6	0.024	3.84	2.7
-11	6.8	0.026	3.69	2.5
-12	8.2	0.028	3.55	2.2
-13	10.0	0.033	3.27	2.0
-14	12.0	0.037	3.09	1.8
-15	15.0	0.040	2.97	1.6
-16	18.0	0.044	2.84	1.5
-17	22.0	0.050	2.66	1.4
-18	27.0	0.070	2.25	1.2
-19	33.0	0.075	2.17	1.1
-20	39.0	0.084	2.05	1.0
-21	47.0	0.104	1.84	0.93
-22	56.0	0.130	1.65	0.85
-23	68.0	0.145	1.56	0.77
-24	82.0	0.152	1.53	0.71
-25	100.0	0.208	1.30	0.64
-26	120.0	0.283	1.12	0.58
-27	150.0	0.330	1.04	0.52
-28	180.0	0.362	0.99	0.48
-29	220.0	0.505	0.84	0.43
-30	270.0	0.557	0.80	0.39
-31	330.0	0.650	0.74	0.35
-32	390.0	0.770	0.68	0.32
-33	470.0	1.03	0.59	0.29
-34	560.0	1.14	0.56	0.27
-35	680.0	1.50	0.49	0.25
-36	820.0	1.98	0.42	0.22
-37	1000.0	2.30	0.39	0.20
-38	1200.0	2.55	0.37	0.18
-39	1500.0	3.00	0.34	0.16
-40	1800.0	4.00	0.30	0.15
-41	2200.0	4.40	0.28	0.14
-42	2700.0	5.80	0.25	0.12
-43	3300.0	6.56	0.23	0.11
-44	3900.0	8.63	0.20	0.10
-45	4700.0	10.1	0.19	0.09
-46	5600.0	11.2	0.18	0.09
-47	6800.0	15.0	0.15	0.08
-48	8200.0	20.8	0.13	0.07
-49	10000.0	23.4	0.12	0.06
-50	12000.0	26.0	0.12	0.06
-51	15000.0	36.0	0.10	0.05
-52	18000.0	40.0	0.09	0.05


1/ Measured at 1 V with no dc current.
2/ The current at which the inductance will decrease by a maximum of 5 percent from its initial zero dc value.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:25Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical characteristics (final).

Inspection group	Allowable percent variation from the initial measurement	
Qualification inspection:	Inductance	DC resistance
Group II	±5	±3 (+.001 ohm)
Group III	±5	±2 (+.001 ohm)
Group IV	±5	-----





ENLARGED CUT-AWAY OF CLAMP

Legend	
Ltr	Description
A	G-10 base
B	Upper V-block hold-down clamp
C	Clamp screws
D	Upper V-block (body contact)
E	End cap contact retaining wall
F	End cap contact V-block (in contact with E)
G	Lower V-block (body contact)
H	G-10 insulators (separating G from F/E)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Metric equivalents are in parentheses.

FIGURE 2. Test fixture for insulation resistance, dielectric withstanding voltage and barometric pressure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:25Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Electrical ratings: See table I.

Electrical characteristics (final): See table II.

Dimensions and configuration: See figure 1.

Weight: 2.5 grams maximum.

Case: Grade 5, encapsulated.

Operating temperature range: -55°C to +130°C.

Temperature rise (at +85°C): +45°C, Method of mounting shall be on test substrates that provide test pieces one inch minimum separation.

Altitude: 70,000 feet.

Power: 0.50 watts, maximum power dissipation at 85°C.

Resistance to soldering heat: Method 210, test condition B, MIL-STD-202. Depth of immersion shall be the entire mounting surface for 4 to 5 seconds.

Bond strength: Method 2011, test condition F, MIL-STD-883.

Dielectric withstanding voltage: Method 301 of MIL-STD-202, test voltage 1000 V rms.

Barometric pressure: Method 105, test condition C, MIL-STD-202, (70,000 feet), test voltage 500 V rms.

Insulation resistance: Method 302, MIL-STD-202, 1,000 megohms minimum at 500 V dc.

Electrical characteristics (initial): See table I.

Vibration, high frequency: Method 204, test condition D, MIL-STD-202.

Moisture resistance: Method 106, MIL-STD-202, method of mounting shall be on test substrates that provide test pieces one inch minimum separation.

Test fixture: Test shall be performed using text fixture shown on figure 2, or equivalent.

Marking location: See figure 1.

Part or Identifying Number (PIN): M27/370-(dash number from table I).

Referenced documents. In addition to MIL-PRF-27, this document references the following:

MIL-STD-202
MIL-STD-883

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:25Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5950-1185)

Review activities:
Army - MI
Navy - AS, OS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of this information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:25Z
Check the source to verify that this is the current version before use.