MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, RECTANGULAR, PLUG, MICROMINIATURE, POLARIZED SHELL, PIN CONTACTS, CLASS P, CRIMP TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the connectors described herein shall consist of this specification and the latest issue of MIL-C-83513.





FIGURE 1. Connector, plug (.050 spacing).

Ⓑ denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:28Z
Check the source to verify that this is the current version before use.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.



Configuration B

FIGURE 1. Connector, plug (.050 spacing) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:28Z
Check the source to verify that this is the current version before use.


Number of cavities	A ±.010	B BSC	C +.010 -.018	D BSC
9	.778 (19.76)	.2918 (7.412)	.398 (10.11)	.565 (14.35)
15	.928 (23.57)	.4418 (11.222)	.548 (13.92)	.715 (18.16)
21	1.078 (27.38)	.5918 (15.032)	.698 (17.73)	.865 (21.97)
25	1.178 (29.92)	.6918 (17.572)	.798 (20.27)	.965 (24.51)
31	1.328 (33.73)	.8418 (21.382)	.948 (24.08)	1.115 (28.32)
37	1.478 (37.54)	.9918 (25.192)	1.098 (27.89)	1.265 +.010(.25) (32.13)-.005(.13)
51	1.428 (36.27)	.9418 (23.922)	1.048 (26.62)	1.215 (30.86)

INCHES	MM
.0019	0.048
.002	0.05
.0038	0.097
.004	0.10
.006	0.15
.010	0.25
.014	0.36
.025	0.64
.027	0.69
.032	0.81
.036	0.91
.045	1.14
.0459	1.166
.050	1.27
.0664	1.687
.088	2.24
.093	2.36
.094	2.39
.130	3.30
.1338	3.399
.173	4.39
.199	5.05
.208	5.28
.220	5.59
.250	6.35
.360	9.14
.395	10.03


NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.005 (0.13 mm).
4. Metric equivalents are in parentheses or columns.
5. Plane from which the lead length is measured.

FIGURE 1. Connector, plug (.050 spacing) - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:28Z
Check the source to verify that this is the current version before use.




9 CAVITY




25 CAVITY




15 CAVITY




31 CAVITY



21 CAVITY



37 CAVITY



51 CAVITY

NOTE: Engaging face of pin insert shown cavity identification numbers are for reference only and do not appear on part.

FIGURE 2. Insert arrangement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:28Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1. This specification sheet describes the pin side of a rectangular, plastic shell connector. This connector uses reverse gender contacts, i.e., the live pin recessed in the insulator with the static socket protruding from a shrouded interface.

Contact identification: See figure 2 for contact layout numbering.

Contact connection: The pin contact (being recessed in the insulator) is normally connected to the live side of the circuit.

Current rating, maximum: 3 amperes per contact.

Ⓑ Mounting and mating hardware: Hardware is to be ordered separately (see MIL-C-83513/5, configurations A and B).

Mating receptacle: Shall conform to MIL-C-83513/7 or MIL-C-83513/9.

Example of part number:

M83513/08- (Specification sheet number) **A** (Insert arrangement (see figure 2)) **01** (Wire type) 1/

Insert arrangement (see figure 2):

A = 9	
B = 15	
C = 21	
D = 25	
E = 31	
F = 37	
G = 51	

Wire type:

01 =	M22759/11-26-9, 18 inches long
02 =	M22759/11-26-9, 36 inches long
03 =	M22759/11-26-( ), 18 inches long 2/
04 =	M22759/11-26-( ), 36 inches long 2/
05 =	QQ-W-343, Type S, 25 AWG, except shall be gold plated 10 microinches; 0.5 inch long
06 =	QQ-W-343, Type S, 25 AWG, except shall be gold plated 10 microinches; 1.0 inch long
07 =	QQ-W-343, Type S, 25 AWG, tin plated 100 microinches; 0.5 inch long
08 =	QQ-W-343, Type S, 25 AWG, tin plated 100 microinches; 1.0 inch long

01 02 03 04 → 3/

05 06 07 08 → 4/

1/ These connectors have leads attached of which wire type, wire size, wire color, and lead length is specified in part number.

Ⓑ 2/ Color coding in accordance with MIL-STD-681, system I, except the appropriate color code shall be the individual contact cavity number minus 1. For example, for contact cavity number one, color code is 1-1 or 0 (black) for contact positions 1 thru 10 only.

3/ Lead length tolerance +1.0, -0.0 inch.

4/ Lead length tolerance +0.2, -0.0 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:28Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - AS, SH
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AT, ME
Navy - CG, MC

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5935-3477-8)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:28Z
Check the source to verify that this is the current version before use.