MILITARY SPECIFICATION
TEST SET, ANTENNA, BORESIGHT
TS-3568( )/AWM-23 (V)

This specification has been approved by the Naval Air Systems Command, Department of the Navy

1. SCOPE

1.1 Scope. This specification covers the performance, design and test requirements for the Antenna Boresight Test Set (ABTS) TS-3568( )/AWM-23(V).

1.2 Classification. The ABTS consists of the following items:

	Nomenclature	Reference Paragraph
a.	Boresight fixture, antenna (array)	3.6.1
b.	Boresight fixture, antenna (base)	3.6.2
c.	Spindle Mirror	3.6.3
d.	Autocollimator	3.6.4
e.	Zero pins (two each)	3.6.5
f.	Array support positioning plate	3.6.6
g.	Storage case	3.6.7

2. APPLICABLE DOCUMENTS

2.1 General. The following documents, of the issue specified in AS-4053, Applicable Document List for Airborne Weapon Control System (AWCS) Test Set AN/AWM-23(V), form a part of this specification to the extent specified herein. MIL-T-81734 (AS) is the applicable general specification for the set described herein (see 6.6).

FSC-4935

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:59Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

Military

MIL-E-17555	Electronic and Electrical Equipment, Accessories, and Repair Parts; Packaging and Packing of
MIL-T-18303	Test Procedure, Preproduction, Acceptance, and Life for Aircraft Electronic Equipment, Format for
MIL-N-18307	Nomenclature and Identification for Electronic Aeronautical and Aeronautical Support Equipment including Ground Support Equipment
MIL-T-21200	Test Equipment for use with Electronic and Fire Control Systems, General Specification for
MIL-T-81734 (AS)	Test Set, Airborne Weapon Control System, AN/AWM-23(V)

Hughes Aircraft Company

FS 31050-038	Finish Specification, AN/AWM-23 Ground Support Equipment
GS 30620-781	General Specification for Identification and Marking of AN/AWM-23 Ground Support Equipment

STANDARDS

Military

MIL-STD-167	Mechanical Vibrations of Shipboard Equipment
MIL-STD-280	Definitions of Item Levels, Item Exchangeability, Models, and Related Terms

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:59Z
Check the source to verify that this is the current version before use.

MIL-STD-454	Standard General Requirements for Electronic Equipment
MIL-STD-480	Configuration Control Engineering Changes, Deviations and Waivers

DRAWINGS

Hughes Aircraft Company

493720-1XX	Test Set, Antenna Boresight

2.2 Availability of documents. When requesting specifications, standards, drawings, and publications, refer to both title and number. Copies of applicable specifications required by contractors in connection with specific procurement functions may be obtained upon application to the Commanding Officer, Naval Supply Depot, 5801 Tabor Avenue, Philadelphia, Pennsylvania 19120.

2.3 Precedence of documents. When the requirements of the contract, this specification, or applicable subsidiary documents are in conflict, the following precedence shall apply:

a. Contract - The contract shall have precedence over any other document.

b. This specification - This specification shall have precedence over all applicable subsidiary documents (see 6.6).

c. Referenced documents - Any document referenced in this specification shall have precedence over all applicable documents referenced therein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:59Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials, parts, and processes. Not applicable. Good commercial practice shall apply.

3.1.1 Selection of materials, parts, and processes. Not applicable.

3.1.1.1 Approval of nonstandard materials, parts, and processes. Not applicable. Nonstandard parts, materials and process selected shall not require Government approval (see 6.3.15).

3.1.2 Flammable materials. In lieu of the requirements of MIL-T-21200, the following shall apply:

a. Use of materials which may support combustion shall be avoided, wherever practical.

b. No materials capable of causing an explosion shall be used.

3.1.3 Cables and connectors. Not applicable.

3.1.4 Wire. Not applicable.

3.1.5 Rotary switches. Not applicable.

3.1.6 Finishes. Finishes and surface treatments shall be in accordance with FS 31050-038.

3.1.7 Marking and identification. Marking and identification shall be in accordance with GS 30620-781. The requirements of MIL-N-18307 shall apply as specified in GS 30620-781.

3.1.8 Soldering. Not applicable.

3.1.9 Welding. Not applicable.

3.1.10 Printed wiring. Not applicable.

3.1.11 Engineering changes to printed circuit board. Not applicable.

3.1.12 Replaceability of electronic standard parts and materials. Not applicable.

3.2 Design and construction. The ABTS shall include all necessary cables required for operation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:59Z
Check the source to verify that this is the current version before use.

3 .2.1 Design features. Not applicable.

3.2.1.1 Method of operation. The ABTS shall be manually operable.

3.2.1.2 Commercial test equipment. Not applicable.

3.2.1.2.1 Other commercial components. Other commercial components (such as power supplies, tape readers, or tape recorders) , may be incorporated in the ABTS. When installed in the ABTS, they shall meet the environmental and electrical service conditions of this specification.

3.2.1.3 Circuit grounds. Not applicable.

3.2.1.4 Interchangeability. Interchangeability shall be in accordance with MIL-STD-454, Requirement 7.

3.2.1.5 Identification of product. MIL-T-21200 shall apply.

3.2.1.6 Human factors. The human engineering requirements of MIL-STD-454, Requirement 62, shall apply.

3.2.1.7 Test set generated acoustic noise. Not applicable.

3.2.1.8 Forced-liquid cooling. Not applicable.

3.2.1.9 Space and weight limitations. The maximum size of the elements of the ABTS when stored in the storage case shall be 20 inches by 14 inches by 13 inches. The maximum weight of the ABTS shall be 45 pounds.

3.2.1.10 Connectors. Not applicable.

3.2.1.11 Secondary electrical power. Not applicable.

3.2.1.12 Interface. The ABTS shall interface with Antenna AS-2764( )/AWG-9.

3.2.2 Utilities. The test set shall be designed to accept the utilities specified herein.

3.2.2.1 Electrical power. The electrical power required for operation of the ABTS shall be 115 volts, 60 Hertz, single phase, 5 volt-amperes maximum from a facility utility outlet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:59Z
Check the source to verify that this is the current version before use.

3.2. 2.2 Clean-air. Not applicable.

3.2. 2.3 Potable water. Not applicable.

3.2.2.4 Liquid coolant. Not applicable.

3.2.2.5 Helium. Not applicable.

3.2.2.6 Nitrogen. Not applicable.

3.2.2.7 Hydraulic fluid. Not applicable.

3.2.3 Service conditions

3.2.3.1 Electrical. The ABTS shall be designed to meet the performance requirements of this specification when supplied with the electrical power of 3.2.2.1. Commercial equipment items selected as elements of the ABTS shall meet the electrical service requirements of the manufacturer's specifications covering these items.

3.2.3.2 Environmental. The ABTS shall operate satisfactorily under the environmental service conditions specified below.

3.2.3.2.1 Organizational level. Not applicable.

3.2.3.2.2 Intermediate Level. Equipment designed for use at the intermediate level of maintenance shall meet the following environmental requirements:

a. Vibration - The equipment shall withstand exposure to vibration in accordance with MIL-STD-167, Type I.

b. Shock - The equipment shall withstand, with commercial equipment not installed in the ABTS, shock pulses of 15 g amplitude for 11 ±1 milliseconds duration applied in accordance with MIL-T-21200.

c. Temperature/altitude - The ABTS shall provide continuous, satisfactory operation over temperatures ranging from zero to 45 degrees C (+32 to +113 degrees F) at altitudes ranging from sea level to 10,000 feet. The maximum nonoperating temperature shall be +71 degrees C (+159.8 degrees F), and the minimum shall be -40 degrees C (-40 degrees F). The maximum nonoperating altitude shall be 50,000 feet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:59Z
Check the source to verify that this is the current version before use.

d. Humidity - The ABTS shall withstand the effects of humidities up to 95 percent, with no condensation, under operating or nonoperating conditions. The ABTS, except commercial equipment, shall withstand the effects of humidities up to 95 percent, including condensation, under operating or nonoperating conditions.

3.2.4 Maintainability. MIL-T-21200, as modified below, shall apply.

3.2.4.1 Mean time to repair (MTTR). The ABTS shall be capable of being restored to normal operation within 4 hours (mean time) after a malfunction is detected (see 6.3.14).

3.2.4.2 Test points. Not applicable.

3.2.4.3 Shop replaceable assemblies. Not applicable.

3.2.4.4 Self test capabilities. No self test capability shall be provided.

3.2.5 Reliability. The MTBF shall be 500 hours minimum.

3.2.5.1 Operating life. The ABTS shall have a minimum of 15,000 hours operating life (see 6.3.12) with scheduled maintenance and replacement of parts.

3.2.5.2 Storage life. Storage life of the ABTS shall be a minimum of 5 years.

3.2.5.3 Operational stability. The ABTS shall operate satisfactorily over a period of 16 hours, continuously or intermittently, without the necessity for readjustment of any controls which are inaccessible during normal use.

3.2.6 Electromagnetic interference (EMI). Not applicable.

3.2.7 Utilities protection. Not applicable.

3.2.8 Calibration cycle. The ABTS shall be designed for a minimum calibration cycle of 12 months, exclusive of routine maintenance adjustments. Commercial equipment will be calibrated at periodic intervals established by the Navy.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:59Z
Check the source to verify that this is the current version before use.

3.3 Performance

3. 3.1 General. The ABTS shall be capable of verifying that the antenna array mounting pads are aligned with respect to the machined boresight surface on the antenna base within ±2 milliradians. During this verification, the antenna may be mounted in either Antenna Mounting Stand MT-4445( )/AWM-23(V) at Low Frequency Test Station OJ-215( )/AWM-23(V), or in Antenna Handling Adapter MX-9046( )/AWM-23(V) or MX-9691( )/AWM-23(V).

3.3.2 Organizational level functional requirements. Not applicable.

3.3.3 Intermediate level functional requirements. Intermediate level functional capability shall be limited to measuring the alignment of the two surfaces of the antenna (see 3.3.1).

3.3.4 Warm-up time. Not applicable.

3.4 Detailed functional requirements. The detailed functional requirements of the ABTS shall be as stated in 3.6.

3.5 Workmanship. Workmanship shall conform to MIL-STD-454, Requirement 9.

3.6 Set elements. The elements of the ABTS shall be as follows.

3.6.1 Boresight fixture, antenna (array). The boresight fixture, antenna (array) shall provide a means of mounting the autocollimator on the antenna array boresight pads.

3.6.2 Boresight fixture, antenna (base). The boresight fixture, antenna (base) shall provide a means of mounting the spindle mirror to the antenna base boresight surface.

3.6.3 Spindle mirror. The spindle mirror shall be adjustable and shall reflect collimated beams back to the autocollimator when the mirror is mounted in the boresight fixture on the antenna base.

3.6.4 Autocollimator. The autocollimator shall provide an accurate means of simultaneously determining the angular deviation of the reflected beam from the spindle mirror in azimuth and elevation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:59Z
Check the source to verify that this is the current version before use.

3. 6.5 Zero pins. The two zero pins shall provide a means for holding the antenna array in the zero azimuth and elevation positions during boresighting.

3.6.6 Array support positioning plate. The array support positioning plate shall provide a means for holding and aligning the array support arms during maintenance or when the array is detached.

3.6.7 Storage case. The storage case shall provide compartments of foam polyurethane, of 4 pounds per cubic foot density, to provide storage for the elements of the ABTS and to protect these elements against damage during normal handling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:59Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 General. Acceptance of the ABTS shall be solely on the basis of this specification.

4.2.1 Classification. The ABTS shall be classified as a production model in accordance with paragraph 3.3.5 of MIL-STD-280: "A model in its final form of final production design made by production tools, jigs, fixtures, and methods. It employs standard parts (or nonstandard parts approved by the agency concerned)." If it is necessary to depart temporarily from the mandatory requirements (parts, processes, etc.) of the technical documents, a form DD 1694 shall be prepared. Minor deviations shall be submitted to the Navy Technical Representative (NTR) for approval. Major and critical deviations and waivers shall be submitted to Naval Air Systems Command for approval in accordance with the contract. The DD Form 1694 (Request for Deviation/Waiver) shall be prepared as delineated in MIL-STD-480 .

4.2.2 Individual items. The ABTS will be accepted separately and independently of other items of the AN/AWM-23.

4.2.3 In-process inspection. Prior to entering acceptance tests, the ABTS shall have completed in-process inspections.

4.2.4 In-process data. The data resulting from contractor conducted in-process inspections shall be presented to the Cognizant Government Inspector (GCI) at the time the ABTS is offered for Government inspection and acceptance.

4.2.5 Acceptance test plan. All testing shall be as specified in the acceptance test plan, as shown in Table I. Data sheets containing test criteria and measurement results are a part of the acceptance procedure document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:59Z
Check the source to verify that this is the current version before use.

TABLE I
ACCEPTANCE TEST PLAN FOR ANTENNA BORESIGHT TEST SET
TS-3568( )/AWM-23(V)

Item	Test Plan	Requirements
1	TEST OBJECTIVE	To demonstrate that the materials, interchangeability and workmanship requirements of 3.1, 3.2.1.4, and 3.5, respectively, have been met.
2	TEST CONDITIONS	Not applicable.
3	TESTS	Inspect each item of the set for conformance to 493720-1XX.

4.2.6 Test results. The contractor shall present test data, as documented evidence that the ABTS has completed tests, as applicable. Test indications shall be recorded on test data sheets by the responsible contractor test engineer and inspected by contractor Quality Assurance (QA). A record shall be kept of all failures.

4.2.7 Acceptance. Upon completion of Government inspection, Government acceptance will be consummated by CGI execution of the DD Form 250.

4.2.8 Utilities. Forced-air-cooling, electrical power consumption, water, nitrogen, compressed air, and forced liquid cooling performance are facilitities requirements and need not require verification as conditions of acceptance. The contractor may use his facilities providing they are within the required tolerances of 3.2.2.

4.2.9 Configuration. Not applicable. The physical configuration of the ABTS during acceptance shall be in accordance with Drawing 493720-1XX.

4.3 Tests

4.3.1 Electrical and electronic items - operational run-in tests. Not applicable.

4.3.2 Mechanical items. As specified in the acceptance test plan, the ABTS shall be inspected for conformance to drawings.

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:59Z
Check the source to verify that this is the current version before use.

4.4 Environmental test conditions. All tests shall be performed under the prevailing environmental conditions which shall be within the following limits:

a.	Temperature	Room ambient (30 ±10 degrees C)
b.	Altitude	Normal ground
c.	Vibration	None
d.	Humidity	Room ambient up to 90 percent relative humidity.

4.5 Test location. Inspection for the purpose of acceptance shall be made at the contractor's plants and the contractor's vendors' plants.

4.6 Acceptance schedule. The schedule of acceptance activities is shown in Table II. Upon completion of Government acceptance, the ABTS shall be shipped in accordance with the allocation instructions. Minor changes may be made in the schedule of acceptance activities as informally agreed to by representatives of the Government and the contractor without requiring changes to this document.

4.7 Test procedures. Acceptance tests shall be performed in accordance with a test plan and test procedures mutually agreeable to the procuring activity and the supplier. The test plan shall be prepared by the supplier. MIL-T-18303 shall be used as a guide for preparation of test procedures. All inspections and testing shall be under the supervision of the Government inspector. Acceptance or approval of material during the course of manufacture shall not be construed as a guarantee of the acceptance of the finished product.

4.8 Rejection and retest. Equipment which has been rejected may be reworked or have parts replaced to correct the defects and be resubmitted for acceptance. Before resubmitting, full particulars concerning previous rejection and the action taken to correct the defects found in the original shall be furnished to the Government Inspector. Units rejected after retest shall not be resubmitted without the specific approval of the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:59Z
Check the source to verify that this is the current version before use.

TABLE II
ACCEPTANCE ACTIVITIES

Item	Acceptance Activities	Responsibility	Time
1	Submit request for allocation instructions to CAO*	HAC**	Delivery (D) day minus 120 days
2	Provide allocation instructions	CAO	D day minus 30 days
3	Complete Contractor inspection	HAC	D day minus 10 days
4	Notify Government that GSE control items are ready for inspection and acceptance	HAC	D day minus 10 days
5	Conduct Government inspection for acceptance	AFQAR***	D day
6	Accept and deliver units as appropriate	AFQAR	D day

*Contract Administrative Officer. Shipping instructions are provided to the CAO by NAVAIR.

**Hughes Aircraft Company

***Air Force Quality Assurance Representative

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:59Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 General. The ABTS shall be preserved, packaged, packed and marked for the level of shipment specified in the contract or order in accordance with MIL-E-17555.

6. NOTES

6.1 Intended use. The ABTS is intended for use at the intermediate level to facilitate alignment of the boresight surface of the antenna array with respect to the boresight surface of the antenna base.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification

b. Applicable level of packaging and packing desired.

6.3 Definitions. For the purpose of this specification, the following definitions shall apply.

6.3.1 Proper performance of the maintenance function. Proper performance of the maintenance function is defined as testing, memory loading, fault isolating, repair, and adjustment to a degree of quality and thoroughness consistent with the requirements established for a given maintenance level, accomplished by the support personnel and resources established for that level, and accomplished in a period of time consistent with the work load predicted for maintenance involved in performing the function.

6.3.2 Organizational level maintenance. All maintenance performed by the using organization employing only those skills, tools, support equipment, publications, procedures, and techniques planned for service use when deployed. (Organizational maintenance of avionics equipment installed in an aircraft would be performed at or in the aircraft.)

6.3.3 Intermediate level maintenance. Al 1 maintenance other than organizational maintenance performed at the using activity, employing only skills, tools, support equipment, publications, procedures, techniques, and utilities planned for normal service use on board an aircraft carrier or at a designated intermediate maintenance facility ashore.

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:59Z
Check the source to verify that this is the current version before use.

6.3.4 Ground support equipment (GSE). GSE is defined as equipment used by operating forces for service, maintenance, test, fault isolation, and repair of units or components of the WCS AN/AWG-9 and is not physically a part of the WCS. It is composed of special test, special handling, and special conditioning equipment.

6.3.5 Commercial test equipment. Commercial test equipment is defined as test equipment listed and described in a manufacturer's catalog as a standard item. It is built to standards of good commercial practice; however, it is not required to meet military specifications.

6.3.6 Weapon replaceable assembly (WRA). WRA is a generic term which includes all the replaceable packages of an avionic equipment pod or system as installed in an aircraft weapon system with the exception of cables, mounting provisions, and fuse boxes or circuit breakers.

6.3.7 Shop replaceable assembly (SRA). A generic term which includes all the packages within a test set. The term SRA includes Quick Replaceable Assemblies (QRA) and In-Place Repairable Assemblies (IRPA).

6.3.8 Quick replaceable assembly (QRA). A preferred form of SRA which is easily removable from the test set without complex removal operations. It is typified by a plug-in design.

6.3.9 In-place repairable assembly (IPRA) . The least desirable form of SRA having the characteristic that it is repaired in the shop while in place in the test set.

6.3.10 Checkout. Checkout is defined as a test operation to verify compliance with established performance standards.

6.3.11 Primary failures. Failures which occur without being the result of associated equipment failures or through procedural errors, are primary failures.

6.3.12 Operating life. operating life shall exclude standby power condition and includes only time on the elapsed time meter in the high voltage condition.

6.3.13 MTBF. The definition of MTBF shall be in accordance with MIL-STD-721. The determination of MTBF value includes the AN/AWG-9 items used as "slave" units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:59Z
Check the source to verify that this is the current version before use.

6.3.14 MTTR. Mean time to repair, applied herein, consists of locating a defective shop replaceable assembly (SRA), replacing that SRA with a serviceable assembly, and performing a confidence test to verify repair.

6.3.15 Nonstandard. Parts, materials and processes are defined as nonstandard if they are not covered by the documents listed in ANA-Bulletin 400, Airborne Electronic and Associated Equipment, Applicable Documents.

6.4 Nomenclature cross reference. The following is a cross reference between the official Navy nomenclature and the major contractor part numbers. The contractor part number suffix is controlled by the configuration list in the contract.

Item	Official Nomenclature	Contractor Part Number
a.	Antenna AS-2764( )/AWG-9	481031-1XX
b.	Test Station, Low frequency OJ-215( )/AWM-23(V)	493350-1XX
c.	Stand, Mounting, Antenna MT-4445( )/AWM-23(V)	493354-1XX
d.	Adapter Handling, Antenna MX-9046( )/AWM-23(V)	493602-1XX
e.	Adapter Handling, Antenna MX-9691( )/AWM-23(V)	493602-1XX
f.	Test Set, Antenna, Boresight, TS-3568( )/AWM-23(V)	493720-1XX

6.5 Liquid Cooler. Not applicable.

6.6 Use of this specification. This specification is a detail specification which uses MIL-T-81734 (AS) as a general specification. When the term “not applicable” is used in this specification, it means that the corresponding paragraph requirements of MIL-T-81734 (AS) are not required to be met (see 6.6 of MIL-T-81734 (AS)).

6.7 Abbreviations and acronyms.

ABTS	Antenna Boresight Test Set
AFQAR	Air Force Quality Assurance Representative

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:59Z
Check the source to verify that this is the current version before use.

BIT	Built in test
C	Celsius (centigrade)
CAO	Contract Administrative Officer
CGI	Cognizant Government Inspector
EMI	Electromagnetic interference
F	Fahrenheit
GSE	Ground support equipment
HAC	Hughes Aircraft Company
Hz	Hertz
IPRA	In-place repairable assembly
kW	Kilowatts
MTBF	Mean time between failures
MTTR	Mean time to repair
NAFI	Naval Avionics Facility, Indianapolis
NAVAIR	Naval Air Systems Command
NDRO	Nondestructive readout
NTR	Naval Technical Representative
OOT	Out-of-tolerance
P-P	Peak-to-peak
PSIG	Pounds per square inch gage
QA	Quality assurance
QRA	Quick replaceable assembly
SRA	Shop replaceable assembly
Test Set	Airborne Weapon Control System Test Set AN/AWM-23(V)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:59Z
Check the source to verify that this is the current version before use.

Vac	Volts alternating current
Vdc	Volts direct current
WCS	Weapon Control System

6.8 Convenience outlet power. Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:59Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-T-85027(AS) TEST SET, ANTENNA, BORESIGHT TS-3568( )/AWM-23(V)

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:59Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

Naval Air Systems Command
Washington, D. C.

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID

DOD 316



NAVAL AIR SYSTEMS COMMAND (AIR-52021E)
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20361

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:59Z
Check the source to verify that this is the current version before use.