INCH-POUND
MIL-C-25D
AMENDMENT 7
24 September 1999
SUPERSEDING
AMENDMENT 6
22 May 1998

MILITARY SPECIFICATION

CAPACITORS, FIXED, PAPER-DIELECTRIC, DIRECT CURRENT
(HERMETICALLY SEALED IN METAL CASES),
GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-C-25D, dated 21 June 1968, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

1.2.1.7, line 1: Following “capacitance”, add “tolerance”.

PAGE 10

3.18, dissipation factor requirement, delete and substitute:

“Dissipation factor - - - - - - - - Shall not exceed 1 percent when measured as specified in 4.6.5, except for characteristic F which shall not exceed 1.5 percent.”

PAGE 12

4.4.4, delete and substitute:

“4.4.4 First article inspection. For styles CP75, CP76, CP77, CP78, CP80, CP81, and CP82, first article inspection shall consist of all the tests specified in table IX in the order shown. Sample sizes shall be reduced by one half.”

PAGE 14

4.5.1.3.1, Delete in its entirety and substitute:

“4.5.1.3.1 Sampling plan. The sampling plan shall be as specified in table XII.”

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:17Z
Check the source to verify that this is the current version before use.

TABLE XII, delete in its entirety and substitute.

"TABLE XII Group A inspection.

Examination or test	Requirement Paragraph	Test method paragraph	Sampling proceedure
Visual mechanical examination Materials Body dimensions Design and construction (other than body dimensions) Marking 1/ Workmanship	3.3 to 3.3.2 3.1 3.4 to 3.4.4.2 3.20 to 3.20.2 3.21 to 3.21.2	4.6.1	13 Samples 0 Failures
Insulation resistance (at 25°C) Capacitance Dissipation factor	3.6 3.7 3.8	4.6.3 4.6.4 4.6.5	13 Samples 0 Failures

1/ Marking defects are based on visual examination and shall be charged only for illegible, incomplete, or incorrect marking. Any subsequent electrical defects shall not be used as the basis for determining marking defects."

TABLE XIII, delete in its entirety and substitute.

"TABLE XIII. Group B inspection

Test	Requirement paragraph	Test method paragraph	Sampling proceedure
Subgroup 1 Barometric pressure (flashover) Vibration Temperature and immersion cycling	 3.9 3.10 3.12	 4.6.6 4.6.7 4.6.9	 5 Samples 0 Failures
Subgroup 2 Insulation resistence (at high-test temperature) Life	 3.6 3.18	 4.6.3 4.6.15	 5 Samples 0 Failures

"

4.5.1.4.1, Delete in its entirety and substitute:

"4.5.1.4.1 Sampling plan. The sampling plan shall be as specified in table XII."

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:17Z
Check the source to verify that this is the current version before use.

PAGE 16

TABLE XIV: Delete "Initial production and every month" and "Initial production and every 2 months" and substitute "Subgroup 1" and "Subgroup 2" respectively.

4.5.1.5.1, delete and substitute:

"4.5.1.5.1 Sampling plan. Sample units shall be selected from the initial production, processed for acceptance at the start of the contract, and from each year's production thereafter in accordance with table XIV. A different set of sample units shall be selected for each subgroup. Sample units of the same style (any one style covered by a specification sheet may be representative of any other style specified therein; see table XVII) shall be selected in each characteristic, irrespective of voltage and capacitance. These sample units may be in any capacitance tolerance. If the number of defectives exceeds those allowed in table XIV, the sample shall be considered to have failed."

4.5.1.5.1.1 and 4.5.1.5.1.2: Delete in their entirety.

PAGE 17

* 4.5.3, delete and substitute.

"4.5.3 Verification of qualification. Every 12 months, the manufacturer shall provide verification of qualification to the qualifying activity. Continuation of qualification shall be based on meeting the following requirements:

a. Group A inspection.

b. Group B inspection.

c. Periodic group C inspection.

In the event that there is no production of a single style device during a reporting period and the manufacturer is listed for more than one style on the QPL, a report shall be submitted certifying that the manufacturer still has the capabilities and facilities necessary to produce that product. If during three consecutive reporting periods there has been no production of a given style, the manufacturer may be required, at the discretion of the qualifying activity, to submit a representative product of that style to testing."

PAGE 23

6.2, last sentence, delete and substitute:

"Information pertaining to qualification of products may be obtained from the Defense Supply Center, Columbus (DSCC-VQP), 3990 East Broad Street, Columbus, OH 43213-1199."

PAGE 24

6.14, line 2: Delete "±0.2 kHz at a level of 1 ±0.5" and substitute "1 ±0.2 kHz at a level of 1 ±0.2".

PAGE 25

TABLE XVII: "Delete column heading "Style group" and substitute "Style group 1/". Add the following footnote to the bottom of table XVII:

"1/ Style groups D and E may be combined for acceptance test purposes allowing selection from any one of the six styles."

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:17Z
Check the source to verify that this is the current version before use.

PAGE 26

20.1.5, line 3: Delete “4.6.17” and substitute “4.6.16”.

PAGE 28

30.1f, line 1: Delete “C67 and C91” and substitute “CP67 and CP91”.

30.1g, line 1: Delete “CP87” and substitute “CP78”.

PAGE 30

TABLE XX, columns 2 and 5, line 4: Delete “CP12A1KE105K-“ and “0.08” and substitute “CP12A1KE474K-“ and “0.04”, respectively.

TABLE XX, columns 2 and 5, line 6: Delete “CP13A1KE105K-“ and “0.08” and substitute “CP13A1KE474K-“ and “0.04”, respectively.

TABLE XX, columns 2, 4, and 5, line 12: Delete “CP13A1KE684K-“, “IB”, and “0.122” and substitute “CP13A1KF474K-“, “IA”, and “0.08”, respectively.

TABLE XX, column 2, line 13: Delete “CP28A1EG104K1“ and substitute “CP28A1EH104K1“.

TABLE XX, columns 2, 5, and 6, line 24: Delete “CP70D1ER105K1“, “2.8”, and “7,500” and substitute “CP70E1EM504K1”, “4”, and “4,000”, respectively.

TABLE XX, columns 2, 5, and 6, line 29: Delete “CP72D1ER105K1“, “2.8”, and “7,500” and substitute “CP72E1EM504K1”, “4”, and “4,000”, respectively.

PAGE 31

TABLE XXI, column 2, lines 1 and 2: Delete “CP091FA6” and CP091SA6” and substitute “CP091FB6” and “CP091SB6”, respectively.

TABLE XXI, column 2, line 16: Delete “CP072SJ3” and substitute “CP072SJ11”.

NOTE: The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA-CC

Review activities:
Army - AR, MI
Navy - AS, MC, OS
Air Force - 19, 99

(Project 5910-2055)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:17Z
Check the source to verify that this is the current version before use.