INCH-POUND

The documentation and process conversion measures necessary to comply with this document shall be completed by 28 February 2026.

MIL-PRF-19500/464J
w/AMENDMENT 2
31 October 2025
SUPERSEDING
MIL-PRF-19500/464J
w/AMENDMENT 1
28 February 2025

PERFORMANCE SPECIFICATION SHEET

TRANSISTOR, NPN, SILICON, POWER,
DEVICE TYPES 2N5685 AND 2N5686, JAN, JANTX, AND JANTXV

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN silicon, power transistors. Three levels of product assurance (JAN, JANTX, and JANTXV) are provided for each device type as specified in MIL-PRF-19500.

1.2 Package outlines. The device package outlines are as follows: TO-3 in accordance with figure 1 for all encapsulated device types.

1.3 Maximum ratings. T_C = +25°C, unless otherwise specified.

Type	P_T (1) T_C = +25°C	P_T (1) T_C = +100°C	V_{CBO}	V_{CEO}	V_{EBO}	I_B	I_C	T_J and T_{STG}	$R_{\theta JC}$
	W	W	V dc	V dc	V dc	A dc	A dc	°C	°C/W
2N5685	300	171	60	60	5	15	50	-55 to +200	.584
2N5686	300	171	80	80	5	15	50	-55 to +200	.584

(1) Between T_C = +25°C and T_C = +200°C linear derating factor 1.715 W/°C.

Comments, suggestions, or questions on this document should be addressed to DLA Weapons Support, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics. Unless otherwise specified, T_C = +25°C.

Type	h_{FE2} (1)	h_{FE3} (1)	$V_{BE(sat)}$ (1)	$V_{CE(sat)1}$ (1)	$V_{CE(sat)2}$ (1)
	V_{CE} = 2 V dc I_C = 25 A dc	V_{CE} = 5 V dc I_C = 50 A dc	I_C = 25 A dc I_B = 2.5 A dc	I_C = 25 A dc I_B = 2.5 A dc	I_C = 50 A dc I_B = 10 A dc
	Min Max	Min Max	V dc Min Max	V dc Min Max	V dc Min Max
2N5685	15 60	5	2.0	1.0	5.0
2N5686	15 60	5	2.0	1.0	5.0

Type	C_{obo}	$\|h_{fe}\|$	h_{fe}	Switching (see table I and figure 2 herein)	
	V_{CB} = 10 V dc I_E = 0 0.1 MHz ≤ f ≤ 1.0 MHz	V_{CE} = 10 V dc I_C = 5 A dc f = 1 MHz	V_{CE} = 5 V dc I_C = 10 A dc f = 1 kHz	t_{on}	t_{off}
	Min Max pF	Min Max	Min Max	Min Max µs	Min Max µs
2N5685	1,200	2 20	15	1.5	3.0
2N5686	1,200	2 20	15	1.5	3.0

(1) Pulsed (see 4.5.1).

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.5.1 JAN brand and quality level designators for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: "JAN", "JANTX", and "JANTXV".


1.5.2 Device type. The designation system for the device types of transistors covered by this specification sheet are as follows.

1.5.2.1 First number and first letter symbols. The transistors of this specification sheet are identified by the first number and letter symbols "2N".

1.5.2.2 Second number symbols. The second number symbols for the transistor covered by this specification sheet are as follows: "5685" and "5686".

1.5.3 Lead finish. The lead finishes applicable to this specification sheet are listed on QML-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.



Ltr	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CD		.875		22.22	3
CH	.250	.450	6.35	11.43	
HR	.495	.525	12.57	13.34	
HR_1	.131	.188	3.33	4.78	6
HT	.060	.135	1.52	3.43	
LD	.057	.063	1.45	1.60	4, 5, 9
LL	.312	.500	7.92	12.70	4, 5, 9
L_1		.050		1.27	5, 9
MHD	.151	.165	3.84	4.19	7
MHS	1.177	1.197	29.90	30.40	
PS	.420	.440	10.67	11.18	
PS_1	.205	.225	5.21	5.72	5
S_1	.655	.675	16.64	17.15	

NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Body contour is optional within zone defined by CD.
4. These dimensions shall be measured at points .050 inch (1.27 mm) to .055 inch (1.40 mm) below seating plane. When gauge is not used, measurement shall be made at seating plane.
5. Both terminals.
6. At both ends.
7. Two holes.
8. The collector shall be electrically connected to the case.
9. LD applies between L_1 and LL. Lead diameter shall not exceed twice LD within L_1.
10. Terminal 1 is emitter; terminal 2 is base; case is collector.

FIGURE 1. Physical dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Copies of these documents are available online at https://quicksearch.dla.mil.)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface and physical dimensions. Interface and physical dimensions shall be as specified in MIL-PRF-19500, and on figure 1.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I.

3.7 Electrical test requirements. The electrical test requirements shall be as specified in table I.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and tables I and II).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table II tests, the tests specified in table II herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

4.3 Screening (JANTX and JANTXV levels). Screening shall be in accordance with table E-IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen	Measurements for JANTX and JANTXV levels only
(1) 3c	Thermal impedance (see 4.3.2)
11	h_{FE2} and I_{CEX1}
12	See 4.3.1
13	Subgroup 2 of table I herein; ΔI_{CEX1} = 100 percent of initial value or 1 µA dc, whichever is greater; Δh_{FE2} = 25 percent of initial value.

(1) Shall be performed anytime after temperature cycling, screen 3a; and does not need to be repeated in screening requirements.

4.3.1 Power burn-in conditions. Power burn-in conditions are as follows: T_J = +187.5°C ±12.5°C; V_{CB} ≥ 20 V dc, T_A ≤ +100°C.

4.3.2 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3131 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{SW}, t_{MD} and V_H where appropriate). See table II, group E, subgroup 4 herein.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500, and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500, appendix E table E-V, and table I herein. Electrical measurements (end-points) shall be in accordance with the table I, subgroup 2 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIB (JAN, JANTX and JANTXV) of MIL-PRF-19500 and as follows.

Subgroup	Method	Conditions
B3	1037	V_{CE} ≥ 10 V dc, ΔT_J between cycles ≥ +100°C, adjust power or current to achieve a ΔT_J = +100°C.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500 and as follows.

Subgroup	Method	Conditions
C2	2036	Test condition A, weight = 10 pounds, t = 15 s.
C5	3131	See 4.3.2, $R_{\theta JC}$ = .584°C/W.
C6	1037	V_{CE} ≥ 10 V dc, ΔT_J between cycles ≥ +100°C, adjust power or current to achieve a ΔT_J = +100°C.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of MIL-PRF-19500 and as specified herein.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance 2/	3131	See 4.3.2	$Z_{\theta JX}$			°C/W
Breakdown voltage collector to emitter 2N5685 2N5686	3011	Bias condition D; I_C = 100 mA dc, pulsed (see 4.5.1)	$V_{(BR)CEO}$	 60 80		 V dc V dc
Collector to emitter cutoff current 2N5685 2N5686	3041	Bias condition D V_{CE} = 30 V dc V_{CE} = 40 V dc	I_{CEO}		500	µA dc
Collector to emitter cutoff current 2N5685 2N5686	3041	Bias condition A;V_{BE} = -1.5 V dc V_{CE} = 60 V dc V_{CE} = 80 V dc	I_{CEX1}		10	µA dc
Emitter to base cutoff current	3061	Bias condition D; V_{EB} = -5 V dc, I_C = 0	I_{EBO}		1.0	mA dc
Collector to base cutoff current 2N5685 2N5686	3036	Bias condition D V_{CB} = 60 V dc V_{CB} = 80 V dc	I_{CBO1}		2.0	mA dc
Base to emitter saturated	3066	Test condition A; I_C = 25 A dc, I_B = 2.5 A dc, pulsed (see 4.5.1)	$V_{BE(sat)}$		2.0	V dc
Base to emitter non-saturated	3066	Test condition B; I_C = 25 A dc, V_{CE} = 2 V dc, pulsed (see 4.5.1)	V_{BE}		2.0	V dc
Collector to emitter saturated voltage	3071	I_C = 25 A dc; I_B = 2.5 A dc pulsed (see 4.5.1)	$V_{CE(sat)1}$		1.0	V dc
Collector to emitter saturated voltage	3071	I_C = 50 A dc; I_B = 10 A dc, pulsed (see 4.5.1)	$V_{CE(sat)2}$		5.0	V dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued						
Forward current transfer ratio	3076	V_{CE} = 2 V dc; I_C = 5 A dc, pulsed (see 4.5.1)	h_{FE1}	30		
Forward current transfer ratio	3076	V_{CE} = 2 V dc; I_C = 25 A dc, pulsed (see 4.5.1)	h_{FE2}	15	60	
Forward current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 50 A dc, pulsed (see 4.5.1)	h_{FE3}	5		
Subgroup 3						
High temperature operation:		T_A = +150°C				
Collector to emitter cutoff current 2N5685 2N5686	3041	Bias condition A; V_{BE} = -1.5 V dc V_{CE} = 60 V dc V_{CE} = 80 V dc	I_{CEX2}		5	mA dc
Low temperature operation:		T_A = -55°C				
Forward current transfer ratio	3076	V_{CE} = 2.0 V dc; I_C = 25 A dc, pulsed (see 4.5.1)	h_{FE4}	7		
Subgroup 4						
Pulse response	3251	Test condition A, except test circuit and pulse requirements (see figure 2)				
Turn-on time		V_{CC} = 30 V dc; I_C = 25 A dc, I_{B1} = 2.5 A dc	t_{on}		1.5	µs
Turn-off time		V_{CC} = 30 V dc; I_C = 25 A dc, I_{B1} = - I_{B2} = 2.5 A dc	t_{off}		3.0	µs
Storage time		V_{CC} = 30 V dc; I_C = 25 A dc, I_{B1} = - I_{B2} = 2.5 A dc	t_s		2.0	µs
Magnitude of common emitter small-signal short-circuit forward-current transfer ratio	3306	V_{CE} = 10 V dc; I_C = 5 A dc, f = 1 MHz	$\|h_{fe}\|$	2	20	

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 4 - Continued						
Small-signal short-circuit forward-current transfer ratio	3206	V_{CE} = 5 V dc; I_C = 10 A dc, f = 1 kHz	h_{fe}	15		
Open circuit output capacitance	3236	V_{CB} = 10 V dc; I_E = 0, 0.1 MHz ≤ f ≤ 1 MHz	C_{obo}		1,200	pF
Subgroup 5						
Safe operating area (continuous dc)	3051	T_C = +25°C; t = 1 s, 1 cycle (see figures 3 and 4)				
Test 1		V_{CE} = 6 V dc; I_C = 50 A dc				
Test 2		V_{CE} = 30 V dc; I_C = 10 A dc				
Test 3						
2N5685 2N5686		V_{CE} = 50 V dc; I_C = 560 mA dc V_{CE} = 60 V dc; I_C = 640 mA dc				
Safe operating area (switching)	3053	Load condition C (unclamped inductive load) (see figure 5)				
		T_C = +25°C duty cycle ≤ 10 percent R_S = 0.1 Ω; t_r = t_f ≤ 500 ns				
Test 1		t_p approximately 5 ms (vary to obtain I_C); R_{BB1} = 10 Ω; V_{BB1} = 20 V dc; R_{BB2} = ∞; V_{BB2} = 0 V; V_{CC} = 50 V dc; I_C = 20 A dc; L = 1 mH; Sanford Miller CK - 50, 50 A .002 Ω (or equivalent)				
Test 2		t_p approximately 5 ms (vary to obtain I_C); R_{BB1} = 100 Ω; V_{BB1} = 10 V dc; R_{BB2} = ∞; V_{BB2} = 0 V; V_C = 50 V dc; I_C = 1.5 A dc; L = 80 mH; (2 each signal transformer CH06, 6A) 0.4 Ω (or equivalent)				

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 5 - Continued						
Safe operating area (switching)	3053	Clamped inductive load (see figures 6 and 7) T_A = +25°C; V_{CC} = 50 V dc				
2N5685		Clamp voltage = 60 V dc				
2N5686		Clamp voltage = 80 V dc				
Electrical measurements		See table I, subgroup 2				


1/ For sampling plan, see MIL-PRF-19500.
2/ This test required for the following end-point measurements only:
Group B, subgroups 2 and 3 (JAN, JANTX, and JANTXV).
Group C, subgroups 2 and 6.
Group E, subgroup 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.


TABLE II. Group E inspection (all quality levels) - for qualification or re-qualification only.

Inspection	MIL-STD-750		Sample plan
	Method	Conditions	
Subgroup 1			45 devices, c = 0
Temperature cycling	1051	Test condition C, 500 cycles.	
Hermetic seal	1071	Fine and gross leak.	
Electrical measurements		See table I, subgroup 2 herein.	
Subgroup 2			45 devices, c = 0
Blocking life	1048	Test temperature = +125°C; V_{CB} = 30 V dc; T = 1,000 hours.	
Electrical measurements		See table I, subgroup 2 herein.	
Subgroup 4			
Thermal impedance curves		See MIL-PRF-19500.	
Subgroup 8			45 devices, c = 0
Reverse stability	1033	Condition B.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.



TURN-ON (t_{ON}) TIME TEST CIRCUIT



toff = ts + tf

TURN-OFF (t_{OFF}) TIME TEST CIRCUIT

FIGURE 2. Switching time test circuits.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.




FIGURE 3. Maximum safe operating area graph continuous dc (2N5685).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.




FIGURE 4. Maximum safe operating area graph continuous dc (2N5686).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.





FIGURE 5. Safe operating area for switching between saturation and cutoff (unclamped inductive load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.



PROCEDURE:

1. With switch S_1 closed, set the specified test conditions.
2. Open S_1. Device fails if clamp voltage not reached.
3. Perform specified end-point tests.

NOTES:

1. L = 2.0 mH (2 each 1 mH, 50 A, R = .002 Ω, Sanford Miller CK-50, or equivalent).
2. $R_S \leq 0.1\Omega$, 12 W; 1 percent tolerance maximum; (noninductive).

FIGURE 6. Clamp inductive sweep test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.




FIGURE 7. Safe operating area for switching between saturation and cutoff (clamped inductive load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.


b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.5 and 6.4.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML-19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Weapons Support, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://assist.dla.mil.

6.4 PIN construction example. The PINs for encapsulated devices are construction using the following form.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.

6.5 List of PINs. The following is a list of possible PINs for encapsulated devices available on this specification sheet.

PINs for types 2N5685	PINs for types 2N5686
JAN2N5685	JAN2N5686
JANTX2N5685	JANTX2N5686
JANTXV2N5685	JANTXV2N5686

6.6 Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Army − CR
Navy − SH
Air Force − 85
NASA − NA
DLA − CC

Review activities:
Army − AR, MI
Air Force − 19, 70, 170

Preparing activity:
DLA − CC

(Project 5961−2025−107)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:13Z
Check the source to verify that this is the current version before use.