INCH-POUND

MIL-R-39016/27E
AMENDMENT 2
20 November 1991
SUPERSEDING
AMENDMENT 1
9 September 1991

MILITARY SPECIFICATION

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, SPDT, LOW LEVEL TO 0.5 AMPERE (LATCHING) WITH INTERNAL DIODES FOR COIL TRANSIENT SUPPRESSION

This amendment forms a part of MIL-R-39016/27E, dated 20 July 1988, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Requirements, resistive, delete in its entirety and substitute:

"Resistive:
0.5 ampere at 28 V dc.
250 milliamperes at 115 V ac 60 and 400 Hz case not grounded.
100 milliamperes at 115 V ac 60 and 400 Hz case grounded."

Requirements, overload (high level only), delete and substitute:

"Overload (high level only): Two times rated current. Not applicable to ac load ratings."

PAGES 3 AND 4

* Electrical data, delete footnote 1/ and associated references to footnote 1/ in their entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-21T17:43Z
Check the source to verify that this is the currentversion before use.

The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - AS, OS, SH
Air Force - 99
DLA - ES

User activities:
Navy - MC
Air Force - 11, 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0872-10)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:43Z
Check the source to verify that this is the current version before use.