INCH-POUND

MIL-R-39016/30E
AMENDMENT 3
11 August 1992
SUPERSEDING
AMENDMENT 2
20 November 1991

MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT,
LOW LEVEL TO 1.0 AMPERE (LATCHING) WITH INTERNAL DIODES FOR COIL
TRANSIENT SUPPRESSION AND POLARITY REVERSAL PROTECTION

This amendment forms a part of MIL-R-39016/30E, dated 20 July 1988 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

REQUIREMENTS, resistive, delete in its entirety and substitute:

"Resistive:
1.0 ampere at 28 V dc.
250 milliamperes at 115 V ac 60 and 400 Hz case not grounded.
100 milliamperes at 115 V ac 60 and 400 Hz case grounded."

REQUIREMENTS, overload (high level only), delete and substitute:

"Overload (high level only): Two times rated current. Not applicable to ac load ratings."

ELECTRICAL DATA, delete footnote 1/ and associated references to footnote 1/ in their entirety.

PAGE 5

* DIODE CHARACTERISTICS, delete and substitute:

"Coil transient suppression: Applicable.

Diode block integrity (perform this test after coil transient suppression test in all inspection tables of MIL-R-39016): With applicable voltage applied to the relay coil circuit in the reverse direction, monitor leakage current with dc microammeter, oscilloscope, or qualifying activity approved test equipment. Leakage current shall not exceed the specified value.

Block integrity maximum leakage current: 1 μA at 50 V dc.

Maximum negative transient: 1.0 volt.

Breakdown voltage: 100 V dc minimum at 10 microamperes (μA). (This test may be performed in-process or as final assembly).

Semiconductor in-process screening: Applicable, visual inspection of semiconductors shall be in accordance with MIL-STD-750, methods 2073 or 2074."

* Footnote 3/, delete in its entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:44Z
Check the source to verify that this is the current version before use.

* TABLE I, add the following new footnote 9/:

"9/ Delete "Coil resistance" and substitute "Coil current" test in all inspection tables of MIL-R-39016."

* TABLE I, add footnote 9/ to the coil circuit column.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AL, AR, AT, MI
Navy - OS, SH
Air Force - 99
DLA - ES

User activities:
Army - AV, ME
Navy - AS, MC
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0897-05)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:44Z
Check the source to verify that this is the current version before use.