INCH-POUND

MIL-R-39016/31B
AMENDMENT 1
27 February 1989

MILITARY SPECIFICATION

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, HERMETICALLY SEALED, 4 PDT, LOW LEVEL TO 2 AMPERES (0.150-INCH TERMINAL SPACING), LATCHING

This amendment forms a part of MIL-R-39016/31B, dated 20 July 1988, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 5

TABLE I, footnote 2, delete and substitute:

"2/ WARNING: When latching relays are installed in equipment, the latch and reset coils should not be pulsed simultaneously. Coils should not be pulsed with less than the rated coil voltage."

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - AS, OS, SH

User activities:
Navy - MC
Air Force - 11, 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0805)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:45Z
Check the source to verify that this is the current version before use.