MILITARY SPECIFICATION SHEET

RELAYS, RADIO FREQUENCY (COAXIAL), ESTABLISHED RELIABILITY,
ELECTRICAL, HERMETICALLY SEALED,
SPDT AND DPDT, DC TO 1 GHz

This amendment forms a part of Military Specification Sheet MIL-R-39016/33D(EC), dated 13 March 1984, and is approved for use by the Space and Naval Warfare Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 6

ENVIRONMENTAL DATA, delete "Vibration" and "Shock" in their entirety and substitute:

"Vibration (sinusoidal): MIL-STD-202, method 204, (20 g's, 10 to 2,000 Hz). Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

"Shock (specified pulse): MIL-STD-202, method 213, test condition B (75 g's). Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts."

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5945-N604-1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:45Z
Check the source to verify that this is the current version before use.

FSC 5945

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.