INCH-POUND

MIL-PRF-39016/37B
AMENDMENT 2
28 June 1996
SUPERSEDING
AMENDMENT 1
10 July 1992

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT, LOW LEVEL TO 2 AMPERES (0.150-INCH TERMINAL SPACING) WITH INTERNAL DIODE FOR COIL TRANSIENT SUPPRESSION

This amendment forms a part of MIL-PRF-39016/37B, dated 20 July 1988 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Requirements, contact data, load ratings, high level (relay case grounded), resistive: Delete "400 Hz life test not required for qualification testing."

*Requirements, contact data, overload (high level only): Add "(post overload life test shall be 25,000 cycles)".

The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - AS, MC, OS, SH
Air Force - 19, 99

Preparing activity:
DLA - ES

(Project 5945-1000-02)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:47Z
Check the source to verify that this is the current version before use.