MIL-B-7525B
Amendment 2
24 FEB 86
SUPERSEDING
AMENDMENT 1
27 MARCH 1978

MILITARY SPECIFICATION

BRACKET AND RECEPTACLE, HOT CUP, AIRBORNE

This amendment forms a part of Military Specification MIL-B-7525B, dated 29 January 1971, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 2.1 Air Force - Navy Aeronautical. Change AN373 Nut, Self-Locking, Plate, Countersink 100 , 250 F to MS21049 Nut, Self-Locking, Plate Countersink 100 , 125 KSI FTU, 450 F.

* 2.2 National Bureau of Standards.

Change "Handbook H-28" to "FED STD H28".

PAGE 3

After paragraph 3.2.1 add the following new paragraph:

3.2.1.1 Reclaimed Materials. The brackets and receptacles shall contain reclaimed materials to the maximum extent possible without jeopardizing their intended use and performance. Reclaimed materials shall have been reprocessed, remanufactured, and recycled in such a manner as to restore them to their original chemical composition and physical properties. Reclaimed materials shall include, but not be limited to, iron, steel, copper, brass, aluminum, lead, zinc, fiber products, plastic and elastomers that have been collected from discarded solid, liquid semi-solid or gaseous waste such as garbage, refuse or sludge.

* 5.5 Specification definitive part number. The Specification Part Number is definitive and formatted to identify each item covered by selecting from the requirement options available in this specification as follows (see 1.2).

Definitive Specification Part Number M 7525 X

M Prefix - an item defined by inch-pound (US) units
Specification Number
Class of Bracket and Receptacle (see Table I)

Example: M7525-C Class C Bracket and Receptacle (4-Cup Unit, 115 Volts).

FSC 7310

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:34Z
Check the source to verify that this is the current version before use.

* 5.5.1 Class of hot cup brackets and receptacles. A one-position alpha field used to designate the class of hot cup brackets and receptacles required (see Table I).

TABLE I

DASH NO.	CLASS	DESCRIPTION OF HOT CUP BRACKETS AND RECEPTACLE
A	A-1	4-Cup Unit, 28 Volts
B	A-2	1-Cup Unit, 28 Volts
C	B-1	4-Cup Unit, 115 Volts
D	B-2	1-Cup Unit, 115 Volts

The margins of this amendment are marked with an asterick or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CUSTODIANS:
Army - GL
Navy - AS
Air Force - 99

PREPARING ACTIVITY:
Air Force - 84

PROJECT NUMBER:
7310-0706

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:34Z
Check the source to verify that this is the current version before use.