MIL-I-7566C(USAF)
AMENDMENT 2
23 May 1986
SUPERSEDING
AMENDMENT 1
15 MAY 1979

MILITARY SPECIFICATION

INDICATOR SYSTEM, FUEL FLOWMETER, GENERAL
SPECIFICATION FOR

This amendment forms a part of MIL-I-7566C(USAF), dated 8 Nov 74, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Delete "2.1" and add:
"2.1 Government documents."

* Add:
"2.1.1 Specifications and standards. The following specifications and standards, form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation."

* Under SPECIFICATIONS, Federal, delete "QQ-Z-325", "QQ-P-416" and add: "PPP-B-601 Boxes, Wood Cleated-Plywood".

* Under SPECIFICATIONS, Military, delete "MIL-D-1000" and add: "DOD-D-1000".

Add boxed paragraph to bottom center of page.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

* Under SPECIFICATIONS, Military, add: "MIL-C-83488 Coating, Aluminum, Ion Vapor Deposited".

* Under STANDARDS, Military, add: "MIL-STD-810 Environmental Test Methods".

* Add:
"2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:36Z
Check the source to verify that this is the current version before use.

issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ASTM-D-3951-82 Packaging, Commercial - 29 Jan 82.

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)"

PAGE 8

* Paragraph 3.5 line 5 delete "MIL-D-1000" and add: "DOD-D-1000".

PAGE 9

* Delete paragraph "3.8.3" and add:
"3.8.3 Steel parts. Steel parts shall be coated with ion vapor deposited aluminum, where practicable, in accordance with MIL-C-83488, type I or II as applicable and of a class that is adequate to achieve the degree of protection required. Other protective coating, in lieu of MIL-C-83488, may be used if demonstrated to be satisfactory and approved by the preparing activity. Cadmium plating must be avoided when satisfactory alternative processes can be used.

PAGE 11

* Delete paragraph "4.4.1.1".

PAGE 18

* Paragraph 4.5.2.2.1 delete "MIL-E-5272" and add: "MIL-STD-810C".

PAGE 21

Delete Section 5 in its entirety and add:
5 PACKAGING

5.1 Preservation-packaging. Preservation packaging shall be level A, C, or Industrial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Indicators shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Indicators shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3 Preservation application. Not applicable.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each indicator shall be packaged in quantity units packs of one each in accordance

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:36Z
Check the source to verify that this is the current version before use.

with Method 1C1 of MIL-P-116. Overbox completed pack in PPP-B-636 container. Apply sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the indicator when completed packs are subjected to the rought handling drop tests of MIL-P-116.

5.1.2 Level C. Indicators shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3 Industrial. The industrial preservation of indicators shall be in accordance with ASTM-D-3951-82.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1 Level A. Indicators packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, minimum tare and cube consistant with the protection required.

5.2.2 Level B. Indicators packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 apply.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

5.2.4 Industrial. The packaged indicators shall be packed in accordance with ASTM-D-3951-82.

5.3 Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129.

6.2, Add:
"(b) Preservation and Packing as required."

Add new paragraph 6.7:
"6.7 Reclaimed materials. The use of reclaimed materials shall be encouraged to the maximum extent possible."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:36Z
Check the source to verify that this is the current version before use.

Custodian:
Air Force - 99

Preparing Activity:
Air Force - 71

Project Number:
6620 - F400

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:36Z
Check the source to verify that this is the current version before use.