INCH-POUND

MIL-M-7507B
AMENDMENT 4
31 March 1989
SUPERSEDING
AMENDMENT 3
3 AUGUST 1983

MILITARY SPECIFICATION

MACHMETER, PITOT STATIC,
RANGE .3 TO 1.0, Type A-1

This amendment forms a part of MIL-M-7507B, dated 5 February 1962, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1 Delete "first sentence" and add: "Government documents."

* Add: "2.1.1 Specifications and standards. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2)."

* Add: SPECIFICATION, Federal, "PPP-B-601 Wood, Boxes, Cleated Plywood" and "PPP-B-636 Box, Shipping, Fiberboard."

* Under SPECIFICATION, Military, delete "MIL-E-5272", "MIL-P-7936", "MIL-D-70327" and add: "DOD-D-1000 Drawing, Engineering, and Associated Lists."

* Under STANDARDS, Military, delete "MIL-STD-143" and add: "MIL-STD-810C Environmental Test Methods & Engineering Guidelines", "MIL-STD-970 Standards & Specificatons, Order Of Preference For The Selection Of" and "MIL-STD-2073-1 DOD Material Procedures For Development Application of Packaging Requirements."

* Add the following boxed paragraph to bottom of page:

"Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMRDO, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter."

PAGE 2

* Delete the parenthetical source statement that follows the listing of Government specifications and standards and add: (Unless otherwise indicated, copies of

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:33Z
Check the source to verify that this is the current version before use.

federal and military specificatons and standards are available from the Naval Publicatons and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia Pa 19120-5099).

* Add: "(Copies of MIL-STD-810C is available from Director, Naval Publications & Printing Service Office, 700 Robbins Ave, Bldg 4 Section D, Philadelphia PA 19111.)"

* Add: "2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issues of DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2)."

American Society For Testing and Materials (ASTM)
ASTM D3951 Packaging, Commercial

(Application for copies should be addressed to: ASTM, 1916 Race Street, Philadelphia, PA 19103).

(Non-Government standards and other publications are normally available from the organizations that prepare or distrubute the documents. These documents also may be available in or through libraries or other informational services)."

* Add: "2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained."

* 3.1 Delete and add: "3.1 First article. When specified (see 6.3), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.4."

* 3.2.4 Line 5 delete "MIL-STD-143" and add" "MIL-STD-970".

PAGE 7

3.5 Delete "MIL-D-70327" and add: "DOD-D-1000."

* 4.1 Delete entire "paragraph" and add new: 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements."

* Add: 4.1.1 Responsibility for compliance. All items shall meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:33Z
Check the source to verify that this is the current version before use.

contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material."

PAGE 9

* Delete "4.2", "a", and "b" entirety and add: "4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5)."

* 4.3 Delete entirety and add new: "4.3 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in 4.3.1 of this specification."

PAGE 10

4.4 Delete "Qualification testing." and add: "First article inspection."

4.4.1 Delete "paragraph" entirety.

4.4.2 Line 1 delete "qualification tests" and add: "first article inspection" Line 3 delete "qualification" and add: "inspection."

4.4.3 Title and line 1 delete "Qualification tests" and add; "First article inspection."

4.5 Delete "title" and add new title: "Quality conformance inspection."

PAGE 16

* 4.6.13 Delete paragraph entirety and add: "Vibration failure. The instrument shall be mounted on the apparatus in its normal operating position. The machmeter shall be subject to vibration in accordance with Method 514 of MIL-STD-810C."

PAGE 17

* 4.6.14 Delete "first and second sentences and add: "The machmeter shall be subjected to low temperature in accordance with Method 502 of MIL-STD-810C."

* 4.6.15 Delete "first three sentences" and add: "The machmeter shall be subjected to high temperature in accordance with Method 501 of MIL-STD-810C. While still at high temperature, the machmeter shall operate without indications of sticking or erratic action."

* 4.6.16 Delete "first two sentences" and add: The machmeter shall be subjected to humidity in accordance with Method 507 of MIL-STD-810C. After the machmeter has returned to room temperature, it shall be subjected to the test specified in paragraph 4.6.3."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:33Z
Check the source to verify that this is the current version before use.

* 4.6.17 Delete "first sentence" and add: "The machmeter shall be subjected to Method 508 of MIL-STD-810C."

4.7 Delete existing paragraph and add: Inspection of packaging. The inspection of the preservation-packaging and interior package marking shall be in accordance with Group A and B quality conformance inspection requirements, Section 4 of MIL-P-116. The sampling and inspection of the packing and marking for shipment and storage shall be in accordance with the quality assurance provisions of applicable container specifications and the marking requirements of MIL-STD-129.

4.7.2 First article. When the unit container is capable of serving as the shipping container, First Article Inspection and rough handling drop tests as outlined in Section 4 of MIL-P-116, shall be accomplished followed by a functional test of the unit to insure freedom from operational malfunction."

* Delete Section 5 in its entirely and add:

"5. PACKAGING

5.1 Preservation. Preservation shall be level A, C, or Industrial, IAW MIL-STD-2073-1, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Machmeter shall be cleaned in accordance with process C-1 or MIL-P-116.

5.1.1.2 Drying. Machmeter shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3 Preservation application. Preservative shall not be used.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each machmeter shall be packaged in quantity unit packs of one each in accordance with Method IIc of MIL-P-116. Each machmeter shall be placed in a PPP-B-636 Fiberboard container weather resistant, with sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the machmeter when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Each machmeter shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3 Industrial. The Industrial preservation of machmeters shall be in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1 Level A. Machmeter packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical,

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:33Z
Check the source to verify that this is the current version before use.

exterior shipping container shall be of uniform shape, size, minimum tare and cube consistent with the protection required.

5.2.2 Level B. Machmeter packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 apply.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

5.2.4 Industrial. The packaged machmeter shall be packed in accordance with ASTM D3951.

5.3 Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129."

* Add: "6.2.g Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1)".

* 6.3 Delete paragraph in its entirety and add new: First article. When first article inspection is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first production item, a sample selected from the first article production items, a standard production item from the contractor's current inventory (see 3.1), and the number of items to be tested as specified in 4.4. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation."

PAGE 19

6.5 Line 3 delete "ABC Air Standard 10/9." and add: "NAT-STD-3338 and AIR-STD-10/9."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:33Z
Check the source to verify that this is the current version before use.

Custodians:
AIR FORCE - 99
NAVY - AS

Preparing activity:
AIR FORCE - 71

Project No: 6610-0282

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:33Z
Check the source to verify that this is the current version before use.