MILITARY SPECIFICATION

CARTRIDGE, IGNITION, M702
PARTS FOR

This Specification is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements and quality assurance provisions for the fabrication of parts and packing of parts for M702, Ignition Cartridge for the 60MM Lightweight Company Mortar System.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified (see 6.2), the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament Research, Development and Engineering Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1310
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-810	-	Environmental Test Methods
MIL-STD-1169	-	Packaging, Packing and Marking for Shipment of Inert Ammunition Components

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT DRAWINGS (see 6.4)

9280530	- Tube
9280532	- Cap
9280533	- Tube, Flash
9285481	- Head
9321224	- Plug, Firing
12561287	- Body

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the reference cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

3.2 Parts. The parts shall comply with all requirements specified on Drawings (dwgs) 9280530, 9280532, 9280533, 9285481, 9321224, 12561287 as applicable, and with all requirements specified in applicable specifications and standards.

3.2.1 Corrosion resistance (salt spray). Parts selected for the salt spray test shall show no evidence of pitting or mottling when tested in accordance with 4.5.3.

3.3 Bursting strength. The tube (9280530) shall not burst at a compression load of 57 pounds, minimum, but shall burst at a compression load of 192 pounds, maximum. Testing shall be as specified in 4.5.2.

3.4 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein. (See 4.3 and 6.2).

3.5 Workmanship. All parts shall be fabricated and finished in a thorough workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, rust and other foreign matter. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.1.1 Responsibility for compliance. All items must meet all requirements of section 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirement of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the components in the quantities described in Table I.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48161B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Tube (dwg. 9280530)				
	Examination for defects	25		3.2	4.4.2.1
	Bursting strength test	25		3.3	4.4.2.1/4.5.2
	Cap (dwg. 9280532)				
	Examination for defects	25		3.2	4.4.2.2
	Tube, Flash (dwg. 9280533)				
	Examination for defects	25		3.2	4.4.2.3
	Salt spray test	25		3.2.1	4.5.3
	Head (dwg. 9285481)				
	Examination for defects	25		3.2	4.4.2.4
	Plug, Firing (dwg. 9321224)				
	Examination for defects	25		3.2	4.4.2.5
	Body (dwg. 12561287)				
	Examination for defects	25		3.2	4.4.2.6
	Salt spray test	25		3.2.1	4.5.3

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48161B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Tube		9280530
			NEXT HIGHER ASSEMBLY
			12561285

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Bursting strength test		(a)	3.3	4.5.2
102	Thickness		0.40%	3.2	Gage
103	Length		0.40%	3.2	Gage
104	Inside diameter		0.40%	3.2	Gage
105	Tube not properly spiral wound		0.40%	3.2	Visual
106	Evidence of tube delaminations, holes, or separations		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:
(a) Sample per MIL-STD-105, Inspection Level I, 0.40% AQL.

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48161B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9280532
4.4.2.2	Cap				NEXT HIGHER ASSEMBLY 9280553
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	True position of cavity		0.40%	3.2	Gage
103	Diameter of cavity		0.40%	3.2	Gage
104	Depth of cavity		0.40%	3.2	Gage
105	Length from base of cavity to face		0.40%	3.2	Gage
106	Protective finish missing		0.40%	3.2	Visual
107	Length from flange to face (3 places)		0.40%	3.2	Gage
Minor					
201	Radii or chamfers missing		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48161B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Tube, Flash		9280533
			NEXT HIGHER ASSEMBLY 9280529

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special					
A	Flash hole(s) missing or obstructed		100%	3.2	Visual
B	Longitudinal flash hole missing or obstructed		100%	3.2	Visual
Major					
101	True position of flash holes		0.40%	3.2	Gage
102	Diameter of flash holes		0.40%	3.2	Gage
103	Length		0.40%	3.2	Gage
104	Large outside diameter		0.40%	3.2	Gage
105	Small outside diameter		0.40%	3.2	Gage
106	Length of small outside diameter		0.40%	3.2	Gage
107	Inside diameter		0.40%	3.2	Gage
108	Length of inside diameter (pin end)		0.40%	3.2	Gage
109	Inside diameter (pin end)		0.40%	3.2	Gage
110	Protective finish missing or damaged		0.40%	3.2	Visual
111	Inside diameter (pellet end)		0.40%	3.2	Gage
112	Salt spray test		0.065%	3.2.1	Visual/4.5.3
113	Radius at base of pellet cavity		0.40%	3.2	Gage
114	Radius at entrance of pellet cavity		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48161B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 9285481
4.4.2.4	Head				NEXT HIGHER ASSEMBLY 9280553
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of internal threads		0.40%	3.2	Gage
102	Minor diameter of internal threads		0.40%	3.2	Gage
103	Pitch diameter of external threads		0.40%	3.2	Gage
104	Major diameter of external threads		0.40%	3.2	Gage
105	Length of internal thread, min.		0.40%	3.2	Gage
106	Overall length		0.40%	3.2	Gage
107	Length of large internal diameter		0.40%	3.2	Gage
108	Small internal diameter		0.40%	3.2	Gage
109	Large internal diameter		0.40%	3.2	Gage
110	Large outside diameter		0.40%	3.2	Gage
111	Small outside diameter		0.40%	3.2	Gage
112	Protective finish missing		0.40%	3.2	Visual
113	True position of internal thread		0.40%	3.2	Gage
114	True position of small internal diameter		0.40%	3.2	Gage
115	True position of large internal diameter		0.40%	3.2	Gage
Minor					
201	Length from small end to shoulder		0.65%	3.2	Gage
202	Length of external thread undercut		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Head (Cont)	2 OF 2	9285481
			NEXT HIGHER ASSEMBLY 9280553

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
203	Length from shoulder to end of external thread		0.65%	3.2	Gage
204	Radii, chamfers or countersinks missing or incorrect		0.65%	3.2	Visual
205	Surface finish improper		0.65%	3.2	Visual
206	Depth of spanner holes		0.65%	3.2	Gage
207	True position of spanner holes		0.65%	3.2	Gage
208	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Plug, Firing	1 OF 1	9321224
			NEXT HIGHER ASSEMBLY: 9280553

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of tip		0.40%	3.2	Gage
102	Total length including tip		0.40%	3.2	Gage
103	Length from tip to small diameter		0.40%	3.2	Gage
104	True position of tip		0.40%	3.2	Gage
105	Radius improper (tip)		0.40%	3.2	Gage
106	Large diameter		0.40%	3.2	Gage
107	Small diameter		0.40%	3.2	Gage
Minor					
201	Protective finish improper		0.65%	3.2	Visual
202	Chamfer missing		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 12561287
4.4.2.6	Body				NEXT HIGHER ASSEMBLY 9280553
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special A	Flash hole missing or obstructed		100%	3.2	Visual
Major					
101	Pitch diameter of threads		0.40%	3.2	Gage
102	Major diameter of threads		0.40%	3.2	Gage
103	Diameter of primer cavity		0.40%	3.2	Gage
104	Depth of Primer cavity		0.40%	3.2	Gage
105	Depth of flash tube cavity		0.40%	3.2	Gage
106	Diameter of flash tube cavity		0.40%	3.2	Gage
107	Diameter of flash hole		0.40%	3.2	Gage
108	Protective finish missing		0.40%	3.2	Visual
109	Large outside diameter		0.40%	3.2	Gage
110	True position of primer cavity		0.40%	3.2	Gage
111	Length of sealant groove		0.40%	3.2	Gage
112	Depth of sealant groove		0.40%	3.2	Gage
113	Small outside diameter		0.40%	3.2	Gage
114	Diameter of countersink at base of primer cavity, max.		0.40%	3.2	Gage
115	Length from large diameter to small end		0.40%	3.2	Gage
116	True position of outside diameter		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48161B (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Body (Cont)	2 OF 2	12561287
			NEXT HIGHER ASSEMBLY: 9280553

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
117	Intermediate outside diameter		0.40%	3.2	Gage
118	Length from large outside diameter to end of external thread		0.40%	3.2	Gage
119	Length from large diameter to beginning of thread		0.40%	3.2	Gage
120	Length of large diameter section		0.40%	3.2	Gage
121	Salt spray test		0.065%	3.2.1	Visual/4.5.3
122	Radius at end of primer flashhole		0.40%	3.2.	Gage
123	Radius at shoulder of flashtube cavity		0.40%	3.2	Gage
Minor					
201	Radii, chamfer and countersink missing or incorrect		0.65%	3.2	Gage
202	Surface finish improper		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and test prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the Tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection

4.5.1 Materials, components and processes. Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspections. The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

4.5.2 Bursting strength. The tube shall be cut in half lengthwise and one of the halves placed in the fixture (see figure 1). The stop (3) shall be completely removed or backed off so that it does not touch the punch (2). Place fixture in universal tester set for a travel speed of 0.125 inches per minute. Proceed with Test Number 1 and 2.


TEST NUMBER 1: NO BURST

Apply 57 pound compression load, remove body assembly. Item is rejected if evidence of bursting is observed. Tearing or puncturing of material shall be considered evidence of bursting.

TEST NUMBER 2: BURSTING

If item is not rejected, replace it in fixture, using opposite end of body and apply 192 pounds compression load. If, item shows no evidence of bursting (punch travels thru material) it shall be rejected.


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.



ASSEMBLY
BUSTING STRENGTH
TEST FIXTURE

FIGURE 1 SHEET 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.



① FIXTURE

MAT'L - MACH. STEEL 1 REQ'D

③ 10-32 SOC. SET SCREW FULL DOG PT 3/8 LG

④ 10-32NF-2A SOC. SET SCREW FULL DOG PT 1/2 LG

NOTE DIAMETER TO SUIT APPLICABLE BODY ASS'Y

FIGURE 1 SHEET 2

DIMENSIONS ARE IN INCHES
TOLERANCES ON DICIMALS ±.005
FRACTIONS: 1/64
ANGLE ± 2°

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.




FIGURE 1 SHEET 3

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

4.5.3 Salt spray test. Samples selected for this test shall be tested using equipment and procedures in accordance with MIL-STD-810 method 509.2, Salt Fog. Parts shall be tested with the black powder pellet end up and the pellet cavity inclined approximately six degrees from the vertical in fixturing which does not obstruct the longitudinal flashhole. Parts shall be tested for 336 hours, minimum. Parts shall be rinsed, dried and examined for evidence of pitting or mottling of the finish especially on all black powder pellet contact surfaces. One or more pits or mottling shall be cause for rejection of all anodized parts represented by the sample.

5. PACKAGING

5.1 Packaging, packing and marking. Packaging, packing and marking shall be in accordance with the requirements of Level B in MIL-STD-1169.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use on the M702 Ignition Cartridge.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approvals. See MIL-A-48078. Submit designs as required to Commander, US Army ARDEC, ATTN: AMSMC-QAT-I (D), Bldg 62, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as, ARRADCOM, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.5 Subject term (key word) listing.

Cartridge, ignition
Plug, firing
Strength, bursting
Tube, flash

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

6.6 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issues due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-A374)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-48161B	CARTRIDGE, IGNITION, M702 PARTS FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.