MILITARY SPECIFICATION

CUSHION, SEAT, SURVIVAL CONTAINER

1. SCOPE

1.1 Scope. This specification covers the seat cushion assembly mounted on the rigid seat style survival container. This cushion is considered as Life Support equipment.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

V-F-106	Fastener, Slide, Interlocking

Military

MIL-P-116	Preservation, Methods of
MIL-B-371	Braid, Textile (Cotton, Tubular)
MIL-L-3754	Leather, Cattlehide, Chrome Tanned, Strap, Pad, and Reinforcement
MIL-C-20696	Cloth, Coated, Nylon, Waterproof
MIL-S-27332	Seat Cushion Insert, Polyurethane Foam, Plastic, General Specification for
MIL-C-81393	Cloth Knitted, Polyamide, High Temperature Resistant, Simplex, Jersey
MIL-T-83193	Thread, Nylon, Spun Staple, High Temperature
MIL-C-83391	Cloth, Duck, Aromatic Polyamide, Non-Melting

STANDARDS

Federal

FED-STD-191	Textile Test Methods

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

FED-STD-595	Colors
FED-STD-751	Stitch, Seam and Stitching

Military

MIL-STD-100	Engineering Drawing Practices
MIL-STD-130	Identification Marking of U. S. Military Property
MIL-STD-143	Standards and Specifications, Order of Precedence for the Selection of
MIL-STD-794	Part and Equipment, Procedures for Packaging and Packing of
MIL-STD-831	Test Reports, Preparation of
MS27983	Fastener, Snap, Style 4

DRAWINGS

Air Force

67D25085	Insert, Seat Cushion
67J25086	Seat Cushion, Survival Container, Assembly of

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

HQ DPSC Handbook 4120.1 List of Armed Services Colors for Clothing, Equipage, and Textiles
Defense Personnel Support Center
2800 South 20th Street
Philadelphia PA 19101

(Application for copies should be addressed to the above mentioned address).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Qualification. Seat cushion assemblies furnished under this specification shall be products which are qualified for listing on the applicable qualified products list at the time set for opening of bids (see 4.3 and 6.4).

3.2 Selection of specification and standards. Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

3.3 Materials. Materials shall conform to applicable specifications and shall be as specified herein and on applicable drawings. Materials which are not covered by specifications, or which are not specifically described herein, shall be of the best quality, or the lightest practicable weight, and suitable for the purpose intended.

3.3.1 Nonmetallic materials. The nonmetallic materials used shall be light in weight and shall be strong enough to withstand constant flexing of the fiber or weave from the maximum weight of a crewmember. Any nonmetallic material which has a tendency to tear, harden, or lose its natural characteristics shall not be used. Natural characteristics shall be defined as properties inherently characteristic of newly processed natural material. For example: Rubber stretching or flexing.

3.3.2 Metals. Metals shall be of the corrosion-resistant type or suitably treated to resist corrosion due to fuels, salt spray, or atmospheric conditions. The use of any protective treatment that will crack, chip, or scale with age or extremes of atmospheric conditions shall be avoided.

3.4 Design and construction. The seat cushion assembly shall be complete when foam insert, slide fasteners, snap fasteners, and reinforcement panels are attached to the cushion or contained within the outer fabric according to 67J25086. The seat cushion shall be designed so as to fit the respective type of rigid seat survival kit and shall provide adequate support and comfort for the aircrew member.

3.4.1 Foam insert. The foam insert shall be polyurethane foam plastic in accordance with MIL-S-27332 and shall be of the desired dimensions as specified on 67D25085.

3.4.2 Basic cover. The basic cover shall contain those materials as specified for the top, bottom, side, and reinforcement panels.

3.4.2.1 Top cover panel. The top cover panel shall be made of knitted polyamide cloth, high temperature resistant, simplex jersey, or equivalent as specified in MIL-C-81393. The color of the top cover panel shall be sage green No. 1565 in accordance with HQ DPSC Handbook 4120.1. All edges of this cloth shall be sealed or seared to prevent fraying.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

3.4.2.2 Bottom cover panel. The bottom cover panel shall conform to MIL-C-83391 and shall be sage green Number 1565 in accordance with HQ DPSC Handbook 4120.1.

3.4.2.3 Side cover panel. The side cover panel shall be made of the same material and shall be of the same color as specified in paragraph 3.4.2.2 for the bottom cover panel.

3.4.2.4 Inner and outer reinforcement cover panels. The reinforcement inner and outer cover panels shall be made of cattlehide leather, tanned, Type II, or equivalent, in accordance with MIL-L-3754 and shall be black No. 111 in accordance with HQ DPSC Handbook 4120.1.

3.4.2.5 Bottom reinforcement cover panel. The bottom reinforcement cover panel shall be made of chloroprene coated nylon cloth, Type II, Class 3 or equivalent, in accordance with MIL-C-20696. The color shall be the same as the bottom cover panel.

3.4.3 Slide fastener. The slide fastener shall be that fastener specified in V-F-106, Style 7 or 8, Class B, Aluminum Alloy, Tape Mildew Resistant, Type I or Type IV with or without pull tab and of the required length as specified on 67J25086. The color shall be sage green No. 34158 in accordance with FED-STD-595.

3.4.4 Thread. The thread used shall be nylon in accordance with MIL-T-83193 and shall be of the same color as the basic fabric.

3.4.5 Snap fastener. The snap fastener shall be that fastener specified in MS27983-1 and MS27983-2 or equivalent, and shall be of the required number and located in the proper location according to 67J25086.

3.4.6 Welting cord. The welting cord shall be 1/8 inch diameter, commercial paper cord with smooth round surface or cotton braid, Type IV in accordance with MIL-B-371.

3.4.7 Flame proofness. All cover materials used in the seat cushion assembly shall be flameproof and pass the test specified in paragraph 4.5.2. Afterflame and after-glow time and char length shall not exceed material specification requirements.

3.4.8 Stitching. Stitching shall be 8 to 10 stitches per inch with a back stitch of ½ inch minimum and shall be stitch type 301 per FED-STD-751. Stitching of required components shall be in accordance with 67J25086.

3.5 Interchangeability. All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable. The drawing numer requirements of MIL-STD-100 shall govern changes in the manufacturer's part numbers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

3.6 Identification of product. The seat cushion assembly shall be marked with the following information in accordance with MIL-STD-130. The marking shall be impregnated in black lettering with no less than 3/16 inch nor greater than 5/16 inch in height and centered on the bottom cover of the basic cover assembly.

* Manufacturer's Name and Code
* Manufacturer's Part Number
* Issue Date
Seat Cushion
* Air Force Part Number
USAF
* Contract No.

NOTE: (*) Manufacturer shall include the applicable information.

3.7 Workmanship. The seat cushion assembly shall be uniform in quality and shall be free from irregularities, defects or foreign matter which could adversely affect safety, performance, reliability or durability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure-supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The examination and testing of the seat cushion assembly shall be classified as follows:

(a) Qualification inspection. Qualification inspection consists of examinations and tests performed on samples submitted for approval as qualified products.

(b) Quality conformance inspection. Quality conformance inspection consists of examinations and tests performed on individual products or lots to determine conformance of the products or lots with the requirements set forth in this specification.

4.3 Qualification inspection. Qualification inspection shall consist of all the examinations and tests of this specification.

4.3.1 Qualification samples. Three seat cushion assemblies shall be prepared in accordance with this specification and shall be representative of production. The test samples that were tested shall be furnished to the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

qualifying activity at the same time as the test reports. The samples shall be identified with such information as required in this specification and the procuring activity.

4.3.2 Test report. Three copies of a test report prepared in accordance with MIL-STD-831 shall be furnished to the qualifying activity. The test report shall include the results of all tests and a detailed statement of compliance or non-compliance with each requirement of this specification, identified by the applicable paragraph number.

4.4 Quality conformance inspection. Quality conformance inspection shall consist of the following examinations and tests.

4.4.1 Individual tests. Each seat cushion assembly shall be visually inspected for defects in workmanship as specified in Table I. Three minor defects out of a lot of 25, or fraction thereof, shall constitute rejection. One critical defect shall constitute rejection.

4.4.2 Rejection and retests. When an item selected from a production run fails to meet the specification, no items still on hand or later produced shall be accepted until the extent and cause of failure have been determined and appropriately corrected. The contractor shall explain to the Government representative the cause of failure and the action taken to preclude recurrence. After correction, all of the tests shall be repeated.

4.5 Test Conditions.

4.5.1 Visual examination. The seat cushion assembly shall be examined according to Table I. Three minor defects out of a lot of 25 spacer assemblies, or fraction thereof, constitutes a major defect. Any major defect shall constitute rejection.

TABLE I

CLASSIFICATION OF DEFECTS FOR VISUAL EXAMINATION

CRITICAL	MINOR
1. Dimensions not meeting specifications within tolerance limits.	101. Identification missing, illegible, or not conforming to specification.
2. Basic cover snagged or torn, stitching loose or missing, cushion insert missing or not conforming to fit, slide fasteners missing or not meeting dimension or detail requirements, snap fasteners missing, reinforcements missing.	102. Basic fabric soiled or otherwise discolored.
3. Slide fasteners damaged or not operating properly.	103. Excess thread showing from seams. Stitching ends not trimmed.
4. Snap fasteners not conforming to specification or damaged.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

TABLE I cont'd

CLASSIFICATION OF DEFECTS FOR VISUAL EXAMINATION

CRITICAL	MINOR
5. Any other impairments or irregularities which might hinder intended use of the seat cushion assembly.	104. Edges of polyamide stretch cloth not sealed or seared to prevent fraying.
6. Precautionary marking illegible, missing, or not conforming to specifications.	
7. Any materials which do not conform to specification.	

4.5.2 Flame resistance. The basic cover shall be subjected to the flame resistance test method 5903 of FED-STD-191. The sample shall meet the design requirements of paragraph 3.4.9.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing and marking. Preservation and packaging of the seat cushion assembly shall be Method III in accordance with MIL-P-116. The seat cushion assembly shall be free from grease, oil or any other foreign substance which might discolor, corrode, or deteriorate the seat cushion assembly. The package shall be marked with the information specified in paragraph 3.6 in accordance with MIL-STD-130. Packing shall be Level A, B or C per MIL-STD-794, as specified in the contract or order (See 6.2).

6. NOTES

6.1 Intended use. The seat cushion assembly shall be used on the rigid seat style survival kits. The seat cushion shall support a crewman comfortably yet not hinder operational effectiveness or safety of the rigid seat survival kit.

6.2. Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.

(b) List of interchangeable components and assemblies.

(c) Level of packing.

6.3 Data. For the information of contractors and contracting officers, any of the data specified in applicable documents listed in Section 2 of this specification or referenced lower-tier documents need not be prepared for the Government and shall not be furnished to the Government unless specified in the contract or order. The data to be furnished shall be listed on DD Form

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

1423 (Contractor Data Requirements List), which shall be attached to and made a part of the contract or order.

6.4 Qualification. With respect to products requiring qualification, awards will be made only for products which are at the time set for opening of bids, qualified for inclusion in the applicable Qualified Products List whether or not such products have actually been so listed by that date. The attention of the suppliers is called to this requirement, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the Qualified Products List is OCAMA (MMEO) Tinker AFB Okla 73145 and information pertaining to qualification of products may be obtained from that activity.

Custodian:
Air Force - 71

Preparing Activity:
Air Force - 71

Project Number
1660-F099

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.