MIL-M-52288A(ME)
12 October 1973
SUPERSEDING
MIL-M-52288(MO)
12 April 1963

MILITARY SPECIFICATION

MAST MOUNTING, FLOODLIGHT

1. SCOPE

1.1 This specification covers a mast mounting to permit attachment of three floodlights to a telescoping mast.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-F-320	- Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.
PPP-T-60	- Tape: Packaging, Waterproof.

FSC 6230

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:13Z
Check the source to verify that this is the current version before use.

Military

MIL-T-704	- Treatment and Painting of Materiel.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.

DRAWINGS

ME

TA13208E4154	- Mast Mounting Floodlight.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street NW, Washington, DC 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:13Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Description. The mast mounting shall be in accordance with Top Assembly TA13208E4154 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the supplier or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 Identification markings. The identification markings shall be in accordance with MIL-STD-130.

3.3 Treatment and painting. The mast mounting shall be cleaned, treated, and painted in accordance with MIL-T-704, color 34087.

3.4 Material. Material shall be as specified herein and on the applicable drawings. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification.

3.5 Workmanship. Joints and seams shall be tight, edges shall be smoothly finished, and welded surfaces shall be clean.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:13Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The supplier is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.1.2 Acceptability criteria. Mast mountings which conform to all requirements in sections 3 and 5 of this specification and pass all applicable examinations and tests in section 4 of this specification will be considered acceptable by the Government.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Quality conformance inspection (see 4.3).
(b) Inspection of preparation for delivery (see 4.5).

4.3 Quality conformance inspection.

4.3.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105, inspection level S-2. AQL shall be 10 percent defective.

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined as specified in 4.4.1.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:13Z
Check the source to verify that this is the currentversion before use.

4.3.3 Tests. Samples selected in accordance with 4.3.1 which have passed the examination specified in 4.3.2 shall be tested as specified in 4.4.2.

4.4 Inspection procedure.

4.4.1 Examination. The mast mounting shall be examined for the following defects:

101. Dimensions not as specified.
102. Parts or components misalined.
103. Materials not as specified.
104. Treatment and painting not as specified.
105. Identification markings missing or illegible.
106. Workmanship not as specified.

4.4.2 Test. Install the mast mounting in a jig which will accommodate the bottom end and hold the mast mounting in a vertical position. Install a 1/2 inch flat washer; install a 1/2-13 UNC-2B nut fully on the threads and tighten to a torque of 500 inch-pounds on each threaded screw to simulate installing and removing a floodlight. Remove the nut. Repeat the procedure five times. Damage to the screw or threads, or any deformation or breakage, or inability of the threads to be fully engaged when torque is applied shall constitute failure of this test.

4.5 Inspection of preparation for delivery.

4.5.1 Quality conformance inspection of pack.

4.5.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.5.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:13Z
Check the source to verify that this is the current version before use.

4.5.1.3 Examination. Samples selected in accordance with 4.5.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

107.	Mast mountings not wrapped as specified for level A.
108.	Packing not as specified for level A or B.
109.	Quantity packed in each container not as specified for level A, B or C.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Each mast mounting shall be wrapped with fiberboard conforming to PPP-F-320, W6c. The fiberboard shall be folded over the ends of the mast mounting and secured with tape conforming to PPP-T-60, type IV.

5.1.2 Level C. The mounting mast shall be packaged to afford protection against deterioration and damage during shipment from the supplier to the initial destination.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. The mast mountings, packaged as specified in 5.1, shall be packed in close fitting boxes conforming to either PPP-B-621, class 2 or PPP-B-601, overseas type, grade B in quantities as specified (see 6.2), not to exceed 200 pounds. Closure and strapping shall be in accordance with the appendix to the applicable box specification.

5.2.2 Level B. The mast mounting shall be either packed as specified in 5.2.1, except the boxes shall be the domestic type, or the mast mountings shall be packed in boxes conforming to PPP-B-636, class weather-resistant with a method V closure.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:13Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. The mast mounting shall be packed in the quantities specified (see 6.2) to assure carrier acceptance and safe delivery to destination at lowest rates in containers complying with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.3 Marking. Packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The mast mounting is intended to be used to mount three floodlights on a telescoping mast.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Level of preservation and packaging and level of packing required (see 5.1 and 5.2).
(c) Quantity to be packed, not to exceed 200 pounds (see 5.2.1 and 5.2.3).

Custodian:

Army - ME

Preparing activity:

Army - ME

Project No. 6230-A109

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:13Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
MIL-M-52288A(ME) Mast Mounting, Floodlight

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1426
11 Oct 72 (Rev)

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:13Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. ARMY MOBILITY EQUIPMENT
RESEARCH, DEVELOPMENT
CENTER
FORT BELVOIR, VIRGINIA 22060

OFFICIAL BUSINESS

AMSME-RZD-S

POSTAGE AND FEES PAID
DOD-314

COMMANDER
U. S. ARMY MOBILITY EQUIPMENT
RESEARCH. DEVELOPMENT CENTER
ATTN: AMSME-RZD-S
FORT BELVOIR, VIRGINIA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:13Z
Check the source to verify that this is the current version before use.