MILITARY SPECIFICATION

MUNITION FOR MINE, ANTI-PERSONNEL: M86 TRANSFER LEAD ASSEMBLY

This specification is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the fabrication of parts, loading, assembling and packing for one type of Transfer Lead Assembly used in the Mine, Anti-Personnel, M86.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For .

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-650 - Explosive: Sampling, Inspection and Testing.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S Army Armament, Munitions and Chemical Command, Attn AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1345

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings and publications. The following other Government documents? and publications form a part of this-specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY ARMAMENT, RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

9245691	-	Detonator, Electric, M100
9298456	-	Lead Cup Assembly
9366664	-	Slider
9366668	-	S&A Assembly
9366678	-	Transfer Lead Assembly
9366684	-	Slider Assembly
12555281	-	Acceptor Lead Assembly

(Copies of specifications, standards, handbooks, drawings, publications and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

CODE OF FEDERAL REGULATIONS

Title 49 - Transportation, Parts 100-199

(Application for copies shoud be addressed to: Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders should specify, “49 CFR 100-199 (latest revisions) “) .

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Transfer lead assembly. The transfer lead assembly shall comply with all requirements specified on drawing (dwg.) 9366678, all associated drawings, and with all requirements specified in applicable specifications.

3.3 Transfer lead assembly output. The transfer lead assembly shall when initiated must produce a minimum dent of .009 inch and a minimum average dent of .013 inch in the witness plate (6061-T6 aluminum plate with 1/4 inch minimum thickness).

3.4 Transfer lead assembly functioning. The transfer lead assembly shall function the lead cup assembly high order as evidenced by detonation of the lead-cup.

3.5 Temperature conditioning and functioning of transfer lead assembly.

3.5.1 Hot temperature. The transfer lead assembly shall function the lead cup assembly high order as specified in 3.4 after conditioning (4 hrs. min.) at 156 ± 5°F and tested at a temperature of 125 + 5°F.

3.5.2 Cold temperature. The transfer lead assembly shall function the lead cup assembly high order as specified in 3.4 after conditioning at -40 ± 5°F and tested at a temperature of -25 + 5°F.

3.6 Waterproofness test of transfer lead assembly. The transfer lead assembly shall be waterproof as evidenced by proper output after being immersed in water maintained at 70 + 10 degrees Fahrenheit (°F) at a depth of 2 inches minimum from the surface to the top of the assembly for a period of 40 hours minimum.

3.7 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Disc, Closure	9366680	25
Cup, Transfer Lead	9366679	25
Transfer Lead Assembly	9366678	175 (Note)

NOTE : Fifteen (15) of these assemblies shall be assembled using the procedure specified in 4.5.3 to obtain the density of the explosive charge.

4.3.2 Inspection to be Performed. See MIL-A-48078 and Table I herein.

4.3.3 Rejection. See MIL-A-48078 and Table I herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70777 (AR)

PARAGRAPH	TITLE: Transfer Lead Assembly and Components		SHEET 1 OF 1		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY: ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Disc, Closure (Dwg. 9366680)				
	Examination for Defects	25	-	3.2	4.4.2.1
	Cup, Transfer Lead (Dwg. 9366679)				
	Examination for Defects	25	0	3.2	4.4.2.2
	Transfer Lead Assembly (Dwg. 9366678)				
	Examination for Defects	175	-	3.2	4.4.2.3
	Functioning Output	50	50-0-1	3.3	4.5.4
	Functioning (Ambient)	20	60-1-2	3.4	4.5.5.4
	Hot temperature conditioning and functioning	20	60-1-2	3.5.1	4.5.5.2
	Cold temperature conditioning and functioning	20	60-1-2	3.5.2	4.5.5.3
	Waterproofness	50	50-1-2	3.6	4.5.6
	Density of explosive charge	15	15-0-1	3.2	4.5.3

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4. 4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of transfer lead assemblies shall contain:

a. PBXN-5, seived in accordance with Dwg. 9366678, from one batch or blending of batches which results in homogeneity of PBXN-5 used in loading the entire lead cup assembly.

b. Parts of one lot interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70777 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Disc, Closure				9366680
					NEXT HIGHER ASSEMBLY 9366678
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.2	Gage
Minor					
201	Diameter, (See Note 1)		0.65%	3.2	Gage
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

1. See Paragraph 4.5.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70777 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Cup, Transfer Lead	1 OF 1	9366679
			NEXT HIGHER ASSEMBLY: 9366678

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined	(See 4.5.1)			
Major					
101	Thickness		0.40%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
103	Inside diameter		0.40%	3.2	Gage
Minor					
201	Finish improper		0.65%	3.2	Gage
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 20260-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70777 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Transfer Lead Assembly				9366678
					NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Explosive on exterior surface		100%	3.2	Visual
102	Closure disc punctured		100%	3.2	Visual
103	Cup split or cracked		100%	3.2	Visual
104	Functioning output	50	50-0-1	3.3	4.5.4
105	Functioning (ambient)	60	60-1-2	3.4	4.5.5.5
106	High temperature conditioning and functioning	60	60-1-2	3.5.1	4.5.5.2
107	Low temperature conditioning and functioning	60	60-1-2	3.5.2	4.5.5.3
108	Density of explosive charge			3.2	4.5.3
109	Moisture and volatiles content of explosive charge			3.2	4.5.2
110	Total length		0.40%	3.2	Gage
111	Outside diameter		0.40%	3.2	Gage
112	Crimp less than 360°		0.40%	3.2	Visual
Minor					
201	Assembly damaged		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

Previous editions of DRSMC QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 20260-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70777 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Box Set-Up, Inner, Prior to Sealing				---
					NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Incorrect number of transfer lead assemblies		0.40%	3.2	Visual
102	Cushion missing or inverted		0.40%	3.2	Visual
Minor					
201	Fillers missing		0.65%	3.2	Visual
202	Marking incorrect or unidentifiable		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70777 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Box, Set-Up, Outer, Prior to Sealing		---
			NEXT HIGHER ASSEMBLY: ---

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Incorrect number of inner boxes		0.40%	3.2	Visual
102	Fillers missing		0.40%	3.2	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70777 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Box, Set-Up, Outer, Sealed Prior to Inserting into Bag	1 OF 1	---
			NEXT HIGHER ASSEMBLY: ---

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Corners not blunted		0.40%	3.2	Visual
102	Sealing strip missing		0.40%	3.2	Visual
Minor					
201	Marking incorrect or unidentifiable		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 20260-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70777 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Sealed Barrier Bag				---
					NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Heat seal of barrier bag missing or incomplete		0.40%	3.2	Visual
102	Barrier bag torn or punctured		0.40%	3.2	Visual
Minor					
201	Marking incorrect or unidentifiable		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70777 (AR)

PARAGRAPH 4.4.2.8	TITLE Packing and Marking for Box, Packing Prior to Sealing		SHEET 1 OF 1		DRAWING NUMBER ---
					NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Incorrect number of bagged outer boxes		0.40%	3.2	Visual
Minor 201	Fillers missing		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70777 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Box, Packing, Sealed	1 OF 1	---
			NEXT HIGHER ASSEMBLY: ---

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box damaged exposing contents		0.40%	3.2	Visual
102	Strapping missing, broken or loose		0.40%	3.2	Visual
Minor					
201	Contents loose		0.65%	3.2	Visual-Manual
202	Marking incorrect or unidentifiable		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with Paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See MIL-A-48078.

4.5 Methods of inspection.

4.5.1 Dimensional control of stamped parts. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts shall be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during 'production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

4.5.2 Moisture and volatiles content of explosive charge. The contractor shall provide adequate controls to insure compliance with the applicable requirements. The mositure and volatiles content of the explosive charge shall be determined at the loading station at the time of loading. This determination shall be made at least once each four (4) hours of production. Sampling and testing of the explosive charge shall be in accordance with MIL-STD-650, Method 101.5. In addition, if the moisture and volatiles content fails to comply with the requirement specified on the applicable drawing and loading has not begun, the explosive charge material shall be rejected until corrective action has been taken as verified by repeating the moisture and volatiles content determination. If loading has begun, lead cup assemblies loaded with the non-conforming explosive charge shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

4. 5.3 Density of explosive charge. A minimum of two (2) assemblies, representative of the transfer lead assemblies being processed, shall be loaded and the densities determined to qualify each press prior to its use in production. In addition, a sample of two (2) assemblies shall be processed during the last portion of each one (1) hour's production from each press and the density determined as a control of each press during production.

If any defective assembly is found when inspection is performed for control of a press, the press producing the defective assembly shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for corrective action.

All presses removed from production because of some fault, may, after corrective action, be returned to production providing they pass the qualification test above.

The following procedure shall be used to determine the density of the explosive charge.

a. Weight empty lead cup (grams).

b. Measure bottom thickness (inches).

c. Measure wall thickness (inches).

d. Load cup.

e. Weight loaded lead cup (grams).

f. Measure height to top of charge (inches).

g" Measure outside diameter of loaded lead cup (inches}.

h. Calculate weight of charge (e-a). (grams).

i. Calculate height of charge (f-b) (inches).

j. Calculate volume of explosive charge (cubic centimeters) = (.7854) x (16.39) x (g-2c) x (g-2c) x (i).

k. Calculate density of explosive charge (above). (grams per cubic centimeter) = (h/j).

If any assembly fails to comply with the density requirements specified on the applicable drawing, it shall be classed defective. This is a destructive test. Assemblies so tested shall not be returned to the lot.

NOTE: When weighing in water, use distilled water containing suitable wetting agent, e.g. "Aerosol" (1cc per 250cc distilled water).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

4.5.4 Functioning output. The transfer lead assemblies shall be assembled into a plastic holder and placed with the end of. the assembly in contact with a witness plate of material and thickness as specified in 3.3. The transfer lead assembly shall be initiated by an M100 electric detonator firing across an air gap of .110 ± .010 inches. The detonator shall be initiated by applying the energy from a suitable power source (e.g. 100 . microfarad capacitor charged to 1.6 volts maximum or 6 volt battery) . The depth of the depression in the witness plate shall be determined using a dial indicator with a .015 ± .001 inch spherical radius indicator tip.

4.5.5 Conditioning and functioning.

4.5.5.1 Preparation of samples. Each transfer lead assembly to be subjected to the functioning test shall be assembled into a slider 9366664 forming a slider assembly as per 9366684. This assembly shall then be assembled into a S&A as per 9366668. The slider shall be assembled as to be ‘in line" with the lead cup 9298456. Assembly of the piston actuator and the safety pin shall be omitted. An electric detonator M100 (Dwg. 9245691) shall be shorted and assembled with seal washer into the input hole of the S&A assembly. A successful test shall constitute of firing the detonator, propagating thru the transfer lead and into the lead cup assembly.

A similar test plan could be formulated by the contractor providing that acceptance of the test method is approved prior to testing by the government agency AMSMC-QAT-M (D).

4.5.5.2 Hot conditioning. The transfer lead assemblies to be conditioning and functioning at hot temperature shall be prepared as specified in 4.5.5.1. They shall then be placed in a suitable temperature conditioning box and the temperature increased to 165 + 5°F with relative humidity not less than 15%. The rate of temperature increase shall not exceed 18°F per minute. The samples shall be maintained at temperature for forty (40) hours minimum.

The temperature in the oven shall then be reduced to 125 ± 5°F and the assemblies shall be conditioned at temperature for two (2) hours minimum. The assemblies shall then be removed from the oven and functioned as specified in 4.5.5.4. Set-up time between removal from the oven and firing shall be five (5) minutes maximum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

4.5.5.3 Cold conditioning. The lead cup assemblies to be conditioned and functioned at cold temperature shall be prepared as specified in 4.5.5.1. They shall then be placed in a suitable chamber and the temperature decreased to -25 ± 5°F. The rate of decrease shall not exceed 18°F per minute. The assemblies shall be conditioned at temperature for two (2) hours minimum. The assemblies shall then be removed from the chamber and functioned as specified in 4.5.5.4. Set-up time between removal from the chamber and firing shall be five (5) minutes maximum.

4.5.5.4 Functioning. Each assembly prepared as specified in 4.5.5.1 and after applicable temperature conditioning shall have a lead cup assembly (Dwg. 9298456) and detonating cord with booster from an accepted lot assembled to the output side of the S&A assembly. It is not necessary to temperature condition the lead cup or detonating cord assembly. The space between the assemblies shall be 0.20 inches minimum. The booster end of the detonating cord shall be taped to an aluminum plate (approximate dimensions l 062″ X 2" X 4 1/2"). The detonator shall be functioned behind an approved barricade. The detonator short shall be removed and the detonator shall be initiated by a suitable power source (e.g. 6-volt battery). If the lead assembly fails to initiate the detonating cord for the minimum length specified in 3.4, as evidenced by a witness mark on the aluminum plate, the lead assembly shall be classed defective. Any assembly in which the detonator fails to fire shall be classed as a “no test” and a replacement S&A assembly as specified in 4.5.5.1 shall be used in its place.

4.5.6 Waterproofness test. The transfer lead assemblies shall be immersed in water at a depth of 2 inches minimum from the surface of the water to the top of-the assemblies. The water temperature shall be maintained at 70° ± 10°F. After a minimum of 40 hours, the assemblies shall be removed from the water and subjected to the output test specified in 4.5.4. The functioning test of all samples shall be completed within four hours after the assemblies are removed from the water.

WARNING: The above tests are conducted on assemblies containing an explosive component. Test barricades (where used), procedures and equipment shall have prior approval of the contractor’s safety officer .

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level C. The transfer lead assembly shall be preserved and packaged in accordance with Dwg. 7548104.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

5.2 Packing.

5. 2.1 Level C. The transfer lead assembly, preserved and packaged as specified in 5.1.1, shall be packed in accordance with Dwgs. 7548103 and 9321552.

5.3 Marking. Marking shall be in accordance with Dwgs. 7548103, 7548104, 9321552 and Code of Federal Regulations, Title 49, Parts 100-199.

5.4 Shipping. When components from more than one lot are shipped at one time, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use in the Munition for the M86 Pursuit Deterrent Munition (PDM).

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment design for approval. See MIL-A-48078. Submit equipment designs as required to Commander, ATTN: AMSMC-QAT-I (D), Picatinny Arsenal, New Jersey 07806-5000. Request letter of submittal state contractor, contract number, s-pacification number, item nomenclature and classification of defects or test paragraph. This address will be specified on the Contract Data Requirements List, DD Form 1423 in this contract. Unless otherwise specified, data item DI-R-1714 will apply.

6.4 Check test for possible deterioration. The following test is designed to prevent transfer lead assemblies that have deteriorated from being assembled into major ammunition items. The test shall be performed on transfer lead assemblies for each lot which have been stored for more than two years, or under adverse conditions for any period of time. If the specification for the ammunition item into which the transfer lead assemblies are assembled does not require that the check test be performed, the Contracting Officer should insert in the contract a provision for the performance of the check test. The contracting officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check test for possible deterioration.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament, Research, Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as Edgewood Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

6.6 Distribution of ammunition data cards, inspection and test results, process controls. Distribution of ammunition data cards, inspection and test results, process controls shall be sent to:

Commander
ARDEC
Picatinny Arsenal, NJ 07806-5000
ATTN: AMSMC-QAT-M (D)

6.7 Subject term (key word) listing.
Transfer Lead Assembly
Acceptor Lead Assembly
Slider Assembly

Custodian:
Army-AR

Preparing activity:
Army -AR

(Project 1345 -A516)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-70777	MUNITION FOR MINE, ANTI-PERSONNEL: M86 TRANSFER LEAD ASSEMBLY

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil – Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to pro suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Munitions &
Chemical Command
ATTN: AMSMC-QA
Picatinny Arsenal, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.