MILITARY SPECIFICATION

CAPACITORS, FIXED MICA DIELECTRIC, HIGH RELIABILITY

STYLE CMS04

This amendment forms a part of MIL-C-87164/1(USAF), dated 22 November 1982, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

TABLE I, delete and substitute:

" TABLE I. Dimensions.

Capacitance (pF)	L		T		W
	Min 1/	Max	Min 1/	Max	Max
1 to 24, incl.	.300(7.62)	.370(9.40)	.100(2.54)	.190(4.83)	.350(8.89)
27	.300(7.62)	.370(9.40)	.100(2.54)	.190(4.83)	.350(8.89)
30 to 68, incl.	.300(7.62)	.380(9.65)	.100(2.54)	.200(5.08)	.350(8.89)
75	.300(7.62)	.380(9.65)	.100(2.54)	.210(5.33)	.360(9.14)
82	.300(7.62)	.380(9.65)	.100(2.54)	.210(5.33)	.360(9.14)
91 and 100	.300(7.62)	.390(9.91)	.100(2.54)	.210(5.33)	.370(9.40)
110 and 120	.300(7.62)	.390(9.91)	.100(2.54)	.220(5.59)	.380(9.65)
130	.300(7.62)	.390(9.91)	.100(2.54)	.220(5.59)	.380(9.65)
150 and 160	.300(7.62)	.390(9.91)	.110(2.79)	.230(5.84)	.380(9.65)
180	.300(7.62)	.400(10.16)	.120(3.05)	.230(5.84)	.390(9.91)
200	.300(7.62)	.400(10.16)	.120(3.05)	.240(6.10)	.390(9.91)

1/ Minimum dimensions are listed for information only."

Custodian:
Air Force - 19

Review activities:
Air Force - 11
DLA - ES

Preparing activity:
Air Force - 19

Agent:
DLA - ES

(Project 5910-F407-1)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:54Z
Check the source to verify that this is the current version before use.