MILITARY SPECIFICATION

TRACTOR, FULL-TRACKED, DIESEL-ENGINE-DRIVEN, COMMERCIAL

This specification is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers diesel-engine-driven full-tracked tractors.

1.2 Classification.

1.2.1 Size. The tractors shall be of the size specified (see 6.2).

Size	Minimum Flywheel Horsepower	Minimum Tractor Weight	Minimum Drawbar Pounds Pull at 1.2 MPH
4	135	26,000	23,400
5	300	55,000	47,400

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATION

Military

MIL-T-3351	Tractor, Full-Tracked, Low-Speed; Tractor, Wheeled, Agricultural; and Tractor, Wheeled, Industrial; and Their Attachments, Packaging of

STANDARDS

Military

MIL-STD-129	Marking for Shipment and Storage

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: HQ AFLC CASO/LODSAC, Federal Center, Battle Creek, MI 49016 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:55Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

LAWS AND REGULATIONS

29CFR 1926.600	Equipment
29CFR 1926.602	Material Handling Equipment
29CFR 1926.604	Site Clearing

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal Agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

SOCIETY OF AUTOMOTIVE ENGINEERS

SAE Handbook

SAE J517	Hydraulic Hoses
SAE J524	Seamless Low Carbon Steel Tubing Annealed for Bending and Flaring
SAE J525	Welding and Cold Drawn Low Carbon Steel Tubing Annealed for Bending and Flaring
SAE J816b	Engine Test Code - Spark Ignition and Diesel
SAE J872a	Reserve Tractive Ability Test Code

(Application for copies should be addressed to the Society of Automotive Engineers, 485 Lexington Avenue, New York, NY 10017.)

3. REQUIREMENTS

3.1 Preproduction. Unless otherwise specified (see 6.2), the contractor shall furnish a complete tractor for inspection in accordance with Sections 4 and 6.

3.2 Design. The tractor shall be diesel-engine-driven, crawler type, and of the current commercial design. The tractor, accessories and allied equipment shall be conventional and designed for heavy construction. The tractor shall be complete with necessary operating accessories customarily furnished with tractors of this type whether stipulated herein or not, together with such modifications and attachments as may be necessary to enable the unit to function reliably and efficiently under sustained operation.

3.2.1 Safety. The tractor shall be fitted with safety devices or covers for all parts that present safety hazards to operating personnel. The device shall include, but shall not be limited to, guards for belts, pulleys, chains, gears and sprockets. All guards shall be designed to provide access to the guarded parts. Unless otherwise specified (see 6.2), the

Source: https://assist.dla.mil Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

tractor shall comply with 29CFR 1926.600, 29CFR 1926.602, and 29CFR 1926.604.

3.2.2 Materials. Recycled and recovered raw materials should be used to the maximum extent possible in lieu of virgin raw materials as long as these materials do not jeopardize the intended use and fully comply with all contract requirements. Materials used shall be free from defects which would affect the performance or maintainability of individual components of the overall assembly.

3.2.3 Lubrication. All bearings (except seal-for-life type), mating gears, and sliding parts shall be provided with means for lubrication. The reservoirs of splash type systems shall be fitted with a device for checking the oil level. All oil holes, grease fittings and filler caps shall be readily accessible.

3.2.4 Interchangeability. All parts shall be manufactured to such standards as will permit replacement or adjustment without modification of parts or tractor, accessories and allied equipment.

3.3 Construction. The tractor shall be complete so that it can be used for any operation for which it was designed. Construction shall be free from any characteristics or defects that will prevent the tractor or associated equipment from passing any of the examination(s) and tests in Section 4.

3.3.1 Painting. The tractor and equipment shall be painted in accordance with the manufacturer's commercial practice, except the finish color shall be as specified (see 6.2).

3.4 Temperature conditions. The tractor shall be capable of satisfactory performance in any ambient temperature up to and including 125°F for at least 4 hours to minus 10°F for at least three days when serviced in accordance with the manufacturer's recommendations. The tractor shall not be damaged by storage at any ambient temperature from plus 160°F for periods of 4 hours per day to minus 40°F for periods of at least three days duration.

3.4.1 Use conditions. Design and construction shall be such that the tractors will withstand the extremely hard usage encountered in service, such as operation over rough terrain, and storage and operation in the open air under all weather conditions for extended periods of time. Components particularly of the electrical, fuel and exhaust systems shall be so designed as to resist any harmful effects of dust or water.

3.5 Engine. The tractor shall be equipped with a commercial diesel engine which shall be the current production of a well established manufacturer. The engine shall be capable of producing not less than the specified horsepower (see 1.2.1).

3.5.1 Horsepower. The horsepower shall be that developed at the engine flywheel in accordance with SAE J816b.

3.5.2 Power and speed rating. The power and speed rating of the engine shall be such that operation of the tractor at specified drawbar pull and at the specified operating conditions will not require horsepower in excess of the intermittent brake horsepower of the engine for the applicable speed as established by the engine manufacturer's performance data. The governed

Source: https://assist.dla.mil Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

speed and power shall not exceed the highest speed and power for intermittent rated operation at which the engine was previously qualified by the engine manufacturer's performance data.

3.5.3 Governing system. The manufacturer's current governing system will be acceptable, providing it meets the following requirements:

a. The engine speed at any load between no load and full-rated load shall be not less than the full rated load speed and shall exceed the full-rated load speed by not more than ten percent.

b. The governor shall hold the engine speed constant to within one percent of operating speed for any constant load between no load and full load. Provision shall also be made for trimming the governed speed setting throughout the entire load range while the tractor is operating.

3.5.4 Engine starting system. The manufacturer's current commercial power starting system will be acceptable for cranking the tractor engine. The starter motor shall turn the engine at sufficient speed to start the engine at temperatures specified herein.

3.5.5 Engine cooling system. The manufacturer's current commercial cooling system will be acceptable; however, the system shall have adequate capacity to prevent overheating when operating under temperature conditions specified herein. The cooling system shall contain sufficient anti-freeze to assure protection down to minus 40°F.

3.5.6 Filters. All air, oil and fuel filters shall be replacement element type. Air filters shall be dry type and have a restriction indicator visible from the operator's seat.

3.6 Instruments. The tractor shall be equipped with the following instruments which shall be installed as specified:

a. Fuel gauge or dipstick

b. Engine lubricating oil pressure gauge

c. Engine cooling liquid temperature gauge

d. Ammeter or Voltmeter

e. Hourmeter

f. Torque converter temperature gauge

g. Brake system air pressure gauge and warning device (when applicable).

Additional instruments standard with the supplier's commercial practice which contribute to safety and dependability of the tractor operation shall be furnished. Instruments may be commercial standard providing they are weatherproof and dust-proof. They shall be of such accuracy and so mounted as to function under all operating conditions specified. All instruments, except the hourmeter and fuel gauge, shall be located on a panel fastened to the dash in a manner as to reduce shock and vibration. The hourmeter may be lo-

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

cated in the engine compartment. The fuel gauge may be located in the fuel tank.

3.7 Hydraulic torque converter. The engine to transmission drive shall be hydraulic, torque converter, single-stage oil type. The manufacturer's current production will be acceptable providing it meets the specified requirements. The torque converter components shall be capable of withstanding maximum torque output of the engine.

3.7.1 Transmission. The tractor shall be equipped with a transmission of the power-shift hydraulically actuated type. The manufacturer's current production will be acceptable; however, the transmission components shall have a torque capacity to withstand the maximum output of the torque converter. One forward speed range shall provide the specified drawbar pounds pull with weight and traction conditions specified herein. Any high reverse speed range which exceeds 5.4 mph must be blocked out.

3.7.2 Neutral start. An attachment or control mechanism shall be provided to prevent the engine from starting until the transmission is neutralized.

3.7.3 Final drive units. The manufacturer's current production of planetary final drives will be acceptable, providing the units shall be capable of withstanding full torque when operating in low gear. The sprockets shall have bolt-on, replaceable rim segments.

3.8 Fuel tank. The manufacturer's current commercial tank(s) will be acceptable, providing the tank(s) have adequate capacity for 10 hours operation. The tank(s) shall also have a readily accessible drain plug.

3.9 Steering devices. The steering shall be the manufacturer's current hydraulically actuated type with hydraulic steering clutches and brakes.

3.10 Track and assembly. Track links, pins, rollers, idlers, and bushings shall be heat-treated steel and they shall be replaceable and interchangeable. Recoil mechanisms shall be provided for cushioning the front idlers. The track bearings shall be constructed and arranged so as to eliminate, insofar as possible, damage to the bearings or bearing grease fittings as a result of tracking through sand, gravel, or other loose abrasive material. Hydraulic track adjusters shall be furnished. All lubricant reservoirs in the track system shall be provided with means for inspection and replenishment unless lifetime lubricated. The track links shall be of the sealed type. The track frames shall have 7 rollers on each side with lifetime roller seals and lubrication.

3.10.1 Track shoes and grousers. Track shoes and grousers shall be heat-treated steel offering a maximum resistance to wear and abrasion. Unless otherwise specified (see 6.2) the shoes and grouser widths shall be manufacturer's standard.

3.10.2 Track gauge. The track gauge shall be as follows:

a. Size 4 Not less than 74 inches

b. Size 5 Not less than 84 inches.

3.11 Lighting system. As a minimum, the lighting system shall consist of

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

the following:

a. Lights and circuits. The following lights with associated circuits, circuit-breakers, or other protective devices and switches shall be provided: Two headlights, one rear light, panel lighting, and cab light when cab is furnished.

b. Alternator. The alternator shall be the manufacturer's standard and shall be adequate to maintain the battery in a fully charged state under the operating conditions specified herein.

c. Battery. The battery shall be the manufacturer's standard of the type regularly furnished for cold starting to minus 25°F. Mounting shall permit ready accessibility for servicing, removing and replacement.

d. All lights shall be guarded or recessed to prevent damage from falling debris, tree limbs, and underbrush.

e. Floodlights. When specified (see 6.2) the tractor shall be equipped with four sealed beam adjustable floodlights, two mounted on the front forward of the operator's compartment; one on the left side and one on the right side of the tractor. Lights shall be located to provide adequate illumination of the blade and work area. The other two floodlights shall be mounted on the rear, one on the left side and one on the right side. The lights shall be located to illuminate the area in the rear of the tractor. The front and rear lights shall be controlled by two independent switches or a single multi-position switch mounted on the instrument panel.

3.12 Hydraulic system. The manufacturer's current production system will be acceptable providing it meets or exceeds the specified requirements. The system shall be fully protected from dirt and contamination and shall have sufficient capacity to insure fast acting control when fully loaded. The maximum working pressure shall be not more than 2300 pounds per square inch (psi). High pressure oil lines shall be steel tubing as far as practical and shall meet or exceed the requirements of SAE J524 or SAE J525. When hose is required, the hose assemblies shall meet or exceed the requirements of SAE J517.

3.12.1 Pump. The pumps shall be piston, gear or vane type and shall be directly connected to the engine or input shaft of the torque converter.

3.12.2 Hydraulic cylinder. Each cylinder shall have a stroke of sufficient length to position the components as specified herein.

3.12.3 Piston rods. The exposed surface of the piston rods shall be hard chrome plated in accordance with the manufacturer's standard practice.

3.12.4 Reservoir. The reservoir shall be protected against the entrance of dirt or other foreign material. Design of the reservoir shall include a means for checking its fluid level. An air-breather filter shall be furnished except when a closed system is provided. A magnetic drain plug, a doughnut-type magnet, or magnets on the strainer shall be provided in the reservoir.

3.12.5 Controls. All controls shall be mounted in or near the operator's

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

compartment so that the operator can, in a normal seated position, control all functions of the tractor.

3.13 Drawbar pounds pull. The tractors shall be capable of delivering not less than the drawbar pull specified in 1.2.1. The pull shall be reserve tractive force as defined in SAE J872 and shall be available after drive power losses at a minimum calculated tracklaying ground speed of 1.2 mph with a track drag resistance not less than 100 pounds per ton of tractor operating weight at 0.9 coefficient of traction.

3.13.1 Tractor test weight. The tractor test weight shall be not less than the weight specified in 1.2.1, and shall represent tractor with fuel, coolant, operator and manufacturer's standard track shoes. It shall include not more than the following manufacturer's standard accessory attachments: radiator guard, track and sprocket guards, crankcase guard, front pull hook, drawbar, lighting, hydraulic system and hydraulic lift cylinders.

3.14 Operator's seat. The operator's seat shall be located so as to assure easy operation of the tractor and to permit comfortable riding position or positions.

3.15 Tiedown devices. The tractors shall be provided with suitable, permanently attached devices to permit tiedown of the tractor to the floor or deck of the transportation medium. The tiedown devices shall be of such design, location, and number as to enable the tractor to be anchored in such a manner as to prevent shifting or movement in any direction. The devices shall be designed to withstand thrusts of the following magnitudes: Forward thrust 8G (G=weight of unit); rearward thrust 8G; upward thrust 2-1/4G; and sideward thrust 1-1/2G. The tiedown devices shall be located so as to permit easy attachment of cables or turnbuckles. Tiedown devices shall be indicated by a suitable information plate, by stenciling, or other suitable marking of the machine. The marking shall clearly indicate that the device is intended for tiedown of the machine on the carrier when shipped.

3.16 Accessories. The tractors shall be furnished with the following accessories:

a. Track roller rock shields

b. Sprocket rock shields

c. Front pull hook

d. Rear pull device (drawbar type). Not applicable to tractors equipped with hydraulic rippers.

e. Hydraulic unit to control hydraulic mounted equipment

h. Solid cast or forged equalizer suspension bar

i. Standard semi-U hydraulic-controlled blade with hydraulic tilt

j. Transmission Case Guard

k. Reversible Engine Fan

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

3.17 Attachments. When specified (see 6.2) the tractors shall be furnished with any of the following attachments:

a. Three-shank, hydraulic controlled ripper capable of a 28-inch ripping depth

b. Winch assembly controlled from the cab or canopy with a 113,000 pound line pull, 225 feet of 1-1/8 inch cable with hook and clevix

c. Standard "ROPS" canopy

d. Standard semi-U, dozer-blade reinforcement pusher plate(s)

3.18 Winterization. Unless otherwise specified (see 6.2), a standard "ROPS" cab with mounting parts, heater and piping, defroster, two dome lights and three window wipers (2 front and 1 right hand rear) shall be required. Additionally, these tractors are to be equipped with engine enclosure attachment, boots for brake pedal and governor control level and lubricants, greases and antifreeze for -40 degrees F operation. Starting aids shall permit engine starts down to -25 degrees F. Also, the tractor should be equipped with radiator shutters if required to meet winterization requirements specified herein.

3.19 Tools and lubricating equipment. Tools normally furnished with the tractor by the manufacturer shall be provided together with the manufacturer's regular tool storage space or box. The manufacturer shall furnish greasing equipment necessary to service all fittings.

3.20 Identification Marking. A corrosion resistant metal nameplate, permanently and legibly marked with the following information in accordance with MIL-STD-130 shall be securely attached to each tractor:

Nomenclature
Manufacturer's Model Number
Manufacturer's Serial Number
Special Characteristics, HP, RPM, etc
National Stock Number
Manufacturer's Name
Contract Number
Date of Manufacture
Weight
Height Width Length Cube
Center of Gravity
US.

3.21 Lubrication identification. Two lubrication charts and one plate or decal shall be furnished. The plate shall be securely attached to each tractor and the charts shall be placed in a plastic folder or laminated between clear plastic. The following information shall be furnished on the charts and plate:

Points of application
Service interval
Type of lubricant
Federal of Military Specification Number (IF AVAILABLE).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

3.22 Workmanship. Workmanship of the tractor, allied equipment, and accessories shall be of the quality prevailing among manufacturers normally producing equipment of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. Inspection shall be classified as follows:

a. Preproduction inspection

b. Quality conformance inspection.

4.2.1 Preproduction inspection. Preproduction inspection shall be applied to the preproduction sample submitted in accordance with 3.1. Failure of the preproduction sample to pass the examination or one or more preproduction tests shall be cause for rejection. Preproduction inspection shall consist of the examination in 4.3 and all tests in 4.4.

4.2.2 Quality conformance inspection. Quality conformance inspection shall be applied to each item prior to being offered for acceptance under the contract. Failure of the machine to pass the examination or one or more tests shall be cause for rejection. Quality conformance inspection shall consist of the following:

a. Examination (4.3)

b. Tests (4.4.1)

c. Inspection of preservation, packaging, packing and marking for shipment and storage (4.5).

4.3 Examination. The tractor and equipment shall be examined for design, construction, materials, components, electrical equipment, and workmanship to determine compliance with the requirements of this specification. Any deviation from these requirements shall be cause for rejection.

4.4 Tests.

4.4.1 Operational test. Each tractor produced in fulfillment of the contract or order shall be completely assembled, adjusted, lubricated and otherwise serviced for operation. Engine shall be started and after having been subjected to a warm-up period, a run-in test shall be conducted in accordance with the manufacturer's recommendations. During the operational test, all controls, adjusting mechanisms, and other accessories shall be operated sufficiently to insure against restrictions or malfunction. Failure to pass any phase of this test shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

4.4.2 Reserve tractive ability. Reserve tractive force of the tractor shall be tested in accordance with SAE J872. Failure to comply with 3.13 shall be cause for rejection.

4.4.3 Environmental test. The supplier shall furnish a certification that his equipment will perform satisfactorily at the specified temperatures, and will not be damaged from storage under the specified temperatures (see 3.4).

4.4.4 Tiedown device test. The weight of the tractor shall be determined. Each tiedown device shall be subjected to its proportionate share of the forward, rearward, upward, and sideward thrusts specified in 3.15. Thrust measurements shall be made with a dynamometer or other suitable accurate measuring devices. There shall be no separation, permanent deformation, or breakage of any tiedown device or any other part of the tractor. Manufacturer's certified engineering calculations will be acceptable in lieu of the foregoing tiedown device test.

4.4.5 Flywheel horsepower test. The engine horsepower shall be tested as stated in 3.5.1. Failure to meet the horsepower requirements shall be cause for rejection. At the manufacturer's option, compliance with the horsepower specified in 1.2.1 may be determined from his certified power curve, verified by regular production dynamometer tests with standard allowance for friction variations in new engines and power deductions for fan, generator or alternator and water pumps, if not on engine during tests, in lieu of the horsepower test as stated in 3.5.1.

4.5 Inspection of preservation, packaging, packing and marking for shipment and storage. The preservation, packaging, packing, and marking shall be inspected to verify conformance to the requirements of Section 5.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. The preservation and packaging shall be Level A or C, as specified (see 6.2).

5.1.1 Level A. The complete tractor shall be preserved and packaged in accordance with the Level A, Type KK, unboxed (mobile) requirements of Specification MIL-T-3351.

5.1.2 Level C. The complete tractor shall be preserved and packaged in accordance with the supplier's standard commercial practice.

5.2 Packing. The packing shall be Level A, B, or C as specified (see 6.2).

5.2.1 Level A. The complete tractor shall be packed in accordance with the Level A, Type II, unboxed (mobile) requirements of Specification MIL-T-3351.

5.2.2 Level B. The complete tractor shall be packed in accordance with the Level B, Type II, unboxed (mobile) requirements of Specification MIL-T-3351.

5.2.3 Level C. The complete tractor shall be packed or prepared for shipment in a manner to insure arrival at destination in satisfactory condition and which will be acceptable to carriers at lowest rates.

5.3 Marking. The tractor attachments, interior packages, and shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The tractor is intended primarily for use in bulldozing in land leveling, road construction and sanitary rehabilitation programs.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of specification

b. Size of tractor required (see 1.2.1)

c. Preproduction sample (3.1)

d. Painting finish color required (see 3.3.1)

e. Tract shoes and grouser widths if different (see 3.10.1)

f. Floodlights if required (see 3.11e)

g. Attachments if required (see 3.17)

h. If winterization required is different from that specified herein (see 3.18)

i. Level of preservation and packaging, and level of packing required (see 5.1 and 5.2)

j. If tractor is not required to comply with 29CFR 1926.600, 29CFR 1926.602 or 29CFR 1926.604 (see 3.2.1)

k. Paint type, if different from specified herein (see 3.3.1)

l. Finish color required (see 3.3.1)

6.3 Preproduction sample. The sample may be a preproduction item or a production item which meets the requirements of this specification. In either case, the sample shall be identical with the proposed item and shall be made or shall have been made by the methods that are to be used or were used in production of items to fulfill the terms of the contract. The preproduction sample may be shipped as part of the contract. Approval of a preproduction sample shall not relieve the contractor of the responsibility to furnish equipment in accordance with the requirements of this specification.

Custodian:

Air Force - 99

Preparing Activity

Air Force - 99

Project No.

2410-F039

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE
MIL-T-83978A Tractor, Full-Tracked, Diesel-Engine-Driven, Commercial

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 PREVIOUS EDITION WILL BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:55Z
Check the source to verify that this is the current version before use.