[INCH-POUND]
A-A-55559/1
August 31, 1995

COMMERCIAL ITEM DESCRIPTION

TAPE, ELECTRONIC DATA PROCESSING, UNFORMATTED, 6.35 MILLIMETER (MM) (.25 INCH (IN)) WIDE, IN A 5.25-INCH FORM FACTOR DATA CARTRIDGE

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.

1 SCOPE This CID covers the general requirements for a 6.35 mm (.25 inch) wide electronic data processing tape in a 5.25-inch form factor data cartridge. Electronic data processing tapes covered by this CID are intended for commercial/industrial applications.

2 CLASSIFICATION This CID uses a classification system which is included in the Part or Identification Number (PIN) as shown in the following example (see 6.1)

AA55559/01 - 001

AA55559/01: CID number
001: Dash number (see table I)

3 SALIENT CHARACTERISTICS

3.1 Design and construction. Electronic data processing tape supplied to this CID shall be as specified herein, and meet the corresponding industry standard specified in table I

3.2 Tape format. This electronic data processing tape shall be unformatted.

3.3 Overall cartridge dimensions The cartridge dimensions shall be 152.4 ±0.13 mm (6.00 inches ±.005 inch long x 101.6 mm ±0 13 mm (4.00 inches ±.005 inch) wide x 16.89 ±0 13 (.665 inch ±.005 inch) high

3 4 Tape width and tolerance The tape width and tolerance shall be 6.274 ±0.013 mm (.2470 inch ±.0005 inch)

3.5 Tape length The tape length shall be as specified in table I

3.6 Operating Temperature The operating ambient temperature shall be +5° Celsius (C) to +45°C (+41° fahrenheit (F) to +113°F).

3 7 Operating relative humidity The operating relative humidity shall be 20 percent to 80 percent non-condensing

3.8 Dewpoint temperature The maximum dewpoint temperature shall be +29°C (+84°F)

3 9 Storage Temperature The storage temperature shall be +5° Celsius (C) to +45°C (+23° F to +113°F)

3 10 Storage relative humidity The storage relative humidity shall be 20 percent to 80 percent non-condensing

3 11 Maximum wet bulb temperature The maximum wet bulb temperature shall be +26°C (+79°F)

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to. Defense Electronics Supply Center, ATTN: DESC-ELDM, 1507 Wilmington Pike, Dayton, OH 45444-5765, or telephone (513) 296-6189, or facsimile (FAX) (513) 296-8868.

AMSC N/A FSC 7045
DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:52Z
Check the source to verify that this is the current version before use.

TABLE I Characteristics

CID PIN AA55559/01-	Cartridge type	Cartridge industry standard	Native formatted memory capacity	Minimum tape length feet (ft)	Tape speed coercivity (oersteds)
-001	DC300A	ANSI X3.55	2 9 Megabyte (Mb)	300	300
-002	DC300XL	ANSI X3 55	45 Mb	450	300
-003	DC300XLP	ANSI X3 127	45 Mb	450	300
-004	DC600A	ANSI X3 55	60 Mb	600	550
-005	DC600HW	ANSI X3 55	60 Mb	600	550
-006	DC615A	ANSI X3 55	15 Mb	150	550
-007	DC6037	ANSI X3.235 1/	37 Mb	155	550
-008	DC6080	ANSI X3 251 1/	80 Mb	155	550
-009	DC6081	ANSI X3 251 1/	80 Mb	155	550
-010	DC6150	ANSI X3 235 1/	150 Mb	620	550
-011	DC6250	ANSI X3.235 1/	250 Mb	1,020	550
-012	DC6320	ANSI X3.251 1/	320 Mb	620	550
-013	DC6525	ANSI X3.251 1/	525 Mb	1,020	550
-014	DC9100	QIC-136	1 Gigabyte (Gb)	760	900
-015	DC9120	QIC-136	1 2 Gb	760	900
-016	DC9135	QIC-137	1.35 Gb	760	900
-017	DC9200	QIC-136	2 Gb	950	900
-018	DC9250	QIC-136	2.5 Gb	1,200	900
-019	DC9500	QIC-137	5 Gb	1,200	900

1/ Not approved as of the date of this document, shown for reference only

3 12 Flammability The materials used in the external cartridge covers must have a flammability rating of at least UL 94V-2

3.13 Used or reconditioned material. A manufacturer shall not furnish any electronic data processing tape which is used or reconditioned or is comprised of used or reconditioned material

3 14 Marking Electronic data processing tape supplied to this CID shall be marked with the manufacturer's standard commercial PIN

4. QUALITY ASSURANCE PROVISIONS. Quality assurance provisions shall be as specified in A-A-55559

5. PACKAGING Packaging shall be as specified in A-A-55559.

6. NOTES

6.1 PIN. The PIN should be used for Government purposes to buy commercial products to this CID. See section 2 for PIN format example

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:52Z
Check the source to verify that this is the current version before use.

6 2 CAGE code For ordering purposes, inventory control, and submission of these instruments to DESC under the Military Parts Control Advisory Group (MPCAG) evaluation program, CAGE code 58536 should be used

6 3 Source of documents

Commercial Item Description

A-A-55559 - Tape, Electronic Data Processing, Cartridge, General Specification for

(Copies of commercial item descriptions are available from the Defense Printing Service Detachment Office, Building 4D (Customer Service), 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Other Publications

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI X3.55 - Unrecorded Magnetic Tape Cartridge for Information Interchange - 0.250 Inch (6.30 mm), 1600 bpi (63 bpmm), Phase Encoded.

ANSI X3 127 - Unrecorded Magnetic Tape Cartridge for Information Interchange - 0.250 Inch (6.30 mm), 6400-10000 ftpi (252-394 ftpmm)

ANSI X3 235 - Unrecorded Magnetic Tape Cartridge for Information Interchange, 0 25 in (6.30 mm), 10,000-12,500 ftpi (394-492 ftpmm), Coercivity 550 Oe (44,000 amperes/meter), (Types 6150, 6250, 6037)

ANSI X3.251 - Unrecorded Magnetic Tape Cartridge for Information Interchange, 0.25 in (6 30 mm), 20,000 ftpi (787 ftpmm), Coercivity 550 Oersteds (44,000 amperes/meter), (Types 6320, 6525, 6080, 6081)

(Applications for copies should be addressed to the American National Standards Institute, 11 West 42nd Street, New York, NY 10036-8002.)

QUARTER-INCH CARTRIDGE DRIVE STANDARDS, INCORPORATED (QIC)

QIC-136 - Unrecorded Magnetic Tape Cartridge for Information Interchange, 0.25 inch (6.35 mm) tape width, 900 Oersteds (72000 amperes/meter) for 5.25-inch form factor tape drives Intended for use with QIC-1000-DC or QIC-2GB-DC recording formats.

QIC-137 - Unrecorded Magnetic Tape Cartridge for Information Interchange, 0.25 inch (6.35 mm) tape width, 900 Oersteds (72000 amperes/meter) for 5.25-inch form factor tape drives Intended for use with QIC-1350-DC, QIC-2100-DC, or QIC-5GB-DC recording formats

QIC-139 - Unformatted Servo-written Magnetic Tape Cartridge for Information Interchange, 0.25 inch (6.35 mm), 5.25-inch form factor, 50800 ftpi (2000 ftpmm), 900 Oersteds (72000 amperes/meter) Intended for use with QIC-5010-DC recording format

(Applications for copies should be addressed to the Quarter-Inch Cartridge Drive Standards, Incorporated, 311 East Carrillo Street, Santa Barbara, CA 93101

(Industry association specifications and standards are generally available for reference from libraries They are also distributed among technical groups and using Federal agencies)

6 4 Government users To acquire information on obtaining these electronic data processing tapes from the Government inventory system, contact Defense Electronics Supply Center, ATTN DESC-EOC, 1507 Wilmington Pike, Dayton, OH 45444, or telephone (513) 296-5625

6 5 Ordering data. Ordering data shall be as specified in A-A-55559

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:52Z
Check the source to verify that this is the current version before use.

6 6 Suggested sources of supply Suggested sources of supply are listed below Additional sources will be added as they become available

CID dash number (see table I) AA55559/01-	Vendor commercial PIN CAGE OCEN9	Vendor commercial PIN CAGE 00A14	Vendor commercial PIN CAGE OEGZ7	Vendor commercial PIN CAGE 52327
001	---	---	---	DC300A
002	---	---	14418	DC300XLP
003	PL300XLP	G0-10061	14419	DC300XLP
004	PL600A	G0-10063	14016	DC600A
005	---	---	---	DC600HW
006	---	---	---	DC615A
007	---	---	---	DC6037
008	---	---	---	DC6080
009	---	---	---	DC6081
010	PL6150	G0-10065	14018	DC6150
011	PL6250	G0-10066	14435	DC6250
012	PL6320	G0-10067	14437	DC6320
013	PL6525	G0-10068	14438	DC6525
014	PL9100	G0 10073	36040	DC9100
015	PL9120	G0-10114	38296	DC9120
016	---	G0-10071	36041	DC9135
017	PL9200	G0-10080	38298	DC9200
018	---	---	---	DC9250
019	---	---	---	DC9500

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:52Z
Check the source to verify that this is the current version before use.

Vendor CAGE number	Vendor name and address
0CEN9	Syncom Technologies, Incorporated 1000 Syncom Drive Mitchell, SD 57301-4767 (800) 843-9862
0DA14	Anacomp Incorporated 1155 Western Avenue Cincinnati, OH 45203-1123 (203) 647-7646
0EGZ7	BASF Corporation Information Systems Division 35 Crosby Drive Bedford, MA 01730-1471 (703) 642-1551
52327	Minnesota Mining And Manufacturing Company Data Storage Products Division 3M Center, 224-5N-39 St Paul, MN 55144-1000 (805) 388-4029

CIVIL AGENCY COORDINATING ACTIVITY

GSA - KMR

Preparing Activity

DLA-ES

Project 7045-0022-01

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:52Z
Check the source to verify that this is the current version before use.