MILITARY SPECIFICATION SHEET

CABLE, SPECIAL PURPOSE, ELECTRICAL, MULTICONDUCTOR, (3 CONDUCTORS) AND SINGLE SHIELDED M27072/61GEDD*

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the cable described herein shall consist of this specification and the latest issue of MIL-C-27072.




FIGURE 1. Cable configuration.

* Jacket compound is clear with no additional color coding.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:51Z
Check the source to verify that this is the current version before use.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

DESIGN DATA:

Design and construction: See figure 1.

Number of conductors: Three.

Conductor size and stranding: See table I.

Wire: In accordance with M16878/5BHE*** (see table I).

Jacket undershield: Not applicable.

Shielding: Silver coated copper 36 AWG.

Sheath: Fluorinated ethylene propylene.

Temperature rating: 200°C.

REQUIREMENTS:

Visual and dimensional:

Basic wire: In accordance with M16878/5BHE*** or M16878/22BHE*** (see table I).

Components:

Filler: Applicable.

Lay: 3 inches maximum.

Tape material: Not applicable.

Shield:

Material: Silver coated copper.

Braid angle: 20 to 40 degrees.

Gauge: 36 AWG.

Workmanship: In accordance with MIL-C-27072.

Colors:

Black.

Red.

White

Sheath:

Material: Fluorinated ethylene propylene.

Wall thickness: .010 inch.

Tensile strength: 2200 pound-force per square inch minimum.

Elongation: 200 percent, minimum.

Tension set: Not applicable.

Tear strength: Not applicable.

Accelerated aging: Not applicable.

Oil resistance: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:51Z
Check the source to verify that this is the current version before use.

Color: See table IV of MIL-C-27072.

Finished cable:

Diameter: .213 inch nominal.

Dielectric strength: In accordance with MIL-W-16878/5 or MIL-W-16878/22.

Cold bend: Mandrel size in accordance with table XIII of MIL-C-27072.

Ozone: Mandrel size in accordance with table XIV of MIL-C-27072.

TABLE I. Construction data.

Part number M27072/61	Conductor				Finished cable diameter (in.) ±10%	Basic wire M16878/5 M16878/22
	Wire size (AWG)	Number of strands	Strand size (AWG)	Nominal diameter (in.)		
GEDD*	18	19	30	.079	.213	BHE***

Asterisks (*) shall be replaced by the appropriate color designator.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians:
Army - CR
Navy - SH
Air Force - 85

Review activities:
Air Force - 99
DLA - ES, IS

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 6145-0908-12)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:51Z
Check the source to verify that this is the current version before use.