MILITARY SPECIFICATION SHEET

CABLE, SPECIAL PURPOSE, ELECTRICAL, MULTICONDUCTOR, (7 CONDUCTORS) AND SINGLE SHIELDED M27072/66LDDD*

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the cable described herein shall consist of this specification and the latest issue of MIL-C-27072.




FIGURE 1. Cable configuration.

* The complete part number requires a color code designator (see table I).

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil - Downloaded: 2026-10-20T10:53Z
Check the source to verify that this is the correct version before use.

DESIGN DATA:

Design and construction: See figure 1.

Number of conductors: Seven.

Conductor size and stranding: See table I.

Wire: In accordance with M16878/BFE* (see table I).

Jacket undershield: Not applicable.

Shielding: Silver coated copper.

Sheath: Fluorinated ethylene propylene.

Temperature rating: 200°C.

REQUIREMENTS:

Visual and dimensional:

Components:

Basic wire: Silver coated copper.

Dimension: See table I.

Primary insulation:

Material: Polytetrafluoroethylene.

Wall thickness: .014 inch ±.002.

Colors:

Black.

Blue.

Brown.

Green.

Red.

White.

Yellow.

Spark test voltage: 5,000 V rms.

Inspection test voltage: 3,000 V rms.

Impulse dielectric test: 8,000 V peak.

Jacket over insulation: Not applicable.

Wall thickness: Not applicable.

Color: Not applicable.

Cabling:

Core:

Number of conductors: One.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:53Z
Check the source to verify that this is the current version before use.

Pitch or lay: Pull in straight.

First Layer:

Number of conductors: Six.

Pitch or lay: 2.75 inches maximum.

Tape material: Polytetrafluoroethylene.

Shield:

Material: Silver coated copper.

Gauge: 36 AWG.

Braid angle: 20 to 40 degrees.

Workmanship: In accordance with MIL-C-27072.

Sheath:

Material: Fluorinated ethylene propylene.

Wall thickness: .015 inch nominal.

Tensile strength: See table V of MIL-C-27072.

Elongation: See table V of MIL-C-27072.

Tension set: Not applicable.

Tear strength: Not applicable.

Accelerated aging: Not applicable.

Oil resistance: Not applicable.

Color: See table IV of MIL-C-27072.

Finished cable:

Diameter: See table I.

Conductor resistance: In accordance with MIL-W-16878/4 or MIL-W-16878/21.

Dielectric strength: In accordance with MIL-W-16878/4 or MIL-W-16878/21.

Cold bend: Mandrel size in accordance with table XIII of MIL-C-27072.

Ozone: Mandrel size in accordance with table XIV of MIL-C-27072.

Marking durability: In accordance with MIL-C-27072.

Heat stability: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:53Z
Check the source to verify that this is the current version before use.

TABLE I. Construction data.

Part number M27072/66	Conductor				Finished cable diameter (in.) ±10%	Basic wire M16878/4 M16878/21
	Wire size (AWG)	Number of strands	Strand size (AWG)	Nominal diameter (in.)		
LDDD*	22	19	34	.060	.250	BFE***

Asterisks (*) shall be replaced by the appropriate color designator.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians:
Army - CR
Navy - SH
Air Force - 85

Review activities:
Air Force - 99
DLA - ES, IS

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 6145-0908-15)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:53Z
Check the source to verify that this is the current version before use.