MILITARY SPECIFICATION SHEET

CABLE, SPECIAL PURPOSE, ELECTRICAL, MULTICONDUCTOR, (3 CONDUCTORS) AND SINGLE SHIELDED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the cable described herein shall consist of this specification and the latest issue of MIL-C-27072.




FIGURE 1. Cable configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:56Z
Check the source to verify that this is the current version before use.

DESIGN DATA:

Design and construction: See figure 1.

Number of conductors: Three.

Conductor size and stranding: See table I.

Wire: In accordance with M16878/4 (see table I for complete part number).

Jacket undershield: Not applicable.

Shielding: Silver coated copper.

Sheath: Polytetrafluoroethylene.

Temperature rating: 200°C.

REQUIREMENTS:

Visual and dimensional:

Components:

Basic wire: Silver coated copper.

Dimension: See table I.

Primary insulation:

Material: Polytetrafluoroethylene.

Colors:

White.

Black.

Red.

Spark test voltage: 3,400 V rms.

Inspection test voltage: 2,000 V rms.

Impulse dielectric test: 6,500 V peak.

Shield:

Material: Silver coated copper.

Construction: See table I.

Braid angle: 20 to 40 degrees.

Workmanship: In accordance with MIL-C-27072.

Sheath:

Material: Polytetrafluoroethylene.

Wall thickness: .010 inch ±.002.

Tensile strength: In accordance with table V of MIL-C-27072.

Elongation: In accordance with table V of MIL-C-27072.

Tension set: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:56Z
Check the source to verify that this is the current version before use.

Tear strength: Not applicable.

Accelerated aging: Not applicable.

Oil resistance: Not applicable.

Surface resistance (sheath): When tested in accordance with method 6041 of FED-STD-228, the initial surface resistance shall be not less than 5 megohms. The final surface resistance shall be within 50 percent of the initial surface resistance. (NOTE: The specimen for this inspection test shall not be subjected to any other electrical tests.)

Color: See table IV of MIL-C-27072.

Finished cable:

Diameter: In accordance with table I.

Conductor resistance: In accordance with MIL-W-16878/4 or MIL-W-16878/21.

Dielectric strength: In accordance with MIL-W-16878/4 or MIL-W-16878/21.

Cold bend: Mandrel size in accordance with table XIII of MIL-C-27072.

Ozone: Mandrel size in accordance with table XIV of MIL-C-27072.

Heat resistance: A specimen of finished cable shall be subjected to 250°C ±5°C in an air oven for 96 hours minimum. It shall be removed from the oven and allowed to cool to room temperature. After 1 hour at room temperature, the insulation and jacket shall be checked for shrinkage of not more than .125 inch. The specimen shall then be wound 5 close turns around a mandrel of 10 times the cable diameter. In this position, the specimen shall be subjected to the dielectric strength test. If the cable fails the dielectric strength test or shrinks more than .125 inch, the lot shall be rejected.

TABLE I. Dimensions.

Part number M27072/89	Conductor AWG	Conductor Stranding (AWG)	Conductor Nom. dia. (in.)	Nom. cable lay	Shield parameters 1/ d	Shield parameters 1/ L	Shield parameters 1/ N	Shield parameters 1/ P	Shield parameters 1/ D	Finished cable dia. (in.) Min.	Finished cable dia. (in.) Max.	Approx. weight per 1000 ft (lb)	Basic wire M16878/4 M16878/21
TDDE*	28	7/36	.015	1.00	.005	18	4	18	.084	.101	.113	12.9	BC8***
SDDE*	26	7/34	.0189	1.10	.005	18	5	17	.093	.114	.126	16.2	BD8***
WDDE*	24	19/36	.0248	1.25	.005	18	5	16	.103	.123	.137	18.9	BEE***
LDDE*	22	19/34	.0312	1.40	.005	16	5	15	.116	.135	.149	23.2	BFE***
JDDE*	20	19/32	.0396	1.60	.005	16	6	13	.133	.150	.166	29.7	BGE***
GDDE*	18	19/30	.0495	1.90	.005	16	8	12	.159	.171	.189	39.9	BHE***
FDDE*	16	19/29	.057	2.20	.005	16	7	10	.187	.192	.212	48.6	BJE***

1/ See MIL-C-27072, overall shielding. Optional shields are acceptable that meet the requirements of MIL-C-27072.

Asterisks (*) shall be replaced with the appropriate color designator.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians:
Army - CR
Navy - SH
Air Force - 85

Review activities:
Air Force - 99
DLA - ES, IS

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 6145-0908-19)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:56Z
Check the source to verify that this is the current version before use.