MILITARY SPECIFICATION SHEET

CABLE, ELECTRICAL, 125 VOLTS, TYPE TRXF

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the cable described herein shall consist of this document and the latest issue of Specification MIL-C-915.

REQUIREMENTS:

Qualification not required.

Construction

First - Copper conductor, uncoated, (see Details for size).
Second - Separator.
Third - Polychloroprene jacket, (see Details for dimensions).

Details

Type and Size	Conductor size, Navy standard	Overall diameter maximum (inch)	Conductor resistance per 1000 ft. maximum (ohms)
TRXF-84	84(2107)	0.60	0.138
TRXF-105	105(2646)	.68	.108
TRXF-133	133(3325)	.75	.0876

EXAMINATION AND TESTS:

	Requirements:
Basic electrical:	
(D) Conductor resistance - Ohms/1000 ft. at 25°C., maximum	(see Details)
(D) Voltage withstand - Conductor to ground, volts, rms, minimum	1200
Group A:	
Visual and dimensional	
Group B:	
Cold bending, cable - At minus 30° ± 2°C., two turns around mandrel with diameter twice that of specimen	No damage
Physicals (unaged)	
Jacket (cable)	
Tensile strength - psi, minimum	1800
Elongation - Percent, minimum	300
Set - Inch, maximum	3/8

(D) Denotes changes

FSC 6145

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:08Z
Check the source to verify that this is the current version before use.

	Requirements:
Group C:	
Flammability - Inches, maximum	2
Physicals (aged)	
Jacket (cable)	
Air pressure heat	
Tensile strength - Percent of unaged, minimum	50
Elongation - Percent of unaged, minimum	50
Hot oil immersion	
Tensile strength - Percent of unaged, minimum	60
Elongation - Percent of unaged, minimum	60

UNIT ORDERING LENGTHS:

All sizes 1000 feet (nominal)

Custodians:
Army - MI
Navy - SH
Air Force - 80

Review activities:
Army - EL, MI, AV
Navy - EC
Air Force - 80

User activities:
Army - ME, MU, WC
Navy - CG

Preparing activity:
Navy - SH
(Project 6145-0648-22)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:08Z
Check the source to verify that this is the current version before use.