MIL-C-915/22G
18 June 1985
SUPERSEDING
MIL-C-00915/22F(SH)
25 January 1982
MIL-C-915/22E
30 May 1980

MILITARY SPECIFICATION SHEET

CABLE, ELECTRICAL, 300 VOLTS, TYPE TSP (INCLUDING VARIATION TYPE TSPA)

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the cable described herein shall consist of this document and the latest issue of MIL-C-915.

This cable can be manufactured in two variations: TSP (unarmored) and TSPA (armored).

REQUIREMENTS:

Qualification required.

Construction (watertight)

First - *Copper conductor*, AWG size 22, class K stranding, tin coated.
Second - Polyvinyl chloride insulation (80°C). Nominal wall thickness 0.015 inch. Telephone identification code applied by method 3.
Third - Two conductors cabled together to form a pair with a lay not greater than 2-1/2 inches.
Fourth - The specified number of pairs (see table I) cabled with a lay not greater than 10 inches in the outer layer. Non-fibrous fillers shall be employed. Cabling sequence shall be consecutive, starting with pair no. 1, from center outward.
Fifth - Binder tape applied helically with overlap.

Construction variant for type TSP

Sixth - Special thermoplastic jacket (gray). Nominal wall thickness 0.080 inch. Cable surface marking required.

FSC 6145

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 202640-16T12:08Z
Check the source to verify that this is the currentversion before use.

Construction variant for type TSPA

Sixth - Special thermoplastic jacket (gray). Nominal wall thickness 0.080 inch.
Seventh - Braided metal armor and paint.

TABLE I. Details.

Size 1/	Number of pairs	Overall diameter (inches)			
		Type TSP		Type TSPA	
		min	max	min	max
11	11	0.680	0.730	0.730	0.785
31	31	.982	1.062	1.032	1.112

1/ Type TSP and TSPA.

EXAMINATION AND TESTS:

	Requirements
Basic electrical:	
Conductor resistance - ohms/1000 feet at 25°C, maximum..	18.73
Voltage withstand - volts, root mean square, minimum	
Conductor to conductor.....	2000
Conductor to water.....	1000
Insulation resistance - megohms/1000 feet, minimum	
Conductor to conductor and conductor to water (TSP only).....	100
Conductor to conductor and conductor to armor (TSPA only).....	100
Group A:	
Visual and dimensional.....	No failure
Watertightness - see MIL-C-915, table XXII, for limits of water leakage.....	No failure
Group B:	
Physicals (unaged)	
Insulation (conductor)	
Tensile strength - lbf/in^2, minimum.....	1800
Elongation - percent, minimum.....	125
Jacket (cable)	
Tensile strength - lbf/in^2, minimum.....	2300
Elongation - percent, minimum.....	250
Drip - at 95 ± 1°C.....	Zero

Source: https://assist.dla.mil -- Downloaded: 202610-16T12:08Z
Check the source to verify that this is the current version before use.

EXAMINATION AND TESTS: (Continued)

	Requirements
Group C:	
Flammability - inches, maximum	2
Physicals (aged)	
Insulation (conductor)	
Air oven	
Elongation - percent of unaged, minimum	80
Jacket (cable)	
Air oven (168 hours at 136°C)	
Tensile strength - percent of unaged, minimum	80
Elongation - percent of unaged, minimum	60
Hot oil immersion	
Tensile strength - percent of unaged, minimum	75
Elongation - percent of unaged, minimum	50
Permanence of printing, type TSP only, (jacket) - cycles, minimum	250
Cable filler removability	No failure
Armor - conformance to material construction and coverage (type TSPA only)	No failure

QUALIFICATION INSPECTION:

Qualification inspection shall include basic electrical, all of groups A, B, and C, plus the following:

Cable aging and compatibility (95 ± 3°C)	No failure
Flame propagation	No failure
Jacket durometer (type A) hardness, minimum	80

UNIT ORDERING LENGTHS:

Size	Feet (nominal)
11	2500
31	1000

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:08Z
Check the source to verify that this is the current version before use.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Note: Not for Air Force use.

Custodians:
Army - MI
Navy - SH

Preparing activity:
Navy - SH
(Project 6145-0885-20)

Review activities:
Army - CR, ER
Navy - EC
DLA - IS

User activities:
Army - AL, AR, ME
Navy - CG

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:08Z
Check the source to verify that this is the current version before use.